





RBCOMMENDBD P.C.B PATTBRN LAYO UT

:act Resistance: 30 MΩ Max.
Dielectric Withstanding Voltage: 500W AC
Temperature Range: −35°C to +85°C
Insulator color: Black/White
Plastic material: PBT/LCP/Others
Shell finish: Nickel plated/Tin−Lead plated
Mechanical:
Mating Force: 3.5KG MAX
Unmating Force: 0.7 KG MIN.
Contact finish:
- 01: Selective Gold Flash
- 02: Selective Gold 3U"
- 03: Selective Gold 5U"
- 04: Selective Gold 15U"
- 05: Selective Gold 30U"

备注：侧弹分为外弹与内弹

产品图 PRODUCT CHART DWG											
公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	MM	制图 DRAWING	Z-Y-B	产品料号	JTJ-USB-AF-07		
X.	±0.25	X°.	±5°	比例 SCALE	1:1	审核 CHKD	雷永键	产品名称 PRODUCT NO.	USB-AF内扣直脚		
.X	±0.20	.X°	±2°								
.XX	±0.15	.XX°	±1°	日期 DATE	2009/10/20	核准 APPD	雷永键	角法 VIEW		版本 VER	A
.XXX	±0.10	.XXX°	±0.5°								