


# MMBT9018G / MMBT9018H

NPN Silicon Epitaxial Planar Transistor  
for AM/FM amplifier and local oscillator of  
FM/VHF tuner applications.




1. Base 2. Emitter 3. Collector  
SOT-23 Plastic Package

Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Collector Base Voltage	$V_{CBO}$	30	V
Collector Emitter Voltage	$V_{CEO}$	15	V
Emitter Base Voltage	$V_{EBO}$	5	V
Collector Current	$I_C$	50	mA
Power Dissipation	$P_{tot}$	200	mW
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature Range	$T_s$	-55 to +150	$^\circ\text{C}$

Characteristics at  $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = 5\text{ V}$ , $I_C = 1\text{ mA}$	MMBT9018G $h_{FE}$	75	-	105	-
	MMBT9018H $h_{FE}$	105	-	190	-
Collector Base Breakdown Voltage at $I_C = 100\ \mu\text{A}$	$V_{(BR)CBO}$	30	-	-	V
Collector Emitter Breakdown Voltage at $I_C = 1\text{ mA}$	$V_{(BR)CEO}$	15	-	-	V
Emitter Base Breakdown Voltage at $I_E = 100\ \mu\text{A}$	$V_{(BR)EBO}$	5	-	-	V
Collector Cutoff Current at $V_{CB} = 12\text{ V}$	$I_{CBO}$	-	-	50	nA
Collector Emitter Saturation Voltage at $I_C = 10\text{ mA}$ , $I_B = 1\text{ mA}$	$V_{CE(sat)}$	-	-	0.5	V
Collector Base Capacitance at $V_{CB} = 10\text{ V}$ , $f = 1\text{ MHz}$	$C_{CBO}$	-	1.3	1.7	pF
Gain Bandwidth Product at $V_{CE} = 5\text{ V}$ , $I_C = 5\text{ mA}$	$f_T$	700	1100	-	MHz



®

**РАДИОТЕХ**

Тел.: (495) 795-0805  
Факс: (495) 234-1603  
Эл. почта: info@rct.ru  
Веб: www.rct.ru