



Aluminum Electrolytic Capacitors

SG

Features

- 105°C, 1,000 hours assured
- High temperature Category range, with 7mm height
- RoHS Compliance




Sleeve & Marking Color: Green & Black

SPECIFICATIONS

Items	Performance																														
Category Temperature Range	-40°C ~ +105°C																														
Capacitance Tolerance	±20% (at 120Hz, 20°C)																														
Leakage Current (at 20°C)	I = 0.01CV or 3 (μA) whichever is greater (after 2 minutes) Where, C = rated capacitance in μF V = rated DC working voltage in V																														
Dissipation Factor (Tan δ at 120Hz, 20°C)	<table border="1"> <thead> <tr> <th>Rated Voltage</th> <th>4</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> </tr> </thead> <tbody> <tr> <td>Tan δ (max)</td> <td>0.35</td> <td>0.23</td> <td>0.20</td> <td>0.17</td> <td>0.15</td> <td>0.12</td> <td>0.10</td> <td>0.10</td> </tr> </tbody> </table>	Rated Voltage	4	6.3	10	16	25	35	50	63	Tan δ (max)	0.35	0.23	0.20	0.17	0.15	0.12	0.10	0.10												
Rated Voltage	4	6.3	10	16	25	35	50	63																							
Tan δ (max)	0.35	0.23	0.20	0.17	0.15	0.12	0.10	0.10																							
Low Temperature Characteristics (at 120Hz)	<p>Impedance ratio shall not exceed the values given in the table below.</p> <table border="1"> <thead> <tr> <th colspan="2">Rated Voltage</th> <th>4</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> </tr> </thead> <tbody> <tr> <td>Impedance</td> <td>Z(-25°C)/Z(+20°C)</td> <td>6</td> <td>4</td> <td>3</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>Ratio</td> <td>Z(-40°C)/Z(+20°C)</td> <td>12</td> <td>10</td> <td>8</td> <td>6</td> <td>4</td> <td>4</td> <td>4</td> <td>4</td> </tr> </tbody> </table>	Rated Voltage		4	6.3	10	16	25	35	50	63	Impedance	Z(-25°C)/Z(+20°C)	6	4	3	3	2	2	2	2	Ratio	Z(-40°C)/Z(+20°C)	12	10	8	6	4	4	4	4
Rated Voltage		4	6.3	10	16	25	35	50	63																						
Impedance	Z(-25°C)/Z(+20°C)	6	4	3	3	2	2	2	2																						
Ratio	Z(-40°C)/Z(+20°C)	12	10	8	6	4	4	4	4																						
Endurance	<table border="1"> <thead> <tr> <th>Test Time</th> <th>1,000 Hrs</th> </tr> </thead> <tbody> <tr> <td>Capacitance Change</td> <td>Within ±20% of initial value</td> </tr> <tr> <td>Dissipation Factor</td> <td>Less than 200% of specified value</td> </tr> <tr> <td>Leakage Current</td> <td>Within specified value</td> </tr> </tbody> </table> <p>* The above specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied with rated ripple current for 1,000 hours at 105°C.</p>	Test Time	1,000 Hrs	Capacitance Change	Within ±20% of initial value	Dissipation Factor	Less than 200% of specified value	Leakage Current	Within specified value																						
Test Time	1,000 Hrs																														
Capacitance Change	Within ±20% of initial value																														
Dissipation Factor	Less than 200% of specified value																														
Leakage Current	Within specified value																														
Shelf Life Test	Test time: 500 hours; other items are the same as those for the Endurance.																														
Ripple Current & Frequency Multipliers	<table border="1"> <thead> <tr> <th rowspan="2">Cap.(μF)</th> <th colspan="6">Freq.(Hz)</th> </tr> <tr> <th>60 (50)</th> <th>120</th> <th>500</th> <th>1k</th> <th>10k up</th> </tr> </thead> <tbody> <tr> <td>Under 47</td> <td>0.75</td> <td>1.00</td> <td>1.20</td> <td>1.30</td> <td>1.45</td> </tr> <tr> <td>100 to 330</td> <td>0.88</td> <td>1.00</td> <td>1.10</td> <td>1.15</td> <td>1.20</td> </tr> </tbody> </table>	Cap.(μF)	Freq.(Hz)						60 (50)	120	500	1k	10k up	Under 47	0.75	1.00	1.20	1.30	1.45	100 to 330	0.88	1.00	1.10	1.15	1.20						
Cap.(μF)	Freq.(Hz)																														
	60 (50)	120	500	1k	10k up																										
Under 47	0.75	1.00	1.20	1.30	1.45																										
100 to 330	0.88	1.00	1.10	1.15	1.20																										

DIAGRAM OF DIMENSIONS



LEAD SPACING AND DIAMETER Unit: mm

φD	4	5	6.3	8
P	1.5	2.0	2.5	3.5
φd	0.45	0.5		
α	1.0			
β	0.5			

Dimension: φD × L(mm)

Ripple Current: mA/rms at 120 Hz, 105°C

DIMENSION & PERMISSIBLE RIPPLE CURRENT

μF	V.DC Contents	4V (0G)		6.3V (0J)		10V (1A)		16V (1C)		25V (1E)		35V (1V)		50V (1H)		63V (1J)		
		φD×L	mA	φD×L	mA	φD×L	mA	φD×L	mA	φD×L	mA	φD×L	mA	φD×L	mA	φD×L	mA	
0.1	0R1													4×7	2	4×7	2	
0.22	R22													4×7	3	4×7	3	
0.33	R33													4×7	4	4×7	4.4	
0.47	R47													4×7	5	4×7	7.9	
1	010													4×7	10	4×7	11	
2.2	2R2													4×7	15	4×7	17	
3.3	3R3													4×7	18	4×7	21	
4.7	4R7												4×7	22	5×7*	23	5×7	26
10	100							4×7	25	4×7	26	5×7*	30	6.3×7*	34	6.3×7	40	
22	220			4×7	31	4×7	32	5×7*	39	5×7*	41	6.3×7	47	6.3×7	53	8×7	70	
33	330	4×7	32	4×7	32	4×7	35	5×7	43	6.3×7	53	8×7*	71	8×7	76			
47	470	4×7	38	4×7	38	5×7*	47	6.3×7*	59	6.3×7	65	8×7	83	8×7	85			
100	101	5×7	61	6.3×7*	75	6.3×7	80	6.3×7	90	8×7	125							
220	221	6.3×7	90	6.3×7	99	8×7	140	8×7	146									
330	331	8×7	156	8×7	156													

Note: Case size in mark of "*" is available to product down size.