

Device Number: DLE-031-095 REV: 1.0

T-1 3/4 (4.7mm) Round Shape LED Lamps

MODEL NO: 313-2SYGC/S530-E2 ECN: Page: 1/4

Features:

- 4.7mm round without flange.
- Available on tape and reel.
- Reliable and rugged.
- Improved brightness.
- Narrow viewing angle.

Description:

- ϕ 4.7mm T-1(3/4)all resin mold.
- General application is for indication, illumination, etc.
- The LED lamp is available with different colors, light intensities, epoxy colors, etc.

Applications:

- TV Set
- Monitor
- Telephone
- Computer

NOTES:

- 1.All dimensions are in millimeters.
- 2.An epoxy meniscus may extend about 1.5mm(0.059") down to the lead.

PART NO	СНІР		CHIP		Lens Color
	Material Emitted Color				
313-2SYGC/S530-E2	AlGaInP	Super Yelloew Green	Water Clear		

CHECKER	APPROVER

SHENZHEN OFFICE:

TEL: 86-755-33590909 FAX: 86-755-33590908



Device Number: DLE-031-095 REV: 1.0

T-1 3/4 (4.7mm) Round Shape LED Lamps

MODEL NO: 313-2SYGC/S530-E2 ECN: Page: 2/4

Absolute Maximum Ratings at $T_A = 25^{\circ}C$

Parameter	Symbol	Rating	Unit
Forward Current	If	25	mA
Operating Temperature	Topr	-40 to +85	$^{\circ}\!\mathbb{C}$
Storage Temperature	Tstg	-40 to +100	$^{\circ}\!\mathbb{C}$
Soldering Temperature	Tsol	260 ± 5	$^{\circ}\!\mathbb{C}$
Power Dissipation	Pd	60	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	160	mA
Reverse Voltage	Vr	5	V

Electronic Optical Characteristics:

Parameter	Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous intensity	Iv	210	17.4 290		mcd	If=2mA If=20mA
Viewing Angle	2 0 1/2		20		deg	If=20mA
Peak Wavelength	λp		575		nm	If=20mA
Dominant Wavelength	λd		573		nm	If=20mA
Spectrum Radiation Bandwidth	Δλ		20		nm	If=20mA
Forward Voltage	Vf		2.0	2.4	V	If=20mA
Reverse Current	Ir			10	μ A	Vr=5V

ESD:2000V



Device Number: DLE-031-095 REV: 1.0


T-1 3/4 (4.7mm) Round Shape LED Lamps


MODEL NO 313-2SYGC/S530-E2


ECN:


Page: 3/4


■ Typical Electro-Optical Characteristic Curves
















Device Number:	DLE-031-095	REV:	1.0
		_	

T-1 3/4 (4.7mm) Round Shape LED Lamps

MODEL NO 313-2SYGC/S530-E2	ECN:	Page:	4/4
----------------------------	------	-------	-----

■ Reliability test items and conditions

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Soldering Heat	TEMP : 260° C ± 5 $^{\circ}$ C	10±1 SEC	76 Pcs	0/1
2	Solderability	TEMP : 230°C ± 5 °C	5±1 SEC	76 Pcs	0/1
3	Temperature Cycle	H:+85°C 30min ∫ 5 min L:-55°C 30min	50 CYCLE	76 Pcs	0/1
4	Thermal Shock	H: $+100^{\circ}$ C 5min $\int 10 \sec$ L: -10° C 5min	50 CYCLE	76 Pcs	0/1
5	High Temperature Storage	TEMP : 100°C	1000 HRS	76 Pcs	0/1
6	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 Pcs	0/1
7	DC Operating Life	If = 20 mA	1000 HRS	76 Pcs	0/1
8	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 Pcs	0/1