



**Micro Commercial Components** 

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

# GBJ35005 THRU GBJ3510

## **Features**

- Lead Free Finish/RoHS Compliant (NOTE 1)("P" Suffix designates RoHS Compliant. See ordering information)
- Ideal for printed circuit board
- Low forward voltage drop, high current capability.
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Mounting: Through Hole for #6 Screw
- Recommended Torque: 5.7 cm-kg (5 in-lbs)
- Mounting Torque: 10 cm-kg (8.8 in-lbs) maximum
- Halogen free available upon request by adding suffix "-HF"

# **Maximum Ratings**

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- UL Recognized File # E165989


MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Reccurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage		Voltage
GBJ35005	GBJ35005	50V	35V	50V
GBJ3501	GBJ3501	100V	70V	100V
GBJ3502	GBJ3502	200V	140V	200V
GBJ3504	GBJ3504	400V	280V	400V
GBJ3506	GBJ3506	600V	420V	600V
GBJ3508	GBJ3508	800V	560V	800V
GBJ3510	GBJ3510	1000V	700V	1000V

#### Electrical Characteristics @ 25°C Unless Otherwise Specified

			<b>-</b>
Average Forward Current	I <sub>F(AV)</sub>	35 A	Tc = 100°C
Peak Forward Surge Current	I <sub>FSM</sub>	400A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	$V_{F}$	1.05V	I <sub>FM</sub> = 17.5 A T <sub>J</sub> = 25°C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	10 μ <b>A</b> 500uA	T <sub>J</sub> = 25°C T <sub>J</sub> = 125°C
Typical thermal resistance	R <sub>OJC</sub>	0.6°C/W	
Typical Junction Capacitance	CJ	85 pF	Measured at 1.0MHz, V <sub>R</sub> =4.0V

Notes:1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7a

# 35 Amp Glass Passivated Bridge Rectifier 50 to 1000 Volts




DIMENSIONS						
	INCHES		ММ			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	1.170	1.190	29.70	30.30		
В	.780	.800	19.70	20.30		
С	.670	.710	17.00	18.00		
D	.019	.019	4.70	4.90		
E	.430	.440	10.80	11.20		
F	.090	.110	2.30	2.70		
G	.120	.130	3.10	3.40		
Н	.130	.150	3.40	3.80		
I	.170	.190	4.40	4.80		
J	.100	.110	2.50	2.90		
K	.020	.030	0.60	0.80		
L	.080	.090	2.00	2.40		
M	.040	.040	0.90	1.10		
N	.390	.400	9.80	10.20		
0	.290	.300	7.30	7.70		
Р	.150	.170	3.80	4.20		
Case Type						



### **RATING AND CHARACTERISTIC CURVES** GBJ35005 thru GBJ3510

### **Micro Commercial Components**






FIG.3 - TYPICAL JUNCTION CAPACITANCE




FIG.4 - TYPICAL FORWARD CHARACTERISTICS





FIG.5 - TYPICAL REVERSE CHARACTERISTICS





### **Ordering Information:**

Device	Packing	
Part Number-BP	Bulk: 1.5K/Ctn	

Note: Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.