



SB270 thru SB2B0

Schottky Barrier Rectifiers

Reverse Voltage 70V to 100V Forward Current 1.0A Amperes

Features


- Metal-Semiconductor junction with guarding
- Epitaxial construction
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications



DO-204AC (DO-15)

Mechanical Data

- Case: JEDEC DO-204AC(DO-15) molded plastic
- Polarity: Color band denotes cathode end
- Weight: 0.014 ounce, 0.39 gram
- Mounting position: Any



Dimensions in inches and (millimeters)

MAXIMUM RATINGS and ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60HZ, resistive or inductive load.

For capacitive load, derate current by 20%

PARAMETER	SYMBOL	SB270	SB280	SB290	SB2B0	UNIT
Maximum repetitive peak reverse voltage	VRRM	70	80	90	100	V
Maximum RMS voltage	VRMS	49	56	63	70	V
Maximum DC blocking voltage	VDC	70	80	90	100	V
Maximum average forward rectified current @ T _L =100°C	IF(AV)	2.0				A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	IFSM	60				A
Maximum forward voltage at 2A DC T _A =25°C T _A =100°C	VF	0.79 0.69				V
Maximum DC reverse current at rated DC blocking voltage ⁽¹⁾	T _J =25°C	0.05				mA
	T _J =125°C	1				
Typical junction capacitance (Note 1)	C _j	50				pF
Typical thermal resistance(Note 2)	R _{θJA}	85				°C/W
	R _{θJC}	45				
	R _{θJL}	40				
Operating junction temperature range	T _J	- 55 to + 150				°C
storage temperature range	T _{STG}	- 55 to + 150				°C

Notes: 1. Measured at 1.0MHZ and applied reverse voltage of 4.0V DC

2. Thermal Resistance at .375(9.5mm) Lead Length, PC Board Mounted



GOOD-ARK

SB270 thru SB2B0

Schottky Barrier Rectifiers

Reverse Voltage 70V to 100V Forward Current 1.0A Amperes

RATINGS AND CHARACTERISTICS CURVES

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 - TYPICAL JUNCTION CAPACITANCE




FIG.4 - TYPICAL FORWARD CHARACTERISTICS




FIG.5 - TYPICAL REVERSE CHARACTERISTICS

