


FEATURES

- | Rating to 1000V PRV
- | Surge overload rating to 175 Amperes peak
- | Ideal for printed circuit board
- | Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- | Lead solderable per MIL-STD-202 method 208
- | Mounting: thru hole for # 6 screw Mounting

Outline Dimensions and Mark**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

Symbols		KBPC 10005	KBPC 1001	KBPC 1002	KBPC 1004	KBPC 1006	KBPC 1008	KBPC 1010	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward output current @ $T_A=50^\circ C$	$I_{F(AV)}$	10.0						A	
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I_{FSM}	175.0						A	
Maximum instantaneous forward voltage at 5.0 A	V_F	1.0						V	
Maximum reverse current @ $T_A=25^\circ C$ at rated DC blocking voltage @ $T_A=100^\circ C$	I_R	10.0 1.0						μA mA	
Operating junction temperature range	T_J	-55 ---- + 125						°C	
Storage temperature range	T_{STG}	-55 ---- + 150						°C	

NOTES:

1. Unit mounted on 8.7" x 8.7" x 0.24" thick (22 x 22 x 0.6 cm) Al. plate.
2. Unit mounted on P.C.B at 0.375" (9.5mm) lead length with 0.47" x 0.47" (12 x 12mm) copper pads.

Bridge Rectifier

KBPC10005 THRU KBPC1010

Formosa MS

FIG.1 – PEAK FORWARD SURGE CURRENT




FIG.2 – FORWARD DERATING CURVE




FIG.3 – TYPICAL FORWARD CHARACTERISTIC




FIG.4 – TYPICAL REVERSE CHARACTERISTIC

