




5.0SMDJ Series 5000W Transient Voltage Suppressor

Rev.4.1

DESCRIPTION:

TVS diodes can be used in a wide range of applications which like consumer electronic products, automotive industries, munitions, telecommunications, aerospace industries, and intelligent control systems.



SMC

FEATURES:

- ✧ Low profile package.
- ✧ Low inductance.
- ✧ Excellent clamping capability.
- ✧ 5000W peak pulse power capability at 10×1000μs waveform.
- ✧ Typical I_R less than 1μA above 30V.
- ✧ Fast response time: typically less than 1.0ps from 0V to V_{BR} min.
- ✧ High temperature to reflow soldering: 260°C/40s at terminals.
- ✧ Plastic package has under writers laboratory flammability 94V-0.
- ✧ Meets MSL level 1, per J-STD020, LF maximum peak of 260°C.
- ✧ For surface mounted applications in order to optimize board space.



Bi-directional



Uni-directional

Symbol


ABSOLUTE MAXIMUM RATINGS (T_A=25°C, RH=45%-75%, unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|---|-----------------------------------|-------------|------|
| Operating junction and storage temperature range | T _J / T _{STG} | -55 to +150 | °C |
| Steady state power dissipation at T _L =75°C | P _{M(AV)} | 6.5 | W |
| Peak pulse power dissipation on 10/1000μs waveform | P _{PP} | 5000 | W |
| Maximum instantaneous forward voltage at 100A for unidirectional only | V _F | 5.0 | V |
| Peak forward surge current, 8.3ms single half sine wave(Note 1) | I _{FSM} | 300 | A |
| Typical thermal resistance junction to lead | R _{θJL} | 15 | °C/W |
| Typical thermal resistance junction to ambient | R _{θJA} | 75 | °C/W |

Notes:

1. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional device only, duty cycle=4 per minute maximum

MARKING



5BEN: Device Marking Code
1409: In ninth week, 2014

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$)

| Part Number | | Marking | | V_R | $I_R@V_R$ | $V_{BR}@I_T$ | | I_T | $V_C@I_{PP}$ | $I_{PP}^{①}$ |
|-------------|-------------|---------|------|-------|---------------|--------------|--------|-------|--------------|--------------|
| Uni-Polar | Bi-Polar | Uni | Bi | V | μA | min(V) | max(V) | mA | max(V) | A |
| 5.0SMDJ11A | 5.0SMDJ11CA | 5PEN | 5BEN | 11 | 5 | 12.20 | 13.50 | 10 | 18.2 | 275.0 |
| 5.0SMDJ12A | 5.0SMDJ12CA | 5PEP | 5BEP | 12 | 5 | 13.30 | 14.70 | 10 | 19.9 | 252.0 |
| 5.0SMDJ13A | 5.0SMDJ13CA | 5PEQ | 5BEQ | 13 | 5 | 14.40 | 15.90 | 10 | 21.5 | 233.0 |
| 5.0SMDJ14A | 5.0SMDJ14CA | 5PER | 5BER | 14 | 5 | 15.60 | 17.20 | 10 | 23.2 | 216.0 |
| 5.0SMDJ15A | 5.0SMDJ15CA | 5PES | 5BES | 15 | 5 | 16.70 | 18.50 | 1 | 24.4 | 205.0 |
| 5.0SMDJ16A | 5.0SMDJ16CA | 5PET | 5BET | 16 | 5 | 17.80 | 19.70 | 1 | 26.0 | 193.0 |
| 5.0SMDJ17A | 5.0SMDJ17CA | 5PEU | 5BEU | 17 | 5 | 18.90 | 20.90 | 1 | 27.6 | 181.0 |
| 5.0SMDJ18A | 5.0SMDJ18CA | 5PEV | 5BEV | 18 | 5 | 20.00 | 22.10 | 1 | 29.2 | 172.0 |
| 5.0SMDJ20A | 5.0SMDJ20CA | 5PEW | 5BEW | 20 | 5 | 22.20 | 24.50 | 1 | 32.4 | 155.0 |
| 5.0SMDJ22A | 5.0SMDJ22CA | 5PEX | 5BEX | 22 | 5 | 24.40 | 26.90 | 1 | 35.5 | 141.0 |
| 5.0SMDJ24A | 5.0SMDJ24CA | 5PEZ | 5BEZ | 24 | 5 | 26.70 | 29.50 | 1 | 38.9 | 129.0 |
| 5.0SMDJ26A | 5.0SMDJ26CA | 5PFE | 5BFE | 26 | 5 | 28.90 | 31.90 | 1 | 42.1 | 119.0 |
| 5.0SMDJ28A | 5.0SMDJ28CA | 5PFG | 5BFG | 28 | 5 | 31.10 | 34.40 | 1 | 45.4 | 110.0 |
| 5.0SMDJ30A | 5.0SMDJ30CA | 5PFK | 5BFK | 30 | 5 | 33.30 | 36.80 | 1 | 48.4 | 103.0 |
| 5.0SMDJ33A | 5.0SMDJ33CA | 5PFM | 5BFM | 33 | 1 | 36.70 | 40.60 | 1 | 53.3 | 93.9 |
| 5.0SMDJ36A | 5.0SMDJ36CA | 5PFP | 5BFP | 36 | 1 | 40.00 | 44.20 | 1 | 58.1 | 86.1 |
| 5.0SMDJ40A | 5.0SMDJ40CA | 5PFR | 5BFR | 40 | 1 | 44.40 | 49.10 | 1 | 64.5 | 77.6 |
| 5.0SMDJ43A | 5.0SMDJ43CA | 5PFT | 5BFT | 43 | 1 | 47.80 | 52.80 | 1 | 69.4 | 72.1 |
| 5.0SMDJ45A | 5.0SMDJ45CA | 5PFV | 5BFV | 45 | 1 | 50.00 | 55.30 | 1 | 72.7 | 68.8 |
| 5.0SMDJ48A | 5.0SMDJ48CA | 5PFX | 5BFX | 48 | 1 | 53.30 | 58.90 | 1 | 77.4 | 64.7 |
| 5.0SMDJ51A | 5.0SMDJ51CA | 5PFZ | 5BFZ | 51 | 1 | 56.70 | 62.70 | 1 | 82.4 | 60.7 |
| 5.0SMDJ54A | 5.0SMDJ54CA | 5PGE | 5BGE | 54 | 1 | 60.00 | 66.30 | 1 | 87.1 | 57.5 |
| 5.0SMDJ58A | 5.0SMDJ58CA | 5PGG | 5BGG | 58 | 1 | 64.40 | 71.20 | 1 | 93.6 | 53.5 |

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, continued)

| Part Number | | Marking | | V_R | $I_R@V_R$ | $V_{BR}@I_T$ | | I_T | $V_C@I_{PP}$ | $I_{PP}^{①}$ |
|-------------|--------------|---------|------|-------|---------------|--------------|--------|-------|--------------|--------------|
| Uni-Polar | Bi-Polar | Uni | Bi | V | μA | min(V) | max(V) | mA | max(V) | A |
| 5.0SMDJ60A | 5.0SMDJ60CA | 5PGK | 5BGK | 60 | 1 | 66.70 | 73.70 | 1 | 96.8 | 51.7 |
| 5.0SMDJ64A | 5.0SMDJ64CA | 5PGM | 5BGM | 64 | 1 | 71.10 | 78.60 | 1 | 103.0 | 48.6 |
| 5.0SMDJ70A | 5.0SMDJ70CA | 5PGP | 5BGP | 70 | 1 | 77.80 | 86.00 | 1 | 113.0 | 44.3 |
| 5.0SMDJ75A | 5.0SMDJ75CA | 5PGR | 5BGR | 75 | 1 | 83.30 | 92.10 | 1 | 121.0 | 41.4 |
| 5.0SMDJ78A | 5.0SMDJ78CA | 5PGT | 5BGT | 78 | 1 | 86.70 | 95.80 | 1 | 126.0 | 39.7 |
| 5.0SMDJ85A | 5.0SMDJ85CA | 5PGV | 5BGV | 85 | 1 | 94.40 | 104.0 | 1 | 137.0 | 36.5 |
| 5.0SMDJ90A | 5.0SMDJ90CA | 5PGX | 5BGX | 90 | 1 | 100.0 | 111.0 | 1 | 146.0 | 34.3 |
| 5.0SMDJ100A | 5.0SMDJ100CA | 5PGZ | 5BGZ | 100 | 1 | 111.0 | 123.0 | 1 | 162.0 | 30.9 |
| 5.0SMDJ110A | 5.0SMDJ110CA | 5PHE | 5BHE | 110 | 1 | 122.0 | 135.0 | 1 | 177.0 | 28.3 |
| 5.0SMDJ120A | 5.0SMDJ120CA | 5PHG | 5BHG | 120 | 1 | 133.0 | 147.0 | 1 | 193.0 | 26.0 |
| 5.0SMDJ130A | 5.0SMDJ130CA | 5PHK | 5BHK | 130 | 1 | 144.0 | 159.0 | 1 | 209.0 | 24.0 |
| 5.0SMDJ150A | 5.0SMDJ150CA | 5PHM | 5BHM | 150 | 1 | 167.0 | 185.0 | 1 | 243.0 | 20.6 |
| 5.0SMDJ160A | 5.0SMDJ160CA | 5PHP | 5BHP | 160 | 1 | 178.0 | 197.0 | 1 | 259.0 | 19.3 |
| 5.0SMDJ170A | 5.0SMDJ170CA | 5PHR | 5BHR | 170 | 1 | 189.0 | 209.0 | 1 | 275.0 | 18.2 |

① Surge waveform:10/1000 μs


V_R : Stand-off voltage -- Maximum voltage that can be applied

V_{BR} : Breakdown voltage

V_C : Clamping voltage -- Peak voltage measured across the suppressor at a specified I_{PP}

I_R : Reverse leakage current

ORDERING INFORMATION



RATINGS AND V-I CHARACTERISTICS CURVES ($T_A=25^{\circ}\text{C}$, unless otherwise noted)

FIG.1: V- I curve characteristics (Uni-directional)




FIG.2: V- I curve characteristics (Bi-directional)




FIG.3: Pulse waveform






FIG.4: Pulse derating curve




SOLDERING PARAMETERS

| | | |
|--|-----------------------------------|---------------------------------|
| Reflow Condition | | Pb-Free assembly (see FIG.5) |
| Pre Heat | -Temperature Min ($T_{s(min)}$) | +150°C |
| | -Temperature Max($T_{s(max)}$) | +200°C |
| | -Time (Min to Max) (ts) | 60-180 secs. |
| Average ramp up rate (Liquidus Temp (T_L) to peak) | | 3°C/sec. Max |
| $T_{s(max)}$ to T_L - Ramp-up Rate | | 3°C/sec. Max |
| Reflow | -Temperature(T_L)(Liquidus) | +217°C |
| | -Temperature(t_L) | 60-150 secs. |
| Peak Temp (T_p) | | +260(+0/-5)°C |
| Time within 5°C of actual Peak Temp (t_p) | | 20-40secs. |
| Ramp-down Rate | | 6°C/sec. Max |
| Time 25°C to Peak Temp (T_p) | | 8 min. Max |
| Do not exceed | | +260°C |




PACKAGE MECHANICAL DATA



| Ref. | Dimensions | | | |
|------|-------------|-------|--------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 5.75 | 6.25 | 0.226 | 0.246 |
| B | 6.90 | 7.40 | 0.272 | 0.291 |
| C | 2.75 | 3.25 | 0.108 | 0.128 |
| D | 0.95 | 1.52 | 0.037 | 0.060 |
| E | 7.70 | 8.20 | 0.303 | 0.323 |
| F | 0.051 | 0.203 | 0.002 | 0.008 |
| G | 0.15 | 0.31 | 0.006 | 0.012 |
| H | 2.15 | 2.62 | 0.085 | 0.103 |
| J | 2.40 | | 0.094 | |
| K | | 4.20 | | 0.165 |
| L | 3.30 | | 0.130 | |

TAPE AND REEL SPECIFICATION-SMC



| Ref. | Dimensions | |
|------|-------------|----------------|
| | Millimeters | Inches |
| A0 | 6.05 ± 0.3 | 0.238 ± 0.012 |
| B0 | 8.31 ± 0.3 | 0.327 ± 0.012 |
| C | 330.0 | 13.0 |
| D0 | 1.55 ± 0.1 | 0.061 ± 0.004 |
| E | 1.75 ± 0.2 | 0.069 ± 0.008 |
| E1 | 13.3 ± 0.3 | 0.524 ± 0.012 |
| F | 7.50 ± 0.2 | 0.295 ± 0.008 |
| P0 | 4.00 ± 0.2 | 0.157 ± 0.008 |
| P1 | 8.00 ± 0.2 | 0.3145 ± 0.008 |
| P2 | 2.00 ± 0.2 | 0.079 ± 0.008 |
| W | 16.0 ± 0.2 | 0.630 ± 0.008 |
| W1 | 19.7 ± 2.0 | 0.776 ± 0.079 |

| PART No. | UNIT WEIGHT (g/PCS) typ. | REEL (PCS) | PER CARTON (PCS) | REEL DIAMETERS (mm) |
|---------------|-----------------------------|---------------|---------------------|---------------------------|
| 5.0SMDJxxCA/A | 0.294/0.342 (NOTE) | 3,000 | 48,000 | 330 |

Notes: 0.342g/PCS for single die; 0.294g/PCS for stacked dies

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the 4.1st version which is made in 19-June-2018. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright©2018 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.