


Wire Wound Chip Ceramic Inductor - MWSD-S Series

Operating Temp. : -40°C~+125°C



FEATURES

- Small chip suitable for surface mounting
- High Q value and high self-resonant frequency with ceramic material
- Tight inductance tolerance and high reliability
- Single-sided package, thinner than SDWL-C series


APPLICATIONS

- High frequency circuit in telecommunication and other equipments
- Mobile phones such as GSM, CDMA, TD-LTE, FDD-LTE, PDC, etc.
- Bluetooth, W-LAN, Broadband network

PRODUCT IDENTIFICATION

①	②	③	④	⑤	⑥																																												
MWSD	1005	C	10N	S	T																																												
①	②	③	④	⑤	⑥																																												
<table border="1"> <thead> <tr> <th colspan="2">Type</th> </tr> </thead> <tbody> <tr> <td>MWSD</td> <td>Wire Wound Chip Inductor</td> </tr> </tbody> </table>	Type		MWSD	Wire Wound Chip Inductor	<table border="1"> <thead> <tr> <th colspan="2">External Dimensions</th> </tr> </thead> <tbody> <tr> <td colspan="2">1005 [0402]</td> </tr> </tbody> </table>	External Dimensions		1005 [0402]		<table border="1"> <thead> <tr> <th colspan="2">Material Code</th> </tr> </thead> <tbody> <tr> <td>C</td> <td>Ceramic</td> </tr> </tbody> </table>	Material Code		C	Ceramic	<table border="1"> <thead> <tr> <th colspan="2">Nominal Inductance</th> </tr> </thead> <tbody> <tr> <th>Example</th> <th>Nominal Value</th> </tr> <tr> <td>4N7</td> <td>4.7nH</td> </tr> <tr> <td>10N</td> <td>10nH</td> </tr> <tr> <td>R10</td> <td>100nH</td> </tr> </tbody> </table>	Nominal Inductance		Example	Nominal Value	4N7	4.7nH	10N	10nH	R10	100nH	<table border="1"> <thead> <tr> <th colspan="2">Inductance Tolerance</th> </tr> </thead> <tbody> <tr> <td>B</td> <td>±0.1nH</td> </tr> <tr> <td>C</td> <td>±0.2nH</td> </tr> <tr> <td>S</td> <td>±0.3nH</td> </tr> <tr> <td>D</td> <td>±0.5nH</td> </tr> <tr> <td>G</td> <td>±2%</td> </tr> <tr> <td>H</td> <td>±3%</td> </tr> <tr> <td>J</td> <td>±5%</td> </tr> </tbody> </table>	Inductance Tolerance		B	±0.1nH	C	±0.2nH	S	±0.3nH	D	±0.5nH	G	±2%	H	±3%	J	±5%	<table border="1"> <thead> <tr> <th colspan="2">Packing</th> </tr> </thead> <tbody> <tr> <td>B</td> <td>Bulk Package</td> </tr> <tr> <td>T</td> <td>Tape & Reel</td> </tr> </tbody> </table>	Packing		B	Bulk Package	T	Tape & Reel
Type																																																	
MWSD	Wire Wound Chip Inductor																																																
External Dimensions																																																	
1005 [0402]																																																	
Material Code																																																	
C	Ceramic																																																
Nominal Inductance																																																	
Example	Nominal Value																																																
4N7	4.7nH																																																
10N	10nH																																																
R10	100nH																																																
Inductance Tolerance																																																	
B	±0.1nH																																																
C	±0.2nH																																																
S	±0.3nH																																																
D	±0.5nH																																																
G	±2%																																																
H	±3%																																																
J	±5%																																																
Packing																																																	
B	Bulk Package																																																
T	Tape & Reel																																																

SHAPE AND DIMENSIONS



Unit: mm

Series	A	B	C	D REF.	E REF.	H REF.	I REF.	J REF.
MWSD1005C	1.1±0.1	0.6±0.1	0.55±0.1	0.5±0.1	0.2±0.1	0.65	0.35	0.50

SPECIFICATIONS

MWSD1005C TYPE

Part Number	Inductance	Tolerance	Min. Quality Factor	L/Q Test Freq.	Max. DC Resistance	Max. Rated Current	Min. Self-resonant Frequency
Units	nH	-	-	MHz	Ω	mA	MHz
Symbol	L	-	Q	Freq.	DCR	I _r	S.R.F
MWSD1005C0N8□T	0.8	C,S,D,K	14	250	0.035	1000	>6000
MWSD1005C1N0□T	1.0	C,S,D,K	10	250	0.085	650	>6000
MWSD1005C1N8□T	1.8	C,S,D,J,K	20	250	0.043	950	>6000
MWSD1005C1N9□T	1.9	C,S,D,J,K	20	250	0.043	950	>6000
MWSD1005C2N0□T	2.0	C,S,D,J,K	23	250	0.043	950	>6000
MWSD1005C2N2□T	2.2	C,S,D,J,K	22	250	0.058	820	>6000
MWSD1005C2N4□T	2.4	C,S,D,J,K	18	250	0.091	650	>6000
MWSD1005C2N7□T	2.7	C,S,D,J,K	24	250	0.050	900	>6000
MWSD1005C3N0□T	3.0	S,D,K	24	250	0.063	790	>6000
MWSD1005C3N3□T	3.3	C,S,D,J,K	24	250	0.063	790	>6000
MWSD1005C3N6□T	3.6	C,S,D,J,K	24	250	0.063	790	>6000
MWSD1005C3N9□T	3.9	C,S,D,J,K	24	250	0.063	790	>6000
MWSD1005C4N1□T	4.1	C,S,D,J,K	22	250	0.070	700	>6000
MWSD1005C4N3□T	4.3	C,S,D,J,K	22	250	0.070	750	>6000
MWSD1005C4N7□T	4.7	C,S,D,J,K	20	250	0.120	570	>6000
MWSD1005C5N1□T	5.1	C,S,D,J,K	23	250	0.100	620	>6000
MWSD1005C5N6□T	5.6	C,S,D,J,K	25	250	0.078	710	>6000
MWSD1005C5N8□T	5.8	C,S,D,J,K	25	250	0.078	710	>6000
MWSD1005C6N2□T	6.2	C,S,D,J,K	25	250	0.078	710	>6000
MWSD1005C6N8□T	6.8	G,H,J,K	24	250	0.105	610	6000
MWSD1005C7N5□T	7.5	G,H,J,K	25	250	0.12	570	6000
MWSD1005C8N2□T	8.2	G,H,J,K	25	250	0.11	590	5500
MWSD1005C8N7□T	8.7	G,H,J,K	25	250	0.11	590	5500
MWSD1005C9N0□T	9.0	G,H,J,K	25	250	0.11	590	5500
MWSD1005C9N1□T	9.1	G,H,J,K	25	250	0.11	590	5500
MWSD1005C10N□T	10	G,H,J,K	24	250	0.15	510	5500
MWSD1005C11N□T	11	G,H,J,K	26	250	0.12	570	5500
MWSD1005C12N□T	12	G,H,J,K	26	250	0.12	570	5500
MWSD1005C13N□T	13	G,H,J,K	24	250	0.18	460	5000
MWSD1005C14N□T	14	G,H,J,K	26	250	0.21	430	5000
MWSD1005C15N□T	15	G,H,J,K	26	250	0.21	430	5000
MWSD1005C16N□T	16	G,H,J,K	25	250	0.28	370	4500
MWSD1005C18N□T	18	G,H,J,K	25	250	0.28	370	4500
MWSD1005C19N□T	19	G,H,J,K	26	250	0.24	400	4000
MWSD1005C20N□T	20	G,H,J,K	26	250	0.24	400	4000
MWSD1005C22N□T	22	G,H,J,K	25	250	0.36	330	4000
MWSD1005C23N□T	23	G,H,J,K	25	250	0.36	330	3800
MWSD1005C24N□T	24	G,H,J,K	25	250	0.36	330	3500
MWSD1005C27N□T	27	G,H,J,K	25	250	0.38	320	3500
MWSD1005C30N□T	30	G,H,J,K	25	250	0.38	320	3300
MWSD1005C33N□T	33	G,H,J,K	24	250	0.55	260	3200
MWSD1005C36N□T	36	G,H,J,K	25	250	0.60	250	3100
MWSD1005C38N□T	38	G,H,J,K	25	250	0.60	250	3000
MWSD1005C39N□T	39	G,H,J,K	25	250	0.60	250	3000
MWSD1005C43N□T	43	G,H,J,K	25	250	0.68	240	3000
MWSD1005C47N□T	47	G,H,J,K	25	250	0.95	200	2900
MWSD1005C51N□T	51	G,H,J,K	25	250	0.95	200	2850
MWSD1005C56N□T	56	G,H,J,K	25	250	1.05	190	2800
MWSD1005C62N□T	62	G,H,J,K	25	250	1.05	190	2600
MWSD1005C68N□T	68	G,H,J,K	25	250	1.35	170	2500
MWSD1005C75N□T	75	G,H,J,K	24	250	1.75	140	2400
MWSD1005C82N□T	82	G,H,J,K	25	250	1.90	140	2300



Specifications subject to change without notice. Please check our website for latest information. Revised 2018/04/15

SPECIFICATIONS

MWSD1005C TYPE

Part Number	Inductance	Tolerance	Min. Quality Factor	L/Q Test Freq.	Max. DC Resistance	Max. Rated Current	Min. Self-resonant Frequency
Units	nH	-	-	MHz	Ω	mA	MHz
Symbol	L	-	Q	Freq.	DCR	I _r	S.R.F
MWSD1005C91N□T	91	G,H,J,K	25	250	1.95	140	2100
MWSD1005C96N□T	96	G,H,J,K	24	250	2.06	130	1500
MWSD1005CR10□T	100	G,H,J,K	24	250	2.06	130	1500
MWSD1005CR11□T	110	G,H,J,K	25	250	2.38	120	1200
MWSD1005CR12□T	120	J,K	25	250	2.66	110	1000


※ □: Please specify the inductance tolerance code (B=±0.1nH, C=±0.2nH, S=±0.3nH, D=±0.5nH, G=±2%, H=±3%, J=±5%, K=±10%).

※: Please refer to "Measurement Notice For RF Inductors".

TYPICAL ELECTRICAL CHARACTERISTICS

MWSD1005C TYPE

Inductance vs. Frequency Characteristics



Q vs. Frequency Characteristics

