

**P-Channel Enhancement Mode Power MOSFET**


# MTEF1P15Q8

BVDSS	-150V
ID@TA=25 °C, VGS=-10V	-1.6A
RDSON@VGS=-10V, ID=-1.6A	650mΩ (typ)
RDSON@VGS=-6V, ID=-1A	700mΩ (typ)


**Features**

- Simple drive requirement
- Low on-resistance
- Fast switching speed
- Pb-free and Halogen-free package

**Equivalent Circuit**




**Outline**



**Ordering Information**

Device	Package	Shipping
MTEF1P15Q8-0-T3-G	SOP-8 (Pb-free lead plating and halogen-free package)	2500 pcs / tape & reel





**Absolute Maximum Ratings** (T<sub>C</sub>=25°C, unless otherwise noted)

Parameter	Symbol	Limits	Unit
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	-150	V
Gate-Source Voltage	V <sub>GS</sub>	±20	
Continuous Drain Current @T <sub>A</sub> =25 °C, V <sub>GS</sub> =-10V	I <sub>D</sub>	-1.6	A
Continuous Drain Current @T <sub>A</sub> =70 °C, V <sub>GS</sub> =-10V		-1.3	
Pulsed Drain Current (Note 1)	I <sub>DM</sub>	-6.4	
Power Dissipation (Note 2)	P <sub>D</sub>	T <sub>A</sub> =25 °C	3.1
		T <sub>A</sub> =70 °C	2
Operating Junction and Storage Temperature Range	T <sub>j</sub> ; T <sub>stg</sub>	-55~+150	°C

Note : 1.Pulse width limited by maximum junction temperature.  
 2.Surface mounted on 1 in<sup>2</sup>copper pad of FR-4 board, t≤10s.

**Thermal Resistance Ratings**

Thermal Resistance	Symbol	Maximum	Unit
Junction-to-Case	R <sub>θJC</sub>	3	°C / W
Junction-to-Ambient (Note)	R <sub>θJA</sub>	40	

Note : W when mounted on a 1 in<sup>2</sup> pad of 2 oz copper, t≤10s; 125°C/W when mounted on minimum copper pad.

**Electrical Characteristics** (T<sub>C</sub>=25°C, unless otherwise noted)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
<b>Static</b>					
BV <sub>DSS</sub>	-150	-	-	V	V <sub>GS</sub> =0V, I <sub>D</sub> =-250μA
V <sub>GS(th)</sub>	-2	-2.8	-3.5		V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =-250μA
I <sub>GSS</sub>	-	-	±100	nA	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V
I <sub>DSS</sub>	-	-	-1	μA	V <sub>DS</sub> =-120V, V <sub>GS</sub> =0V
I <sub>DSS</sub>	-	-	-10		V <sub>DS</sub> =-120V, V <sub>GS</sub> =0V, T <sub>j</sub> =125°C
R <sub>DS(ON)</sub> (Note 1)	-	650	800	mΩ	I <sub>D</sub> =-1.6A, V <sub>GS</sub> =-10V
	-	700	910		I <sub>D</sub> =-1A, V <sub>GS</sub> =-6V
G <sub>FS</sub> (Note 1)	-	2.6	-	S	V <sub>DS</sub> =-10V, I <sub>D</sub> =-1.4A
<b>Dynamic</b>					
C <sub>iss</sub>	-	478	-	pF	V <sub>DS</sub> =-30V, V <sub>GS</sub> =0V, f=1MHz
C <sub>oss</sub>	-	28	-		
C <sub>rss</sub>	-	12	-		
t <sub>d(ON)</sub> (Note 1&2)	-	8	-	ns	V <sub>DS</sub> =-75V, I <sub>D</sub> =-1A, V <sub>GS</sub> =-10V, R <sub>G</sub> =1 Ω
t <sub>r</sub> (Note 1&2)	-	6	-		
t <sub>d(OFF)</sub> (Note 1&2)	-	20	-		
t <sub>f</sub> (Note 1&2)	-	4	-		
Q <sub>g</sub> (Note 1&2)	-	6	-	nC	V <sub>DS</sub> =-75V, I <sub>D</sub> =-1A, V <sub>GS</sub> =-10V
Q <sub>gs</sub> (Note 1&2)	-	2	-		
Q <sub>gd</sub> (Note 1&2)	-	1.4	-		




**Electrical Characteristics(Cont.)** (Tj=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
<b>Source-Drain Diode</b>					
I <sub>S</sub>	-	-	-1.6	A	
I <sub>SM</sub> (Note 3)	-	-	-6.4		
V <sub>SD</sub> (Note 1)	-	-0.78	-1.2	V	I <sub>S</sub> =-1.6A, V <sub>GS</sub> =0V
trr	-	60	-	ns	I <sub>F</sub> =-1A, dI <sub>F</sub> /dt=100A/μs
Qrr	-	120	-	nC	


Note : 1.Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%  
2.Independent of operating temperature  
3.Pulse width limited by maximum junction temperature

**Typical Characteristics**


Typical Output Characteristics




Typical Output Characteristics




Static Drain-Source On-State resistance vs Drain Current




Source Drain Current vs Source-Drain Voltage









Static Drain-Source On-State Resistance vs Gate-Source Voltage



Normalized Drain-Source On-State Resistance vs Junction Temperature




**Typical Characteristics(Cont.)**




**Typical Characteristics(Cont.)**


Single Pulse Power Rating, Junction to Ambient  
 (Note on page 2)




Typical Transfer Characteristics




Transient Thermal Response Curves




Normalized Brekdown Voltage vs Ambient Temperature



**Reel Dimension**




**Carrier Tape Dimension**



**Recommended wave soldering condition**

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

**Recommended temperature profile for IR reflow**




Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T <sub>smax</sub> to T <sub>p</sub> )	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T <sub>s min</sub> )	100°C	150°C
-Temperature Max(T <sub>s max</sub> )	150°C	200°C
-Time(t <sub>s min</sub> to t <sub>s max</sub> )	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T <sub>L</sub> )	183°C	217°C
- Time (t <sub>L</sub> )	60-150 seconds	60-150 seconds
Peak Temperature(T <sub>p</sub> )	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.



**SOP-8 Dimension**



\*: Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.1850	0.2007	4.70	5.10	G	0.0531	0.0689	1.35	1.75
B	0.1496	0.1575	3.80	4.00	H	0.1889	0.2007	4.80	5.10
C	0.2283	0.2441	5.80	6.20	I	0.0019	0.0098	0.05	0.25
D	0.0500*		1.27 *		J	0.0157	0.0500	0.40	1.27
E	0.0130	0.0201	0.33	0.51	K	0.0067	0.0098	0.17	0.25
F	0.1472	0.1527	3.74	3.88	L	0.0531	0.0610	1.35	1.55

Notes: 1.Controlling dimension: millimeters.  
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.  
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

**Material:**

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.