





- ▼ 100% R<sub>g</sub> & UIS Test
- ▼ Fast Switching Characteristic
- ▼ Simple Drive Requirement
- ▼ RoHS Compliant & Halogen-Free



BV <sub>DSS</sub>	650V
R <sub>DS(ON)</sub>	0.38Ω
I <sub>D</sub> <sup>3</sup>	10A



## Description

AP65SL380D series are from Advanced Power innovative design and silicon process technology to achieve the lowest possible on-resistance and fast switching performance. It provides the designer with an extreme efficient device for use in a wide range of power applications.

The TO-252 package is widely preferred for commercial-industrial surface mount applications and suited for low voltage applications such as DC/DC converters.

## Absolute Maximum Ratings@T<sub>j</sub>=25°C(unless otherwise specified)

Symbol	Parameter	Rating	Units
V <sub>DS</sub>	Drain-Source Voltage	650	V
V <sub>GS</sub>	Gate-Source Voltage	±20	V
V <sub>GS</sub>	Gate-Source Voltage, AC (f > 1Hz)	±30	V
I <sub>D</sub> @T <sub>C</sub> =25°C	Drain Current, V <sub>GS</sub> @ 10V <sup>3</sup>	10	A
I <sub>D</sub> @T <sub>C</sub> =100°C	Drain Current, V <sub>GS</sub> @ 10V <sup>3</sup>	6.5	A
I <sub>DM</sub>	Pulsed Drain Current <sup>1</sup>	24	A
dv/dt	MOSFET dv/dt Ruggedness (V <sub>DS</sub> = 0 ...400V )	40	V/ns
P <sub>D</sub> @T <sub>C</sub> =25°C	Total Power Dissipation	78.1	W
P <sub>D</sub> @T <sub>A</sub> =25°C	Total Power Dissipation <sup>6</sup>	2	W
E <sub>AS</sub>	Single Pulse Avalanche Energy <sup>4</sup>	75	mJ
dv/dt	Peak Diode Recovery dv/dt <sup>5</sup>	15	V/ns
T <sub>STG</sub>	Storage Temperature Range	-55 to 150	°C
T <sub>J</sub>	Operating Junction Temperature Range	-55 to 150	°C

## Thermal Data

Symbol	Parameter	Value	Units
R <sub>thj-c</sub>	Maximum Thermal Resistance, Junction-case	1.6	°C/W
R <sub>thj-a</sub>	Maximum Thermal Resistance, Junction-ambient (PCB mount) <sup>6</sup>	62.5	°C/W



## Electrical Characteristics@ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$ , $I_{\text{D}}=250\mu\text{A}$	650	-	-	V
$R_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance <sup>2</sup>	$V_{\text{GS}}=10\text{V}$ , $I_{\text{D}}=3.2\text{A}$	-	-	0.38	$\Omega$
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}$ , $I_{\text{D}}=250\mu\text{A}$	2	-	5	V
$g_{\text{fs}}$	Forward Transconductance	$V_{\text{DS}}=15\text{V}$ , $I_{\text{D}}=3.2\text{A}$	-	6	-	S
$I_{\text{DSS}}$	Drain-Source Leakage Current	$V_{\text{DS}}=520\text{V}$ , $V_{\text{GS}}=0\text{V}$	-	-	100	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Source Leakage	$V_{\text{GS}}=\pm 20\text{V}$ , $V_{\text{DS}}=0\text{V}$	-	-	$\pm 1$	$\mu\text{A}$
$Q_g$	Total Gate Charge	$I_{\text{D}}=5\text{A}$	-	33	52.8	nC
$Q_{\text{gs}}$	Gate-Source Charge	$V_{\text{DS}}=480\text{V}$	-	8	-	nC
$Q_{\text{gd}}$	Gate-Drain ("Miller") Charge	$V_{\text{GS}}=10\text{V}$	-	14	-	nC
$t_{\text{d}(\text{on})}$	Turn-on Delay Time	$V_{\text{DD}}=300\text{V}$	-	13	-	ns
$t_r$	Rise Time	$I_{\text{D}}=5\text{A}$	-	11	-	ns
$t_{\text{d}(\text{off})}$	Turn-off Delay Time	$R_{\text{G}}=3.3\Omega$	-	33	-	ns
$t_f$	Fall Time	$V_{\text{GS}}=10\text{V}$	-	8	-	ns
$C_{\text{iss}}$	Input Capacitance	$V_{\text{GS}}=0\text{V}$	-	1160	1860	pF
$C_{\text{oss}}$	Output Capacitance	$V_{\text{DS}}=100\text{V}$	-	40	-	pF
$C_{\text{rss}}$	Reverse Transfer Capacitance	$f=1.0\text{MHz}$	-	5	-	pF
$R_g$	Gate Resistance	$f=1.0\text{MHz}$	-	3.3	6.6	$\Omega$

## Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{\text{SD}}$	Forward On Voltage <sup>2</sup>	$I_{\text{S}}=3.2\text{A}$ , $V_{\text{GS}}=0\text{V}$	-	0.8	-	V
$t_{\text{rr}}$	Reverse Recovery Time	$I_{\text{S}}=5\text{A}$ , $V_{\text{GS}}=0\text{V}$	-	120	-	ns
$Q_{\text{rr}}$	Reverse Recovery Charge	$dI/dt=100\text{A}/\mu\text{s}$	-	710	-	nC

### Notes:

- 1.Pulse width limited by max. junction temperature.
- 2.Pulse test
- 3.Limited by max. junction temperature. Maximum duty cycle D=0.75
- 4.Starting  $T_j=25^\circ\text{C}$  ,  $V_{\text{DD}}=50\text{V}$  ,  $L=150\text{mH}$  ,  $R_{\text{G}}=25\Omega$
5. $I_{\text{SD}} \leq I_{\text{D}}$ ,  $V_{\text{DD}} \leq \text{BV}_{\text{DSS}}$ , starting  $T_j = 25^\circ\text{C}$
- 6.Surface mounted on 1 in<sup>2</sup> copper pad of FR4 board

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode










Fig 6. Gate Threshold Voltage v.s. Junction Temperature

# AP65SL380DH






Fig 13. Typ. Drain-Source on State Resistance




Fig 14. Total Power Dissipation



**AP65SL380DH**

## **MARKING INFORMATION**

