

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	I_D
60V	4.5mΩ@10V	20A
	5.4mΩ@4.5V	

Feature

- Advanced trench process technology
- High Density Cell Design For Ultra Low On-Resistance

Application


- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification

Package




SOP-8

Circuit diagram



Marking



Absolute maximum ratings (Ta=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	60	V
Gate-Source Voltage	V _{GS}	±20	V
Continuous Drain Current	I _D	20	A
Pulsed Drain Current	I _{DM}	130	A
Power Dissipation	P _D	3.5	W
Thermal Resistance from Junction to Ambient	R _{θJA}	36	°C/W
Junction Temperature	T _J	150	°C
Storage Temperature	T _{STG}	-55 ~ +150	°C

Electrical characteristics (T_A=25 °C, unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	60			V
Zero gate voltage drain current	I _{DSS}	V _{DS} = 60V, V _{GS} = 0V			1	μA
Gate-body leakage current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
Gate threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	1.0		2.4	V
Drain-source on-resistance ¹⁾	R _{DS(on)}	V _{GS} = 10V, I _D = 20A		4.0	4.5	mΩ
		V _{GS} = 4.5V, I _D = 18A		4.6	5.4	
Forward transconductance ¹⁾	g _{FS}	V _{DS} = 5V, I _D = 20A	35			S
Dynamic characteristics²⁾						
Input Capacitance	C _{iss}	V _{DS} = 30V, V _{GS} = 0V, f = 1MHz		4000		pF
Output Capacitance	C _{oss}			680		
Reverse Transfer Capacitance	C _{rss}			23		
Total Gate Charge	Q _g	V _{DS} = 30V, V _{GS} = 10V, I _D = 20A		67		nC
Gate-Source Charge	Q _{gs}			12		
Gate-Drain Charge	Q _{gd}			8.5		
Turn-on delay time	t _{d(on)}	V _{DD} = 30V, V _{GS} = 10V, R _L = 1.7Ω, R _{GEN} = 3Ω		11		nS
Turn-on rise time	t _r			5		
Turn-off delay time	t _{d(off)}			56		
Turn-off fall time	t _f			12		
Source-Drain Diode characteristics						
Diode Forward Current ¹⁾	I _S				20	A
Diode Forward voltage	V _{DS}	V _{GS} = 0V, I _S = 20A			1.2	V

Notes:

- 1) Pulse Test: Pulse Width < 300μs, Duty Cycle ≤ 2%.
- 2) Guaranteed by design, not subject to production testing.



Typical Characteristics




Figure 1 Output Characteristics




Figure 2 Transfer Characteristics




Figure 3 Rdson- Drain Current




Figure 4 Rdson-Junction Temperature




Figure 5 Gate Charge










Figure 6 Source- Drain Diode Forward

Typical Characteristics

Figure 7 Capacitance vs Vds

Figure 8 Safe Operation Area

Figure 9 Power De-rating

Figure 10 Current De-rating

Figure 11 Normalized Maximum Transient Thermal Impedance

SOP-8 Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270(BSC)		0.050(BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°