

深圳市连线电子有限公司

客户承认图

CUSTOMER (客户):		Customer Part NO(客户物品号):									
		Part Descripon(物品规格): 1.0*28*250*A (44/88) (0.035*0.65)									
Item	项目	Specification	规格值								
NO. of conductors	导体芯数	N	28								
Pitch	间距	P	1.0±0.10								
Total Pitch	全间距	PT	27±0.10								
Total Length	总长度	L	250±3								
Insulation Length	绝缘长度	IL	242±3								
Margin Width	边缘宽度	M	1.0±0.12								
Total Width	总宽度	W	29±0.15								
Strip Length	线口长度	S1	4±1								
Strip Length	线口长度	S2	4±1								
Reinforeing tape length	补强板长度	B1	8±2								
Reinforeing tape length	补强板长度	B2	8±2								
Slanting	线口倾斜度	A	≤0.3								
Over lap	冲孔		/								
Terminal thickness	插入厚度	t1	0.303±0.05								
Thickness insulation	线身厚度	t	0.121±0.05								
Conductor thickness	导体厚度	Ct	0.035±0.005					印字内容: E488937 RU AWM 20624 80C 60V VW-1 颜色: 蓝色			
Conductor width	导体宽度	Cw	0.65±0.03					Storage condition:(储存条件) Recommended(推荐)			
Supporting Tapc Color	补强板颜色		(Blue)蓝色					Temp: 15°C~25°C(温度15°C~25°C)Humidity: 30~60RH%(湿度30~60RH%)			
PET(Supporting Tapc Color)	补强板规格		0.225mm					Drawing Not To Scale Hidden Lines Not Shown 图规不能以其线材比来 衡量, 隐藏线不显示		Discharge Date 发行日期	
PET(Insulation)	绝缘胶规格		0.043mm (有印字)	2019. 8. 27						2019082701	
PET(Insulation)	绝缘胶规格		0.043mm (无印字白色)			Drawing by 制图		Checked by 核对		Approved by 确认	
Rev	版本		A1			Unit (单位): mm		Illyen			