

## SOT-23 Plastic-Encapsulate MOSFET

N -Channel MOSFET

### Product Summary

$V_{(BR)DSS}$	$R_{DS(on)}\text{MAX}$	$I_D$
60 V	5Ω@10V	340mA
	5.3Ω@4.5V	

### Features


- High density cell design for Low  $R_{DS(on)}$
- Voltage controlled small signal switch
- Rugged and reliable
- High saturation current capability
- ESD protected

### Applications

- Load Switch for Portable Devices
- DC/DC Converter

### Marking:

- 72K



### Limiting Values (Absolute Maximum Rating)

Symbol	Parameter	Value	Unit
$V_{DS}$	Drain-Source voltage	60	V
$V_{GS}$	Gate-Source voltage	±20	V
$I_D$	Drain Current	340	mA
$P_D$	Power Dissipation	0.35	W
$T_J$	Junction Temperature	150	°C
$T_{stg}$	Storage Temperature	-55~+150	°C
$R_{θJA}$	Thermal Resistance from Junction to Ambient	357	°C /W

## Electrical Characteristics ( $T_A=25^\circ\text{C}$ unless otherwise noted)







Parameter	Symbol	Test Condition	Min	Type	Max	Unit
<b>Static Characteristics</b>						
Drain-source breakdown voltage	$V_{(\text{BR})\text{DSS}}$	$V_{GS} = 0V, I_D = 250\mu\text{A}$	60			V
Zero gate voltage drain current	$I_{DSS}$	$V_{DS} = 48V, V_{GS} = 0V$			1	$\mu\text{A}$
	$I_{GSS1}$	$V_{GS} = \pm 20V, V_{DS} = 0V$			$\pm 10$	$\mu\text{A}$
Gate-body leakage current	$I_{GSS2}$	$V_{GS} = \pm 10V, V_{DS} = 0V$			$\pm 200$	nA
	$I_{GSS2}$	$V_{GS} = \pm 5V, V_{DS} = 0V$			$\pm 100$	nA
Gate threshold voltage*	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	1	1.4	2.5	V
Drain-source on-resistance*	$R_{DS(\text{on})}$	$V_{GS} = 10V, I_D = 500\text{mA}$		1.3	5	$\Omega$
		$V_{GS} = 4.5V, I_D = 200\text{mA}$		1.4	5.3	
Recovered charge	$Q_r$	$V_{GS}=0V, I_s=300\text{mA}, V_R=25V,$ $dI_s/dt=-100\text{A}/\mu\text{s}$		30		nC
<b>Dynamic characteristics**</b>						
Input Capacitance	$C_{iss}$	$V_{DS}=10V, V_{GS}=0V, f=1\text{MHz}$			40	pF
Output Capacitance	$C_{oss}$				30	
Reverse Transfer Capacitance	$C_{rss}$				10	
<b>Switching Characteristics**</b>						
Turn-on delay time	$t_{d(on)}$	$V_{GS}=10V, V_{DD}=50V, R_G=50\Omega$ $R_{GS}=50\Omega, R_L=250\Omega$			10	ns
Turn-off delay time	$t_{d(off)}$				15	
Reverse recovery Time	$t_{rr}$	$V_{GS}=0V, I_s=300\text{mA}, V_R=25V,$ $dI_s/dt=-100\text{A}/\mu\text{s}$		30		
<b>Source-Drain Diode characteristics</b>						
Diode Forward voltage	$V_{SD}$	$V_{GS}=0V, I_s=300\text{mA}$		0.97	1.5	V
<b>GATE-SOURCE ZENER DIODE</b>						
Gate-Source Breakdown Voltage	$BV_{GSO}$	$IGS=\pm 1\text{mA}(\text{Open Drain})$	$\pm 21.5$		$\pm 30$	V

### Notes:


\*Pulse Test: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$ .

\*\*These parameters have no way to verify.

## Typical Characteristics




## SOT-23 Package Outline Dimensions



UNIT	A	B	b <sub>p</sub>	C	D	E	H <sub>E</sub>	A <sub>1</sub>	L <sub>p</sub>
mm	1.40 0.95	2.04 1.78	0.50 0.35	0.19 0.08	3.10 2.70	1.65 1.20	3.00 2.20	0.100 0.013	0.50 0.20

## SOT-23 Suggested Pad Layout



### Note:


1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.05\text{mm}$ .
3. The pad layout is for reference purposes only.

### NOTICE

JSHD reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSHD does not assume any liability arising out of the application or use of any product described herein.

# Reel Taping Specifications For Surface Mount Devices-SOT-23

## SOT-23 Embossed Carrier Tape




### Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

## SOT-23 Tape Leader and Trailer



## SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7" Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×230	