



## BAT54C

DIODE

### SCHOTTKY BARRIER (DUAL) DIODES



#### DESCRIPTION

Planar Schottky barrier diodes are encapsulated in the SOT-23 small plastic SMD package. Single diodes and dual diodes with different pin configuration are available.

#### FEATURES

- \* Low forward voltage
- \* Guard ring protected
- \* Small plastic SMD package

#### SYMBOL




#### ORDERING INFORMATION

| Ordering Number |               | Package | Pin Assignment |    |      | Packing   |
|-----------------|---------------|---------|----------------|----|------|-----------|
| Lead Free       | Halogen Free  |         | 1              | 2  | 3    |           |
| BAT54CL-AE3-R   | BAT54CG-AE3-R | SOT-23  | A1             | A2 | K1K2 | Tape Reel |

Note: Pin Assignment: A: Anode K: Cathode

|   |   |
|---|---|
| <p>BAT54CG-AE3-R</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p> | <p>(1) R: Tape Reel</p> <p>(2) AE3: SOT-23</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p> |
|---|---|

#### MARKING



■ ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ , unless otherwise specified)

| PARAMETER   | SYMBOL    | RATINGS    | UNIT             |
|---|-----------|------------|------------------|
| <b>PER DIODE</b>  |           |            |                  |
| Continuous Reverse Voltage  | $V_R$     | 30         | V                |
| Continuous Forward Current  | $I_F$     | 200        | mA               |
| Repetitive Peak Forward Current ( $t_P < 1\text{s}$ , $\delta \leq 0.5$ ) | $I_{FRM}$ | 300        | mA               |
| Non-repetitive Peak Forward Current ( $t_P < 10\text{ms}$ )               | $I_{FSM}$ | 600        | mA               |
| Junction Temperature  | $T_J$     | +125       | $^\circ\text{C}$ |
| Storage Temperature   | $T_{STG}$ | -60 ~ +150 | $^\circ\text{C}$ |
| <b>PER DEVICE</b>   |           |            |                  |
| Power Dissipation ( $T_A \leq 25^\circ\text{C}$ )                         | $P_D$     | 230        | mW               |

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

| PARAMETER           | SYMBOL        | RATINGS | UNIT                      |
|---------------------|---------------|---------|---------------------------|
| Junction to Ambient | $\theta_{JA}$ | 500     | $^\circ\text{C}/\text{W}$ |

■ ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ , unless otherwise specified)

| PARAMETER                         | SYMBOL | TEST CONDITIONS  | MIN | TYP | MAX | UNIT          |
|-----------------------------------|--------|--|-----|-----|-----|---------------|
| Forward Voltage (See Fig.1)       | $V_F$  | $I_F = 0.1\text{mA}$   |     |     | 240 | mV            |
|                                   |        | $I_F = 1\text{mA}$   |     |     | 320 | mV            |
|                                   |        | $I_F = 10\text{mA}$  |     |     | 400 | mV            |
|                                   |        | $I_F = 30\text{mA}$  |     |     | 500 | mV            |
|                                   |        | $I_F = 100\text{mA}$   |     |     | 800 | mV            |
| Reverse Current (See Fig.2)       | $I_R$  | $V_R = 25\text{V}$   |     |     | 2   | $\mu\text{A}$ |
| Reverse Recovery Time (see Fig.4) | $t_r$  | When switched from $I_F = 10\text{mA}$ to $I_R = 10\text{mA}$ , $R_L = 100\Omega$ measured at $I_R = 1\text{mA}$ |     |     | 5   | ns            |
| Diode Capacitance (see Fig.3)     | $C_D$  | $f = 1\text{MHz}$ , $V_R = 1\text{V}$  |     |     | 10  | pF            |

## TYPICAL CHARACTERISTICS




Fig.1 Forward current as a function of forward voltage; typical values.




Fig.2 Reverse current as a function of reverse voltage; typical values.




Fig.3 Diode capacitance as a function of reverse voltage; typical values.




Fig.4 Reverse recovery definitions

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.