

SPECIFICATION OF QUARTZ CRYSTAL UNITS

1. HOLDER TYPE: SMD SEAM SEALING X'TAL 2.0*1.6
32.0000000 MHz

2. ELECTRICAL SPECIFICATIONS

Standard atmospheric conditions

Unless otherwise specified, the standard range of atmospheric conditions for making measurement

Ambient temperature	: 25±3°C
Relative humidity	: 40% ~ 70%

If there is any doubt about the results ,measurement shall be made within the following limits .


Ambient temperature	: 25±3°C
Relative humidity	: 40% ~ 70%

Electriacal characteristics measured by S&A250B or equivalent .

The crystal is using AT CUT (thinkness shear mode).

3.ELECTRICAL CHARACTERISTICS

	Parameters	SYM	Electrical Spec				Notes
			MIN	TYP	MAX	UNITS	
1	Nominal Frequency	FL	32.000000			MHz	
2	Oscillation mode	-	Fundamental			-	
3	Load Capacitance	CL	8			pF	
4	Frequency Tolerance	-	±10			ppm	at 25±3°C
5	Operating Temperature	-	-20	~	70	°C	
6	Temperature drift (TC)	-	±10			ppm	-20°C~70°C
	Temperature drift (TC)	-					
	Temperature drift (TC)	-					
7	Equivalent Resistance Rr	Rr	-	-	60	Ω	
8	Drive Level	DL	-	100	300	uW	
9	Shunt Capacitance C0	C0	-	-	2.00	pF	
10	Insulation Resistance	-	500	-	-	MΩ	at DC 100V
11	Aging	-	±1			ppm	First Year
12	Storage Temperature Range	-	-55	~	125	°C	



#1, #3 連接石英晶體 connected to quartz element
#2, #4 連接地 connected to the cover

建議焊接區域 Suggested solder padlayout

