

Features

- High Density Cell Design For Ultra Low $R_{DS(on)}$
- High Speed Switching
- ESD Protected Up to 2.5KV (HBM)
- Trench Power LV MOSFET Technology
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings


- Operating Junction Temperature Range : -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 96°C/W Junction to Ambient^(Note1)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	-20	V
Gate-Source Voltage	V_{GS}	±12	V
Drain Current $T_A=25^\circ\text{C}$ Steady State	I_D	-5.6	A
$T_A=70^\circ\text{C}$ Steady State		-4.5	
Pulsed Drain Current ^(Note2)	I_{DM}	-23	A
Total Power Dissipation	P_D	1.3	W

Note 1. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch.

2. Pulse Test: Pulse Width ≤ 300us, Duty cycle ≤ 2%.

Internal Structure:




1. GATE
2. SOURCE
3. DRAIN

Marking: 3415.


P-Channel Enhancement Mode Field Effect Transistor

SOT-23



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.110	0.120	2.80	3.04	
B	0.083	0.104	2.10	2.64	
C	0.047	0.055	1.20	1.40	
D	0.034	0.041	0.85	1.05	
E	0.067	0.083	1.70	2.10	
F	0.018	0.024	0.45	0.60	
G	0.0004	0.006	0.01	0.15	
H	0.035	0.043	0.90	1.10	
J	0.003	0.007	0.08	0.18	
K	0.012	0.020	0.30	0.51	
L	0.007	0.020	0.20	0.50	

Suggested Solder Pad Layout



Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =250μA	-20			V
Gate-Source Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =± 10V		±2.5	±10	μA
		V _{DS} =0V, V _{GS} =± 8V		±0.9	±2	μA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-20V, V _{GS} =0V			-1	μA
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250μA	-0.40	-0.62	-1.0	V
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =-4.5V, I _D =-5.6A		29	42	mΩ
		V _{GS} =-2.5V, I _D =-4.3A		36	55	
		V _{GS} =-1.8V, I _D =-2A		55	100	
Diode Forward Voltage	V _{SD}	V _{GS} =0V, I _S =-5.6A		-0.8	-1.2	V
Maximum Body-Diode Continuous Current	I _S				-5.6	A
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} =-10V,V _{GS} =0V,f =1MHz		940		pF
Output Capacitance	C _{oss}			219		
Reverse Transfer Capacitance	C _{rss}			116		
Switching Characteristics						
Total Gate Charge	Q _g	V _{DS} =-10V,V _{GS} =-4.5V,I _D =-4A		7.2		nC
Gate-Source Charge	Q _{gs}			1.2		
Gate-Drain Charge	Q _{gd}			1.6		
Turn-On Delay Time	t _{d(on)}	V _{GS} =-4.5V,V _{DS} =-10V,R _L =2.5Ω, R _{GEN} =3Ω		15		ns
Turn-On Rise Time	t _r			63		
Turn-Off Delay Time	t _{d(off)}			21		
Turn-Off Fall Time	t _f			12		

Curve Characteristics

Fig. 1 - Typical Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 - $R_{DS(ON)} - I_D$




Fig. 4 - Gate Charge




Fig. 5 - $I_S - V_{SD}$





Fig. 6 - Threshold Voltage



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.