

Product Overview

AP0202AT: Image Signal Processor, 2 MP

For complete documentation, see the data sheet.

AP0202AT is a dedicated automotive image co-processor that enables flexible camera platforms using high performance ON Semiconductor megapixel high dynamic range (HDR) sensors. The two-chip solution of sensor and co-processor allows for multiple camera price and performance points with re-use of circuit board design, fast time to market and design flexibility. Sensor performance is enhanced by the reduction in heat resulting from a separate co-processor chip while at the same time enabling high performance features. The AP0202AT includes a complete imaging color pipe and supports up to 2 Megapixel sensors. It offers parallel and OpenLDI output interfaces. This co-processor works with ON Semiconductor's AR0230AT, AR0132AT, AR0140AT and AR0136AT HDR automotive sensors, and is ideal for digital surround view cameras.

Features

- HDR

Applications

- Automotive

Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	Frame Rate (fps)	Video	Output Format	Compatible Sensors	Package Type
AP0202AT2L00XPGA 0-DR		AEC Qualified PPAP Capable Pb-free Halide free	Active	30	720p/60 fps 1080p/30 fps 1.2 MP/45 fps	H.264 MJPEG	AR0132AT AR0136AT	VFPGA-100
AP0202AT2L00XPGA 0-TR		AEC Qualified PPAP Capable Pb-free Halide free	Active	30	1080p/30 fps 1.2 MP/45 fps 720p/60 fps	MJPEG H.264	AR0136AT	VFPGA-100

For more information please contact your local sales support at www.onsemi.com.

Created on: 8/21/2020