



1. Features

- $R_{DS(on)}=3.5\text{m}\Omega$ (typ.) @ $V_{GS}=10\text{V}$
- 100% avalanche tested
- Reliable and rugged
- Lead free and green device available (RoHS Compliant)

2. Applications

- Switching application
- Power management for inverter systems
- UPS

3. Symbol



Pin	Function
1	Gate
2	Drain
3	Source

4. Ordering Information

Part Number	Package	Brand
KNB2806A	TO-263	KIA

5. Absolute maximum ratings

($T_A=25^\circ\text{C}$,unless otherwise noted)

Parameter		Symbol	Rating	Units
Drain-source voltage		V_{DSS}	60	V
Gate-source voltage		V_{GSS}	± 25	V
Maximum junction temperature		T_J	175	$^\circ\text{C}$
Storage temperature range		T_{STG}	-55 to 175	$^\circ\text{C}$
Diode continuous forward current	$T_c=25^\circ\text{C}$	I_S	150	A
Continuous drain current	$T_c=25^\circ\text{C}$	I_D^3	150	A
	$T_c=100^\circ\text{C}$		105	A
Pulse drain current*	$T_c=25^\circ\text{C}$	I_{DM}^4	580	A
Avalanche energy,single pulsed	$L=1\text{mH}$	E_{AS}^5	1200	mJ
Maximum power dissipation	$T_c=25^\circ\text{C}$	P_D	230	W
	$T_c=100^\circ\text{C}$		115	

6. Thermal characteristics

Parameter	Symbol	Rating	Unit
Thermal resistance,Junction-ambient	$R_{\theta JA}$	62.5	$^\circ\text{C/W}$
Thermal resistance,Junction-case	$R_{\theta JC}$	0.65	$^\circ\text{C/W}$

7. Electrical characteristics

($T_A=25^\circ\text{C}$,unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Units
Drain-source breakdown voltage	BV_{DSS}	$V_{\text{GS}}=0\text{V}, I_{\text{DS}}=250\mu\text{A}$	60	-	-	V
Zero gate voltage drain current	I_{DSS}	$V_{\text{DS}}=48\text{V}, V_{\text{GS}}=0\text{V}$	-	-	1	μA
		$T_J=85^\circ\text{C}$	-	-	10	
Gate threshold voltage	$V_{\text{GS(th)}}$	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=250\mu\text{A}$	2.0	3.0	4.0	V
Gate leakage current	I_{GSS}	$V_{\text{GS}}=\pm 25\text{V}, V_{\text{DS}}=0\text{V}$	-	-	± 100	nA
Drain-source on-state resistance	$R_{\text{DS(on)}}^1$	$V_{\text{GS}}=10\text{V}, I_{\text{D}}=60\text{A}$	-	3.5	4.5	$\text{m}\Omega$
Gate resistance	R_g	$V_{\text{DS}}=0\text{V}, V_{\text{GS}}=0\text{V}, f=1\text{MHz}$	-	0.7	-	Ω
Diode forward voltage	V_{SD}^1	$I_{\text{SD}}=60\text{A}, V_{\text{GS}}=0\text{V}$	-	0.8	1.2	V
Reverse recovery time ²	t_{rr}	$I_F=60\text{A}, V_{\text{DD}}=50\text{V}$ $dI_{\text{SD}}/dt=100\text{A}/\mu\text{s}$	-	30	-	nS
Reverse recovery charge ²	Q_{rr}		-	50	-	nC
Input capacitance ²	C_{iss}	$V_{\text{DS}}=25\text{V}, V_{\text{GS}}=0\text{V}, f=1\text{MHz}$	-	4376	-	pF
Output capacitance ²	C_{oss}		-	857	-	
Reverse transfer capacitance ²	C_{rss}		-	334	-	
Turn-on delay time ²	$t_{\text{d(on)}}$	$V_{\text{DD}}=30\text{V}, I_{\text{DS}}=60\text{A}, R_G=25\Omega, V_{\text{GS}}=10\text{V}$	-	28	-	ns
Rise time ²	t_r		-	18	-	
Turn-off delay time ²	$t_{\text{d(off)}}$		-	42	-	
Fall time ²	t_f		-	54	-	
Total gate charge ²	Q_g	$V_{\text{DS}}=48\text{V}, V_{\text{GS}}=10\text{V}$ $I_{\text{DS}}=60\text{A}$	-	130	-	nC
Gate-source charge ²	Q_{gs}		-	24	--	
Gate-drain charge ²	Q_{gd}		-	47	--	

Note:1:Pulse test;pulse width $\leq 300\text{us}$ duty cycle $\leq 2\%$.

2.Guaranteed by design,not subject to production testing.

3.Package limitation current is 75A,Calculated continuous current based on maximum allowable


junction temperature.

4:Repetitive rating,pulse width limited by junction temperature.


5:Starting $T_J=25^\circ\text{C}, L=1\text{mH}$.

8. Test circuits and waveforms


Power Dissipation




Drain Current




Safe Operation Area




Thermal Transient Impedance




Output Characteristics



Drain-Source On Resistance



Gate-Source On Resistance



Gate Threshold Voltage

