



Poles	Dimensions(mm)		Dimensions(mm)	
	A	B	A	B
02	2.00	6.00	08	14.00
03	4.00	8.00	09	16.00
04	6.00	10.00	10	18.00
05	8.00	12.00	11	22.00
06	10.00	14.00	12	24.00
07	12.00	16.00	13	26.00
				28.00

技术指标:

1. 塑件表面应光洁、无毛边、无明显收缩、缺陷、裂纹等现象。
2. 温度范围: -25° C~85° C.
3. 额定电压: 50V, AC, DC.
4. 接触电阻: ≤0.02Ω.
5. 绝缘电阻: ≥100MΩ

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE
DRAWN	G.M.Chen	2015/7/17
CHECKED		
APPROVALS		

DEALON 德之隆®
ELECTRONICS CO.,LTD

TOLERANCES ARE	30~40 ±0.30	40~50 ±0.20	50~100 ±0.15	ANGLE	±2°
	10~30 ±0.10	30~40 ±0.15	40~50 ±0.10	PART NO.	PH-XXA
	~5	~5	~5	UNIT: mm	SCALE: 1:1
				DRAWING NO.	SHEET 1 OF 1
					PROJ.

2.0 Pitch 直插