


## N-channel 650V, 4A, 1.0Ω Super-Junction Power MOSFET

Description	Product Summary								
<p>Super-junction power MOSFET is a revolutionary technology for high voltage power MOSFET , designed according to the SJ principle. The resulting device has extremely low on resistance,making it especially suitable for applications which require superior power density and outstanding efficiency.</p>	<table> <tr> <td data-bbox="798 321 957 354"><math>V_{DS} @ T_{j,25^\circ C}</math></td><td data-bbox="1092 321 1148 354">650V</td></tr> <tr> <td data-bbox="798 366 925 399"><math>R_{DS(on),max}</math></td><td data-bbox="1092 366 1148 399">1.0Ω</td></tr> <tr> <td data-bbox="798 411 846 444"><math>I_D</math></td><td data-bbox="1092 411 1148 444">4.0A</td></tr> <tr> <td data-bbox="798 455 878 489"><math>Q_{g,typ}</math></td><td data-bbox="1092 455 1164 489">9.1 nC</td></tr> </table>	$V_{DS} @ T_{j,25^\circ C}$	650V	$R_{DS(on),max}$	1.0Ω	$I_D$	4.0A	$Q_{g,typ}$	9.1 nC
$V_{DS} @ T_{j,25^\circ C}$	650V								
$R_{DS(on),max}$	1.0Ω								
$I_D$	4.0A								
$Q_{g,typ}$	9.1 nC								
	 <b>TO-252</b>								
	 <b>TO-251</b>								
	 <b>TO-220F</b>								
	 <b>Drain</b> <b>Gate</b> <b>Source</b>								
	 <b>RoHS</b>								
	<b>N-Channel MOSFET</b>								

### Marking information

Product	Package	Marking	Packing method
RMA65R1K0SN	TO-252	RMA65R1K0SN	Reel
RMG65R1K0SN	TO-251	RMG65R1K0SN	Tube
RMC65R1K0SN	TO-220F	RMC65R1K0SN	Tube

### Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DSS}$	650	V
Continuous drain current ( $T_c = 25^\circ C$ )	$I_D$	4	A
( $T_c = 100^\circ C$ )		2.5	A
Pulsed drain current <sup>1)</sup>	$I_{DM}$	12	A
Gate-Source voltage	$V_{GSS}$	$\pm 30$	V
Avalanche energy, single pulse <sup>2)</sup>	$E_{AS}$	50	mJ
Avalanche current, repetitive <sup>3)</sup>	$I_{AR}$	0.9	A
Power Dissipation TO-252 /TO-251 ( $T_c = 25^\circ C$ )	$P_D$	37	W
- Derate above 25°C		0.3	W/°C
Power Dissipation TO-220F ( $T_c = 25^\circ C$ )	$P_D$	30	W
- Derate above 25°C		0.24	W/°C
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150	°C
Continuous diode forward current	$I_S$	4	A

Diode pulse current	I <sub>S,pulse</sub>	12	A
---------------------	----------------------	----	---

### Thermal Characteristics

Parameter	Symbol	Value		Unit
		TO252/TO-251	TO-220F	
Thermal Resistance, Junction-to-Case	R <sub>θJC</sub>	2.8	4.4	°C/W
Thermal Resistance, Junction-to-Ambient	R <sub>θJA</sub>	62	73	°C/W
Soldering temperature, wave soldering only allowed at leads. (1.6mm from case for 10s)	T <sub>sold</sub>	260	260	°C

### Electrical Characteristics

T<sub>c</sub> = 25°C unless otherwise noted

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
<b>Static characteristics</b>						
Drain-source breakdown voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0 V, I <sub>D</sub> =250uA	650	-	-	V
Gate threshold voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250uA	2.5		4.0	V
Drain cut-off current	I <sub>DSS</sub>	V <sub>DS</sub> =650 V, V <sub>GS</sub> =0 V, T <sub>j</sub> = 25°C T <sub>j</sub> = 125°C	-	-	1	μA
Gate leakage current, Forward	I <sub>GSSF</sub>	V <sub>GS</sub> =30 V, V <sub>DS</sub> =0 V	-	-	100	nA
Gate leakage current, Reverse	I <sub>GSRR</sub>	V <sub>GS</sub> =-30 V, V <sub>DS</sub> =0 V	-	-	-100	nA
Drain-source on-state resistance	R <sub>D(on)</sub>	V <sub>GS</sub> =10 V, I <sub>D</sub> =2 A T <sub>j</sub> = 25°C	-	0.88	1.0	Ω
<b>Dynamic characteristics</b>						
Input capacitance	C <sub>iss</sub>	V <sub>DS</sub> = 100 V, V <sub>GS</sub> = 0 V, f = 1MHz	-	315	-	pF
Output capacitance	C <sub>oss</sub>		-	27	-	
Reverse transfer capacitance	C <sub>rss</sub>		-	1.2	-	
Turn-on delay time	t <sub>d(on)</sub>	V <sub>DD</sub> = 400V, I <sub>D</sub> = 2A R <sub>G</sub> = 25Ω, V <sub>GS</sub> =10V	-	9.4	-	ns
Rise time	t <sub>r</sub>		-	22.6	-	
Turn-off delay time	t <sub>d(off)</sub>		-	36.4	-	
Fall time	t <sub>f</sub>		-	25.4	-	
<b>Gate charge characteristics</b>						
Gate to source charge	Q <sub>gs</sub>	V <sub>DD</sub> =520 V, I <sub>D</sub> =2A, V <sub>GS</sub> =0 to 10 V	-	2.1	-	nC
Gate to drain charge	Q <sub>gd</sub>		-	4.0	-	
Gate charge total	Q <sub>g</sub>		-	9.1	-	
Gate plateau voltage	V <sub>plateau</sub>		-	5.5	-	
<b>Reverse diode characteristics</b>						
Diode forward voltage	V <sub>SD</sub>	V <sub>GS</sub> =0 V, I <sub>F</sub> =2A	-	0.85	-	V
Reverse recovery time	t <sub>rr</sub>	V <sub>R</sub> =50 V, I <sub>F</sub> =2A, dI <sub>F</sub> /dt=100 A/μs	-	159	-	ns
Reverse recovery charge	Q <sub>rr</sub>		-	0.93	-	μC
Peak reverse recovery current	I <sub>rrm</sub>		-	11.2	-	A

Notes:

1. Limited by maximum junction temperature, maximum duty cycle is 0.75.
2.  $I_{AS} = 1A$ ,  $V_{DD} = 50V$ , Starting  $T_j = 25^\circ C$ .

**Electrical Characteristics Diagrams**

Figure 1. Output Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 5. Gate Charge Characteristics




Figure 2. Transfer Characteristics




Figure 4. Capacitance Characteristics




Figure 6. Body Diode Forward Voltage




Figure 7. Breakdown Voltage vs. Temperature





Figure 9. Maximum Safe Operating Area  
TO-252/TO-251



Shaanxi Reactor Microelectronics  
Figure 8. On-Resistance vs. Temperature









Figure 10. Maximum Safe Operating Area  
TO-220F



## Test Circuits


**Gate Charge Test Circuit & Waveform**

**Switching Test Circuit & Waveform**

**Unclamped Inductive Switching Test Circuit & Waveform**


**Mechanical Dimensions for TO-252**



单位: mm

SYMBOL	mm		
	MIN	NOM	MAX
*A	2.20	2.30	2.38
*A1	0.00	-	0.10
A2	0.97	1.07	1.17
*b	0.72	0.78	0.85
b1	0.71	0.76	0.81
*b3	5.23	5.33	5.46
b4	4.27	4.32	4.37
b5	0.72	0.88	0.93
*c	0.47	0.53	0.58
c1	0.46	0.51	0.56
*D	6.00	6.10	6.20
D1		5.30REF	

*E	6.50	6.60	6.70
E1	4.70	4.83	4.92
*e	2.286BSC		
L	1.40	1.50	1.70
L1	2.90REF		
L2	0.51BSC		
*L3	0.90	-	1.25
*L4	0.60	0.80	1.00
L5	1.70	1.80	1.90
L6	0	0.047	0.123
φ	0°	-	8°
*φ1	5°	7°	9°
φ2	5°	7°	9°
K	0.40REF		

**Mechanical Dimensions for TO-251**


SYMBOL	MM		
	MIN	NOM	MAX
*A	2.20	2.30	2.38
*A2	0.97	1.07	1.17
*b	0.72	0.78	0.85
b1	0.71	0.76	0.81
*b2	0.72	0.88	0.95
*b3	5.23	5.33	5.46
*c	0.47	0.53	0.58
c1	0.46	0.51	0.56
*D	6.00	6.10	6.20
D1	5.30REF		
*E	6.50	6.60	6.70
E1	4.70	4.83	4.92
*e	2.286BSC		
*L1	9.20	9.40	9.60
L2	1.25	1.35	1.45
*L3	0.90	1.02	1.25
L5	1.70	1.80	1.90
*θ1	5°	7°	9°
θ2	5°	7°	9°
θ3	11°	13°	15°
K	0.40REF		

**Mechanical Dimensions for TO-220F**


Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
C	4.3	4.7	b1	2.9	3.9
A	9.7	10.3	α	0.55	0.75
B	14.7	15.3	E	2.29	2.79
B1	3.8	4.0	E1	2.29	2.79
B2	2.9	3.1	C1	2.5	2.9
R	3.0	3.4	C2	2.5	2.7
b	12.5	13.5	C	0.5	0.7