

Ordering Information

G PEB101 - XX XX A 081 C 1 H X

No. of Pins per Row
02~50

Standard Plating
02=Gold Flash
Selective Plating
01=Tin


Color
1=Black

Standard Packing
C=Tube (無合適膠管)
Selective Packing
A=Box

REV.	LOCAS.	DESCRIPTION	DATE	DRAWN
A	NEW	INTERIM INITIAL RELEASE.	2020.11.26	郭丙建

Specifications
 Current Rating: 1.0Amp
 Insulation Resistance: 1000MΩMin.
 Dielectric Withstanding Voltage: 600VAC
 Contact Resistance: 20mΩMax.
 Operating Temperature: -40°C to +105°C
 Materials
 Contact Material: Brass
 Insulator Material: High Temperature Thermoplastic, UL 94V-0 LCP or the equivalent material
 All materials must meet GREENCONN hazardous substances control standards.

Recommended P.C.Board Layout
 (Tolerance: ±0.05)



3RD.ANG
PROJ.
PAGE. 1/1

GENERAL TOLERANCE	
X.*±5.0°	X.±0.30
.X*±3.0°	.X±0.25
.XX*±2.0°	.XX±0.15
.XXX*±1.0°	.XXX±0.10

DESIGNED: 林煌隆
 CHECKED: 林煌隆
 APPROVED: 陳義昌

DATE: 2020.11.26
 DATE: 2020.11.26
 DATE: 2020.11.26

DWG. NO.
GPEB101-CA81CH
 PART NO.
GPEB101-XXXX A081C1HX

TITLE.
 1.27 PIN HEADER
 SINGLE ROW R/A TYPE
 BASE 2.54H