

NOTES:

I. MATERIALS AND FINISHES:

- | | |
|-----------------------|---|
| SHELL | - ZINC ALLOY, NICKEL PLATING (.000100" MIN. THINCK) |
| FERRULE | - BRASS, NICKEL PLATING (.000100" MIN. THINCK) |
| WASHER | - BRASS, NICKEL PLATING (.000100" MIN. THINCK) |
| SPRING | - BeCu, NICKEL PLATING (.000100" MIN. THINCK) |
| CONTACT | - BRASS, GOLD PLATING (.000003" MIN. THINCK) |
| BODY & RETAINING RING | - BRASS, NICKEL PLATING (.000100" MIN. THINCK) |
| INSULATOR & SLEEVE | - DELRIN, NATURAL |
| GASKET | - SILICONE RUBBER, RED |

2. ELECTRICAL:

- A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 4 GHz
C. DIELECTRIC WITHSTANDING VOLTAGE: 1200 VRMS, MIN.

3. MECHANICAL:

- A. DURABILITY: 500 CYCLES MIN.
B. TEMPERATURE RANGE: -40°C TO $+85^{\circ}\text{C}$

4. CRIMPED FERRULE HEX CRIMP SIZE .178"

5. CENTER CONTACT ASSEMBLY:

OPTION A: CRIMP CENTER CONTACT WITH OPEN FRAME HEX CRIMP TOOL M22520/5-01 (HX4) USING .068" HEX CRIMP DIE SET.

OPTION B: CRIMP CENTER CONTACT USING ADJUSTABLE QUICK CRIMP TOOL FOR BNC, CTL-6. TOOL RACHET ADJUST WHEEL


NEEDS TO BE SET TO PROPER CHANNEL IN ORDER TO MEET PROPER CABLE RETENTION FORCE.

OPTION C: SOLDER THE CENTER CONTACT TO CABLE CENTER CONDUCTOR.

6. PACKAGING:

- A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 31-315-RFX, DATE CODE"

7. SHOWS CABLE ENTRY DIMENSIONS.



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <0.5mm 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES ± 0.05mm ±0.1mm ±0.2mm ± 0.3mm ±1°				MATERIAL - -		DRAWN M. ZHANG		DATE 26-Dec-16		TITLE BNC CRIMP PLUG (FOR RG-174/U, 188A/U 316/U CABLE)				Amphenol RF www.amphenolrf.com			
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.				REFERENCE AND		ENGINEER O. BARTHELMES		DATE 28-Jan-02									
				CONFIGURATION LEVEL: In Work		APPROVED S. HSIEH		DATE 26-Dec-16		SCALE: 4.0:1.0		SHEET 2 OF 2					
				FINISH		CAD FILE		DWG SIZE B		REV E							
														DRAWING NO. 31-315-RFX		ITEM NO. 31-315-RFX	