

REV.	LOCAS.	DESCRIPTION	DATE	DRAWN
087		依業務要求新增A156C1WX規格圖檔	2016.09.22	胡金花
088		依業務要求新增A064R1BX規格圖檔	2016.12.13	馮國東
089		依業務要求新增A092R1BX與A101R1BX規格圖檔	2016.12.15	馮國東
090		依業務要求新增A159R1WX規格圖檔	2016.12.28	馮國東
091		依業務要求新增A160R1WX規格圖檔	2016.12.29	馮國東
092		依業務要求新增A161R1WX規格圖檔	2017.01.12	馮國東

TABLE.

Serial No.	Dimension Information		Pin request	Remark
	Dim.A	Dim.B	void pins	
001A1BX	3.80	3.05	-----	
003A1BX	2.50	2.50	-----	
007A1BX	4.00	2.60	-----	
007C1BX	4.00	2.60	-----	
007B1BX	4.00	2.60	-----	
010A1BX	4.00	3.00	-----	
011A1BX	2.00	2.80	-----	
012A1BX	20.00	3.00	-----	
014A1BX	5.85	2.85	-----	
016A1BX	4.00	2.80	-----	
016B1BX	4.00	2.80	-----	
019A1BX	3.20	3.50	-----	
019B1BX	3.20	3.50	-----	
022A1BX	7.50	3.00	-----	
023A1BX	4.40	2.80	-----	
028A1BX	4.00	2.10	-----	
034A1BX	4.10	2.70	-----	
034B1BX	4.10	2.70	-----	
035A1BX	3.70	3.00	-----	
035B1AX	3.70	3.00	-----	
036A1BX	8.10	2.80	-----	
037A1BX	5.00	3.10	-----	
041A1BX	4.50	2.54	-----	
042B1BX	2.00	2.00	-----	
043A1BX	4.00	2.70	-----	
043B1BX	4.00	2.70	-----	
044A1BX	8.75	3.85	-----	
044B1BX	8.75	3.85	-----	
046B1BX	5.50	1.60	-----	
047B1BX	7.70	1.60	-----	
048A1BX	3.70	8.90	-----	
049A1BX	3.50	3.50	-----	

Serial No.	Dimension Information		Pin request	Remark
	Dim.A	Dim.B	void pins	
050A1BX	6.30	3.20	-----	
051A1BX	6.30	1.80	-----	
052B1BX	3.50	1.20	-----	
053A1BX	4.00	2.80	-----	
054A1BX	12.00	2.90	-----	
055A1BX	4.00	4.00	-----	
056A1BX	7.00	3.00	-----	
057B1BX	3.50	3.40	-----	
058B1BX	6.00	2.80	-----	
059A1BX	12.30	3.30	-----	
700A1BX	12.30	3.30	Void No.15	
061A1BX	6.10	2.00	-----	
062C1BX	9.50	2.75	-----	
063B1BX	5.08	3.00	-----	
064B1BX	5.00	2.80	-----	
065B1BX	7.00	2.80	-----	
066A1BX	3.50	3.00	-----	
067A1BX	4.50	3.60	-----	
068A1BX	9.00	3.00	-----	
069B1BX	3.20	5.90	-----	
070B1BX	6.00	-----	-----	
071B1BX	5.00	3.50	-----	
071A1BX	5.00	3.50	-----	
072B1BX	8.90	3.20	-----	
073A1BX	5.00	5.00	-----	
074B1BX	3.00	5.10	-----	
075B1BX	4.25	2.45	-----	
076B1BX	2.50	2.00	-----	
077C1AX	3.80	2.90	-----	
078A1BX	5.00	2.50	-----	
078B1BX	5.00	2.50	-----	
079B1BX	3.50	2.60	-----	
080B1BX	6.85	5.25	-----	
081B1BX	5.00	2.10	-----	
082B1BX	7.00	3.60	-----	
083B1BX	2.50	2.80	-----	
084A1BX	8.00	0	-----	
085A1BX	4.60	6.00	-----	
086A1BX	5.00	7.00	-----	
087A1BX	6.50	2.50	-----	
088A1BX	6.60	2.80	-----	

格稜股份有限公司 Greenconn Corporation		GENERAL TOLERANCE		DESIGNED: 馮國東	DATE: 2017.01.12	DWG. NO. GPFA202-CAXXXXX	2.00 PIN HEADER DUAL ROWS DIP TYPE CONNECTOR
		X. \pm 5.0"	X. \pm 0.30	CHECKED: 曹 熙	DATE: 2017.01.12		
.X \pm 3.0"	.X \pm 0.25	CO SIGNED: 劉北平	DATE: 2017.01.12				
.XX \pm 2.0"	.XX \pm 0.15	APPROVED: 李 輝	DATE: 2017.01.12				
REV. 092	UNIT. mm	SCALE. 3:1	PAGE. 2/4			PART NO. GPFA202-XXXX AXXX XXXX	

024

REV.	LOCAS.	DESCRIPTION	DATE	DRAWN
087		依業務要求新增A156C1WX規格圖檔	2016.09.22	胡金花
088		依業務要求新增A064R1BX規格圖檔	2016.12.13	馮國東
089		依業務要求新增A092R1BX與A101R1BX規格圖檔	2016.12.15	馮國東
090		依業務要求新增A159R1WX規格圖檔	2016.12.28	馮國東
091		依業務要求新增A160R1WX規格圖檔	2016.12.29	馮國東
092		依業務要求新增A161R1WX規格圖檔	2017.01.12	馮國東

TABLE.

Serial No.	Dimension Information		Pin request void pins	Remark
	Dim.A	Dim.B		
089B1BX	3.30	7.00	-----	
090B1BX	6.50	3.60	-----	
091A1BX	1.00	5.70	-----	
092B1BX	10.00	2.60	-----	
020B1BX	3.50	2.00	-----	
073B1AX	5.00	5.00	-----	
069R1BX	3.20	5.90	-----	
019R1BX	3.20	3.50	-----	
044R1BX	8.75	3.85	-----	
035R1AX	3.70	3.00	-----	
080R1BX	6.85	5.25	-----	
043R1BX	4.00	2.70	-----	
093B1BX	3.20	4.80	-----	
094B1BX	3.50	2.30	-----	
095B1BX	4.65	2.05	-----	
007R1BX	4.00	2.60	-----	
096B1BX	2.20	2.40	-----	
097C1BX	2.40	2.60	-----	
061B1BX	6.10	2.00	-----	
098B1BX	11.00	3.10	-----	
099R1BX	7.35	2.70	-----	
100B1BX	6.00	1.50	-----	
101B1BX	8.00	2.80	-----	
035R1BX	3.70	3.00	-----	
068B1BX	9.00	3.00	-----	
103B1BX	5.20	2.80	-----	
650B1BX	5.20	2.80	Void No.06,07,08,11, 12,13,14,17,18,19, 20,23,24,27,28,29, 30,33,34,35,36 PINS	
104R1BX	12.70	2.90	-----	
035B1BX	3.70	3.00	-----	

Serial No.	Dimension Information		Pin request void pins	Remark
	Dim.A	Dim.B		
105B1BX	6.30	2.20	-----	
106A1BX	4.30	9.30	-----	
107A1BX	5.70	4.30	-----	
014B1BX	5.85	2.85	-----	
108B1BX	5.65	3.00	-----	
109B1BX	3.05	3.10	-----	
110B1BX	7.50	2.60	-----	
016B1AX	4.00	2.80	-----	
112B1BX	19.00	3.00	-----	
001B1BX	3.80	3.05	-----	
113R1BX	4.50	11.15	-----	
114R1BX	4.45	12.65	-----	
115R1BX	4.45	15.15	-----	
116R1BX	4.45	13.15	-----	
117C1BX	7.80	2.50	-----	
118B1BX	14.25	3.00	-----	
035C1AX	3.70	3.00	-----	
073B1BX	5.00	5.00	-----	
010B1BX	4.00	3.00	-----	
119A1BX	11.30	2.80	-----	
120C1AX	6.20	3.00	-----	
121B1BX	3.20	3.00	-----	
122B1BX	4.20	2.50	-----	
123B1BX	6.90	3.20	-----	
124B1BX	12.00	3.60	-----	
125R1BX	1.00	4.00	-----	
126R1BX	8.60	3.50	-----	
049R1BX	3.50	3.50	-----	
127R1BX	10.55	2.54	-----	
075R1BX	4.25	2.45	-----	
043C1BX	4.00	2.70	-----	
109R1BX	3.05	3.10	-----	
019A1AX	3.20	3.50	-----	
128R1BX	7.35	3.25	-----	
012R1BX	20.00	3.00	-----	
061R1BX	6.10	2.00	-----	
012C1BX	20.00	3.00	-----	
042R1BX	2.00	2.00	-----	

格稜股份有限公司 Greenconn Corporation				GENERAL TOLERANCE		DESIGNED: 馮國東	DATE: 2017.01.12	DWG. NO. GPFA202-CAXXXXX	2.00 PIN HEADER DUAL ROWS DIP TYPE CONNECTOR
				X.*±5.0°	X.±0.30	CHECKED: 曹 熙	DATE: 2017.01.12		
.X*±3.0°	.X±0.25	CO SIGNED: 劉北平	DATE: 2017.01.12	PART NO. GPFA202-XXXX AXXX XXXX					
.XX*±2.0°	.XX±0.15	APPROVED: 李 輝	DATE: 2017.01.12						
REV. 092	UNIT. mm	SCALE. 3:1	PAGE. 3/4		.XXX*±1.0°	.XXX±0.10			

