欧式通用端子台

欧米式に通用できる端子台
European general terminal block

T022/T022-K

T023/T023-K

T024/T024-K

专利 | CE | RoHS | EU 指令 | 省空间 | PLC

T022专利号：201230161014.3
T023专利号：200930166663.0
T024专利号：200930166678.7

有关符合EU指令的产品请参阅附-35

询问胜蓝
0755-8886 0059
当日出货

特点 Features

* T022/T022-K为20P连接器对应20P端子连接，可对应市面上所有带20P MIL插头的PLC连接。
* T023/T023-K为34P连接器对应34P端子连接，对应KEYENCE的KV-32XA/C、KV-64XA/C、KV-32TA/C、KV-64TA/C扩展板使用。
* T024/T024-K为40P连接器对应40P端子连接，体积最小型化设计。

* T022/T022-Kは20Pの連結器対応20P端子連結、市場の中で全部の20P MILプラグのPLC連結に対応できます。
* T023/T023-Kは34Pの連結器対応34P端子連結、KEYENCEのKV-32XA/C、KV-64XA/C、KV-32TA/C、KV-64TA/C拡張に対応使用します。
* T024/T024-Kは40P連結器対応40P端子連結、体積は最小型に設計します。

* T022/T022-K is a 20pin terminal connection for 20pin connector, suitable to all PLC connections with 20pin MIL plug on the market.
* T023/T023-K is a 34pin terminal connection for 34pin connector, applicable to KV-32XA/C, KV-64XA/C, KV-32TA/C and KV-64TA/C expansion modules of KEYENCE PLCs.
* T024T024/T024-K is a 40pin terminal connection for 40pin connector, small size for space saving.

注意事项 note

- 订购前请确认好PLC引脚定义，选择适合的端子台。
- 和PLC连接时，请务必使用本公司开发的与之对应的专用电缆线。
- Before ordering, please confirm the PLC pin definition,choose the suitable terminal.
- When PLC connection,please be sure to use the company developed and the corr esponding special cable.

适合电线 Suitable wire

1.5 mm² Following/ AWG16；
剥线长度：6mm

选型参考 Type selection reference

型号 Model	T022	T022-K	T023	T023-K	T024	T024-K
名称 Name	欧式通用20位端子台		欧式通用34位端子台		欧式通用40位端子台	

适用PLC Suitable PLC

OMRON	CJ1W-MD232 CJ1W-MD233				CJ1W-ID231 CJ1W-ID261 CJ1W-MD261(N) CJ1W-ID232 CJ1W-ID262 CJ1W-MD263(N) CJ1W-MD563(N) CJ1W-OD231 CJ1W-OD261 CJ1W-MD261(Out)	CJ1W-OD232 CJ1W-OD233 CJ1W-OD262 CJ1W-OD263 CJ1W-MD263(Out) CJ1W-MD563(Out) CJ1M-CPU21 CJ1M-CPU22 CJ1M-CPU23
MITSUBISHI	FX1NC-16MT FX1NC-32MT FX2NC-16MT FX2NC-32MT FX3UC-32MT FX2NC-16EX FX2NC-16EX-C	FX2NC-16EXL-C FX2NC-16EYT FX2NC-17EYT-C FX2N-10PG FX2N-10GM FX2N-20GM			QX41 QX41-S1 QX42 QX42-S1 QX71 QX72 QY41P	QY42P QY71 QH42P QD71P4 QD70P QD70D QD75M
KEYENCE		KV-NC16EX KV-NC16ET	KV-C32XA/C KV-C64XA/C KV-C32TA/C KV-C64TA/C	KV-NC32T KV-NC32EX KV-NC32ET KV-NC16EXT	KV-1000 KV-HQ0S KV-3000 KV-HH0S KV-5000	KV-SH04PL
Panasonic					FPG-XY64D2T/P FP2-C1D FP2-X32D2 FP2-X64D2 FP2-32T/P FP2-Y64T/P FP2-XY64D2T FP2-XY64D7T	FP2-XY64D2P FP2-XY64D7P FP2-PP21 FP2-PP22 FP2-PP41 FP2-PP42 FP2-HSCT FP2-PXYT
SIEMENS					40P Plug with a full range	
Yokogawa					F3WD64-3N F3WD32-3F	F3WD64-3F

关联产品 Related products

适用电缆 Suitable cable			
X200-2 X218-1 X218-9	X200-3 X210-3	X200-4 X210-4 X210-5 X218-6	

（详情请参阅本目录缆线系列）For details, please refer to the directory cable series

规格参数 Specifications

输入 Input	额定电流 Nominal operating current	1A
	额定电压 Nominal coil voltage	DC24V
输出侧对应 Corresponding output Devices	Servo motor control signal line circuit	Button Switch,Photoelectric Switch,Solenoid, Indicator,Stepping Servo Motor,etc.

外形图 Dimensions

T022/T022-K



T023/T023-K



T024/T024-K



注明：T022(T022-K)外形尺寸相同，T023(T023-K)外形尺寸相同。
Note: T022 and T022-K have the same shape size, T023 and T023-K have the same shape size.

- 用2个M4的螺丝可固定在零件安装的地方。建议使用M4X16的螺丝，螺纹孔深3mm以上。
- 可安装在标准35mm的DIN导轨上
- Screw Mounting:use M4*16 screw,screw hole depth＞3mm.
- DIN Rail Mounting:Standard 35mm DIN RAIL.

配线图 Wiring Diagram

T022



T022-K



T023



T023-K



T024

T024-K