

● General Description

The AGM40P65E combines advanced trench MOSFET technology with a low resistance package to provide extremely low $R_{DS(ON)}$.

This device is ideal for load switch and battery protection applications.

● Features

- Advance high cell density Trench technology

- Low $R_{DS(ON)}$ to minimize conductive loss

- Low Gate Charge for fast switching

- Low Thermal resistance

● Application

- MB/VGA Vcore

- SMPS 2nd Synchronous Rectifier


- POL application

- BLDC Motor driver

Product Summary

BVDSS	RDS(on)	ID
-40V	70mΩ	-5A

SOT-23-3 Pin Configuration



Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
40P65E	AGM40P65E	SOT-23-3	178mm	8mm	3000

Table 1. Absolute Maximum Ratings (TA=25°C)

Symbol	Parameter	Value	Unit
VDS	Drain-Source Voltage (VGS=0V)	-40	V
VGS	Gate-Source Voltage (VDS=0V)	±20	V
ID	Drain Current-Continuous(TA=25°C) (Note 1)	-3.3	A
	Drain Current-Continuous(TA=70°C)	-2.0	A
IDM (pulse)	Drain Current-Continuous@ Current-Pulsed (Note 2)	-13	A
PD	Maximum Power Dissipation(TA=25°C)	1.4	W
TJ,TSTG	Operating Junction and Storage Temperature Range	-55 To 150	°C

Table 2. Thermal Characteristic

Symbol	Parameter	Typ	Max	Unit
R _{θJA}	Thermal Resistance Junction-ambient (Steady State) ¹	---	89	°C/W







Table 3. Electrical Characteristics (TA=25°C unless otherwise noted)







Symbol	Parameter	Conditions	Min	Typ	Max	Unit
On/Off States						
BVDSS	Drain-Source Breakdown Voltage	VGS=0V ID=250μA	-40	--	--	V
IDSS	Zero Gate Voltage Drain Current	VDS=-40V, VGS=0V	--	--	-1	μA
IGSS	Gate-Body Leakage Current	VGS=±20V, VDS=0V	--	--	±100	nA
VGS(th)	Gate Threshold Voltage	VDS=VGS, ID=-250μA	-1.1	-1.6	-2.3	V
gFS	Forward Transconductance	VDS=-5V, ID=-3.1A	--	-5	--	S
RDS(on)	Drain-Source On-State Resistance	VGS=-10V, ID=-3A	--	70	85	mΩ
		VGS=-4.5V, ID=-2A	--	95	120	mΩ
Dynamic Characteristics						
Ciss	Input Capacitance	VDS=-20V, VGS=0V, F=1MHZ	--	600	--	pF
Coss	Output Capacitance		--	90	--	pF
Crss	Reverse Transfer Capacitance		--	70	--	pF
Rg	Gate resistance	VGS=0V, VDS=0V, f=1.0MHz	--	--	--	Ω
Switching Times						
td(on)	Turn-on Delay Time	VGS=-10V, VDS=-20V, RGEN=3Ω, ID=-3A	--	9	--	nS
tr	Turn-on Rise Time		--	8	--	nS
td(off)	Turn-Off Delay Time		--	25	--	nS
tf	Turn-Off Fall Time		--	9	--	nS
Qg	Total Gate Charge	VGS=-10V, VDS=-20V, ID=-3A	--	14	--	nC
Qgs	Gate-Source Charge		--	2.9	--	nC
Qgd	Gate-Drain Charge		--	3.8	--	nC
Source-Drain Diode Characteristics						
ISD	Source-Drain Current(Body Diode)		--	--	-5.0	A
VSD	Forward on Voltage	VGS=0V, IS=-3A	--	--	-1.2	V
trr	Reverse Recovery Time	IF=-3A, dl/dt=100A/μs,	--	--	--	ns
Qrr	Reverse Recovery Charge		--	--	--	nc



Notes 1.The maximum current rating is package limited.

Notes 2.Repetitive Rating: Pulse width limited by maximum junction temperature


Notes 3.EAS condition: TJ=25°C

Typical Electrical and Thermal Characteristics**Figure 1:Switching Test Circuit****Figure 2:Switching Waveforms****Figure 3 Power Dissipation****Figure 4 Drain Current****Figure 5 Output Characteristics****Figure 6 Drain-Source On-Resistance**

**Figure 7 Transfer Characteristics****Figure 8 Drain-Source On-Resistance****Figure 9 $R_{DS(on)}$ vs V_{GS}** **Figure 10 Capacitance vs V_{DS}** **Figure 11 Gate Charge****Figure 12 Source-Drain Diode Forward**

**Figure 13 Safe Operation Area****Figure 14 Normalized Maximum Transient Thermal Impedance**

SOT-23-3L
PACKAGE OUTLINE DIMENSIONS



COMMON DIMENSIONS CUNITS MEASURE=MILLIMETER			
SYMBOL	MIN	NOM	MAX
A	1.050	—	1.300
A1	0.000	—	0.200
A2	1.050	—	1.200
b	0.300	0.400	0.500
c	0.100	—	0.200
D	2.820	2.900	3.020
E	1.500	1.600	1.700
E1	2.650	2.800	2.950
e	0.950TYP		
e1	1.800	1.900	2.000
L	0.6REF		
L1	0.300	0.450	0.600
θ	0°	--	8°

Unit:mm

Disclaimer:

The information provided in this document is believed to be accurate and reliable. however, Shenzhen Core Control Electronics Technology Co., Ltd. does not assume any responsibility for the following consequences. Do not consider the use of such information or use beyond its scope.

The information mentioned in this document may be changed at any time without notice.

The products and information provided in this document do not infringe patents. Shenzhen Core Control Electronics Technology Co., Ltd. assumes no responsibility for any infringement of any other rights of third parties. The result of using such products and information.

This document is the second version issued on March 10, 2023. This document replaces and Replace all previously provided information.

 It is a registered trademark of Shenzhen Core Control Electronics Technology Co., Ltd.

Copyright © 2017 Shenzhen Core Control Electronics Technology Co., Ltd. all rights reserved.