


REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	07AUG2017	C.W	I.Y
	B	REVISED PER PCN E-19-014633	15FEB2019	AK	NS



NOTES:

1. SECONDARY WEDGE LOCK SOLD SEPARATELY: W2PX-XXXX.
(X = A,B,C,D KEY, XXXX = ALL MODIFICATIONS)
2. THIS RECEPTACLE MATES WITH DT06-2S-XXXX PLUG.
(XXXX = ALL MODIFICATIONS)
- ③ MATERIAL: HOUSING: PA66 GF15, SEE TABLE FOR COLOR
GROMMET: VMQ SEE TABLE FOR COLOR
- ④ DATE CODE: IDENTIFIES THE YEAR, MONTH, DAY AND HOUR OF ASSEMBLY.
YEAR: FIRST AND SECOND DIGITS. (17 = 2017)
MONTH:THIRD DIGIT, EXCLUDING I. A = JAN, B = FEB,
C = MARCH ... (K = OCTOBER)
DAY: FOURTH AND FIFTH DIGITS (14 = 14th DAY)
HOUR:SIXTH AND SEVENTH DIGITS (11 = 11AM)
- ⑤ "E" IDENTIFIES E-SEAL.
6. FOR CONTACTS AND WIRE PERFORMANCE AND APPLICATION
CHARACTERISTICS SEE CUSTOMER DRAWING 0425-015-0000.
- ⑦ XXXX IDENTIFIES THE MODIFICATION NUMBER,
IF APPLICABLE. EXAMPLE: "TB31" FOR DT04-2P-TB31,

CONTACT SIZE	WIRE RANGE	SEALING RANGE	SEAL IDENTIFICATION
#16	14-20AWG (2.5-0.5mm ²)	.088-.145 [2.23-3.68]	STANDARD SEAL N-SEAL
		.053-.120 [1.35-3.05]	EXTRA THIN SEAL E-SEAL

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C. WAN	15OCT2017		 TE Connectivity	
		CHK E. JIANG	15OCT2017			
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD L. YIN	15OCT2017	
		0 PLC ±.		DT SERIES, SNAP CAPS 2 WAY RECEPTACLE, DT04-2P-TXXX		
		1 PLC ±.				
		2 PLC ±0.64				
		3 PLC ±0.64				
4 PLC ±.		APPLICATION SPEC		NAME		
ANGLES FINISH		114-151009				
MATERIAL		WEIGHT		SIZE	CAGE CODE	DRAWING NO
		SEE TABLES		A200779		©-2303812
				RESTRICTED TO		
				-		
CUSTOMER DRAWING				SCALE	2:1	
				SHEET		1 of 2
				REV		B

