SIEMENS

Data sheet US2:52SX2CAB



Metal NEMA 4X, selector switch Maintained, short lever position, C Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

Figure similar

design of the product	Actuator round	
Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
design of the actuating element	selector switch	
material of the actuating element	plastic	
type of unlocking device	rotate-to-unlatch mechanism	
number of switching positions	3	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
color of the front ring	black	
Holder		
material of the holder	Metal	
General technical data		
product component		
light source	No	
degree of pollution	1	
protection class IP	IP66	
operating frequency maximum	600 1/h	
Ambient conditions		
ambient temperature		
 during operation 	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SX2CAB

Cax online generator

last mo	dified:	5/31/2021 🗗
	database (product images, 2D dimension drawings, ww.automation.siemens.com/bilddb/cax_de.aspx?mlfb=	3D models, device circuit diagrams, EPLAN macros,) =US2:52SX2CAB⟨=en
Service	&Support (Manuals, Certificates, Characteristics, Fupport.industry.siemens.com/cs/ww/en/ps/US2:52SX20	AQs,)
nup.//su	ipport.automation.siemens.com/www/CAXorder/derauit.	aspx riang-enamino-052.525A2CAD