REV.	LOCAS.	DESCRIPTION	DATE	DRAWN
01	NEW	BATCH PRODUCTION INITIAL RELEASE.	2017.06.13	何東華



Specifications
Current Rating:3Amp
Insulation Resistance:1000MΩMin.
Dielectric Withstanding Voltage:600VAC
Contact Resistance:20mΩMax.
Operating Temperature:−40°C to +105°C
Materials
Contact Material: Brass
Insulator Material:High Temperature Thermoplastic, UL 94V−0 LCP or the equivalent material
All materials must meet Greenconn requirement for environment protection.





Recommended P.C.Board Layout
(Tolerance:±0.05)



Ordering Information

G PHC201 − XX XX A 002 C 1 B X

- XX: No. Of Pins Per Row 02~40
- XX: Standard Plating 02=Gold Flash; Selective Plating 01=Tin, 05=Gold Flash/Tin
- 1: Color 1=Black
- X: Standard Packing C=Tube(04~40Pin); Selective Packing A=Box, E=Cap+Tube(04~40Pin), F=Cap+Tape&Reel

Dim.D	NOTE
5.00	02Pins
6.00	03~08Pins
8.50	09~40Pins

格稜股份有限公司
Greenconn Corporation

REV.	UNIT.	SCALE.	PAGE.
01	mm	4:1	1/1

GENERAL TOLERANCE	
X.°±5.0°	X.±0.30
.X°±3.0°	.X±0.25
.XX°±2.0°	.XX±0.15
.XXX°±1.0°	.XXX±0.10

DESIGNED: 何東華	DATE: 2017.06.13	DWG. NO. GPHC201−CA2CB	TITLE. 2.54 PIN HEADER DUAL ROWS SMT TYPE CONNECTOR
CHECKED:	DATE:		
CO SIGNED:劉北平	DATE: 2017.06.13	PART NO. GPHC201−XXXX A002C1BX	
APPROVED:	DATE:		