

PRODUCT-DETAILS

S202M-C40DC

S202M-C40DC Miniature Circuit Breaker - 2P - C

- 40 A



|  |                                                       |
|--|-------------------------------------------------------|
|  |                                                       |
|  | S202M-C40DC                                           |
|  | 2TAZ112200R0404                                       |
|  | S202M-C40DC Miniature Circuit Breaker - 2P - C - 40 A |
|  | Miniature Circuit Breaker - S200MDC - 2P - C - 40 A   |

|                                                     |                                                          |
|-----------------------------------------------------|----------------------------------------------------------|
|                                                     |                                                          |
|                                                     | IEC/EN 60898-2<br>GB 10963<br>IEC/EN 60947-2<br>GB 14048 |
|                                                     | C                                                        |
| Rated voltage (U <sub>r</sub> )                     | 440 V                                                    |
| Rated voltage                                       | 440 V DC                                                 |
| Rated current (I <sub>n</sub> )                     | 40 A                                                     |
| Rated impulse withstand voltage (U <sub>imp</sub> ) | 4 kV                                                     |
|                                                     | DC                                                       |
| Rated current (I <sub>n</sub> )                     | 40 A                                                     |
|                                                     | (400 V) 10 kA                                            |
| Rated breaking capacity (I <sub>cu</sub> )          | (440 V DC) 10 kA                                         |

|                         |                                             |
|-------------------------|---------------------------------------------|
| 额定电压 (I <sub>nc</sub> ) | (400 V) 10 kA                               |
| 频率 (f)                  | 0...0 Hz                                    |
| 额定频率 (f)                | 0-0 Hz                                      |
| 额定功率                    | 7.64 W                                      |
| 额定电流                    | 3                                           |
| 额定电压                    | 2                                           |
| 额定功率                    | 2                                           |
| 额定电压                    | III                                         |
| 额定电压                    | C                                           |
| 额定电压                    | DC application                              |
| Accessories Available   | Yes                                         |
| 额定电压                    | Flexible 0 ... 25 mm²<br>Rigid 0 ... 35 mm² |

|                                             |                       |
|---------------------------------------------|-----------------------|
| 额定电压                                        |                       |
| 额定电压                                        | -25...55 °C           |
| 额定电压                                        | Operation -25...55 °C |
| 额定电压                                        | IP20                  |
| 额定电压                                        | 3                     |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363       |

|                            |          |
|----------------------------|----------|
| 额定电压                       |          |
| 额定电压 (U <sub>rated</sub> ) | 2        |
| 额定电压                       | 0.035 m  |
| 额定电压                       | 0.088 m  |
| 额定电压                       | 0.044 m  |
| 额定电压                       | 0.250 kg |
| 额定电压 (t <sub>2</sub> )     | 69 mm    |

|         |                |
|---------|----------------|
| 额定电压    |                |
| 额定电压    | 1 piece        |
| 100000  | carton 6 piece |
| 1000 00 | 1.381 kg       |

|           |                       |
|-----------|-----------------------|
| 额定电压      |                       |
| 额定电压 - CE | No declaration needed |

|              |                    |
|--------------|--------------------|
| Installation |                    |
| 额定电压         | No document needed |

|                   |                    |
|-------------------|--------------------|
| Popular Downloads |                    |
| 额定电压              | No document needed |

