

PRODUCT-DETAILS

S202M-B4DC

S202M-B4DC Miniature Circuit Breaker - 2P - B - 4 A



0000	
0000	S202M-B4DC
0010	2TAZ112200R0045
0000	S202M-B4DC Miniature Circuit Breaker - 2P - B - 4 A
0000	Miniature Circuit Breaker - S200MDC - 2P - B - 4 A

0000	
00	IEC/EN 60898-2 GB 10963 IEC/EN 60947-2 GB 14048
0000	B
0000 (U _r)	440 V
00000	440 V DC
00000 (U _i)	440 V
000000 (U _{imp})	4 kV
00000	DC
0000 (I _n)	4 A
00000	(400 V) 10 kA
0000000 (I _{cu})	(440 V DC) 10 kA

U _{nom} (I _{nc})	(400 V) 10 kA
f	0...0 Hz
f	0-0 Hz
U _{max}	3
U _{min}	2
U _{avg}	2
U _{peak}	III
U _{ripple}	B
U _{DC}	DC application
Accessories Available	Yes
U _{flex}	Flexible 0 ... 25 mm ²
U _{rigid}	Rigid 0 ... 35 mm ²

U _{temp}	-25...55 °C
U _{op}	Operation -25...55 °C
U _{IP}	IP20
U _{poll}	3
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

U _{dim}	2
U _h	0.035 m
U _l	0.088 m
U _h	0.044 m
U _{kg}	0.250 kg
U _{t2}	69 mm

U _{piece}	1 piece
U _{carton}	carton 6 piece
U _{kg}	1.381 kg

U _{CE}	No declaration needed
-----------------	-----------------------

Installation

U _{doc}	No document needed
------------------	--------------------

Popular Downloads

U _{doc}	No document needed
------------------	--------------------

□□	
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE □	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362010
e□	V11.0 : 27141901
□□□□	F

□□

□□□□ → □□□□ → Miniature Circuit Breakers MCBs → □□□□

