THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	10/22/2021	S.XU

FIBER TYPE	SINGLEMODE, LOW WATER PEAK, MIL TAC
CORE DIAMETER	9 µm
CLADDING DIAMETER	125 µm
PRIMARY COATING DIA. (UV CURED ACRYLATE)	245 µm
SECONDARY BUFFER DIA. (HARD ELASTOMERIC)	900 µm
PROOF TEST LEVEL	100 kpsi

WAVELENGTH:	1310 nm	1550 nm
MAXIMUM ATTENUATION	3.5 dB/km	1.5 dB/km
NOMINAL ZERO DISPERSION SLOPE	0.092 ps/(nm^2-km)	

CABLE WEIGHT	16 kg/km (11 lbs/1000 ft)
CABLE DIAMETER	2.9 x 5.8 mm (0.11 x 0.23 in)

SHORT-TERM:	
MAX TENSILE LOAD	500 N (110 lbs)
MIN BEND RADIUS	5.0 cm (2.0 in)

LONG-TERM:	
MAX TENSILE LOAD	250 N (55 lbs)
MIN BEND RADIUS	3.0 cm (1.2 in)

IMPACT RESISTANCE	1000 IMPACTS
CRUSH RESISTANCE	750 N/cm

OPERATING TEMPERATURE	-20°C TO +70°C
STORAGE TEMPERATURE	-40°C TO +70°C
INSTALLATION TEMPERATURE	0°C TO +60°C (actual temp. of cable)
FLAME RETARDANCY	OFNR-LS
ZERO HALOGEN	IEC 60754-2
SMOKE GENERATION	IEC 61034-2





ALL DIMENSIONS IN mm, DRAWING NOT TO SCALE

NOTES:

1. CABLE SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, ~~DIMENSIONS ARE IN INCHES [mm]~~
OVERALL CABLE LENGTH TOLERANCE:
≤12 [305] = +1 [25] / -0
>12 [305] ≤60 [1524] = +2 [51] / -0
>60 [1524] ≤120 [3048] = +4 [102] / -0
>120 [3048] ≤300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0
ALL OTHER DIMENSIONAL TOLERANCES:
.X = ± .2 [5] | .XX = ± .02 [.5] | .XXX = ± .005 [.13]
FRACTIONS ± 1/32 | ANGLES ± 1°
THIRD-ANGLE PROJECTION

APPROVALS	DATE
DRAWN BY BZHANG	09/14/2021
CHECKED BY S.XU	09/14/2021
APPROVED BY S.XU	09/14/2021

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY

COLOR VARIATIONS MAY OCCUR

L-com an INFINITE brand
50 High Street, West Mill,
North Andover, MA 01845 USA.
Phone: 1.800.341.5266
1.978.682.6936

CATEGORY
FIBER OPTIC

PRODUCT DESCRIPTION
1M Interval Economy SMF 9/125 Duplex Fiber Cable 3.0mm OD Yellow LSZH

SIZE	CAGE CODE	ITEM NO.	REV.
A	43321	FOB30SNGZYZV-M	A

SCALE: NONE | CAD FILE: fob30sngzyzv-m.SLDDRW | SHEET 1 OF 1

T-Rev.D