



**Product: 8442** ☑

Electronic, 2 C #22 Str TC, PVC Ins, PVC Jkt, CMG

Request Sample

# **Product Description**

Electronic, 2 Conductor 22AWG (7x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

# **Technical Specifications**

## **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring

## **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding		
Conductor(s)	2	22 AWG	7x30	TC - Tinned Copper	

#### Insulation

Element	Material	Nom. Thickness Nom. Insulation Diameter		Color Code
Conductor(s)	PVC - Polyvinyl Chloride	0.016 in (0.41 mm)	0.060 in (1.5 mm)	Black, Red

## Outer Jacket

	Material	Nom. Thickness	Nom. Diameter
F	PVC - Polyvinyl Chloride	0.025 in (0.64 mm)	0.170 in (4.32 mm)
(	Overall Cable Diameter (I	Nominal): 0.170 in (	4.32 mm)

## **Electrical Characteristics**

# Electricals

ľ	Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
ľ	Conductor(s)	17.8 Ohm/1000ft	30 pF/ft (98 pF/m)	2.9 Amps per Conductor at 25°C

## Voltage

UL Voltage Rating 300 V

## **Mechanical Characteristics**

## Temperature

<b>UL Temperature</b>	Operating		
80°C	-20°C to +80°C		

### **Bend Radius**

ı	Stationary Min.	Installation Min.
ľ	1.7 in (43 mm)	1.7 in (43 mm)
i	Max. Pull Tension	n:
L	IVIAA. FUII TENSIOI	
	Bulk Cable Weigl	ht:

## **Standards and Compliance**

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca; CPR UKCA Class: Eca
NEC / UL Compliance:	Article 800, CMG
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
Plenum Number:	88442, 82442

#### **History**

Update and Revision:	Revision Number: 0.513 Revision Date: 01-20-2023	
----------------------	--	--

#### **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
8442 060100	Chrome	Reel	100 ft	612825207238	
8442 060500	Chrome	Reel	500 ft	612825207269	
8442 060U500	Chrome	UnReel	500 ft	612825207221	
8442 0601000	Chrome	Reel	1,000 ft	612825207245	С
8442 060U1000	Chrome	UnReel	1,000 ft	612825207214	
8442 0605000	Chrome	Reel	5,000 ft	612825207276	CZ
8442 06010000	Chrome	Reel	10,000 ft	612825207252	CY

#### © 2023 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.