



**Product:** [19122](#)

Portable Cordage, 2 C #18 Str BC, PVC Ins, UL Type SPT-1

[Request Sample](#)

**Product Description**

Portable Cordage, 2 Conductor 18AWG (42x34) Bare Copper, PVC Insulation, UL Type SPT-1

**Technical Specifications**

**Product Overview**

Suitable Applications:	Portable cordage and cordage
------------------------	------------------------------

**Construction Details**

**Conductor**

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	2	18	42x34	BC - Bare Copper

**Insulation**

Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
PVC - Polyvinyl Chloride	0.032 in (0.81 mm)	0.110 in (2.79 mm)	Brown, White, Black, Silver, Gray

**Outer Jacket**

Nom. Diameter
0.11 x 0.207 in

**Electrical Characteristics**

**Electricals**

Nom. Conductor DCR	Max. Current
6.97 Ohm/1000ft	10 Amps per Conductor at 25°C (7 Amps over 50 ft)
	7 Amps per Conductor at 25°C (over 50 ft)

**Voltage**

UL Voltage Rating
300 V

**Mechanical Characteristics**

**Temperature**

UL Temperature
60°C

**Bend Radius**

Stationary Min.	Installation Min.
1.1 in (28 mm)	1.1 in (28 mm)
Max. Pull Tension:	42.6 lbs (19.3 kg)
Bulk Cable Weight:	20 lbs/1000ft

**Standards and Compliance**

NEC / UL Compliance:	Article 400, SPT-1
AWM Compliance:	SPT-1
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.492 Revision Date: 01-20-2023
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
19122 010250	Black	Reel	250 ft	612825126614	F
19122 0101000	Black	Reel	1,000 ft	612825126607	C G
19122 001250	Brown	Reel	250 ft	612825126584	F
19122 0011000	Brown	Reel	1,000 ft	612825126577	G
19122 328250	Gray, Silver	Reel	250 ft	612825126621	F
19122 009250	White	Reel	250 ft	612825126591	F

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.