


Specification Sheet

Part Number: 170-03147




Unique construction retains shape and rigidity throughout operating temperature range.

Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

Self wrapping design eliminates the need for fasteners.

Provides a greater flexibility than spiralwrap or convoluted tubing.



Braided Sleeving, Split Wrap, Flame Retardant, 2" Dia, PET, Black, 50 ft/bulk reel

Article Number 170-03147

Type BSSWFR200B

Color Black (BK)

Quantity Per box

Product Description

Used when flame retardancy is a primary requirement, this protection option incorporates a lateral split which allows the tube to open up to accommodate a variety of bundling requirements. The semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners. Split wrap flame retardant braided sleeving is self-extinguishing and complies with UL VW-1 standards where cables exit a wall and need to be managed for an uncluttered, clean appearance.

Short Description	Braided Sleeving, Split Wrap, Flame Retardant, 2" Dia, PET, Black, 50 ft/bulk reel			
Global Part Name	BSSWFR200B-PET-BK			
Length L (Imperial)	50.0			
Length L (Metric)	15.2			
Bundle Diameter Min (Imperial)	0.1			
Bundle Diameter Min (Metric)	2.54			
Bundle Diameter Max (Imperial)	2.0			
Bundle Diameter Max (Metric)	50.8			
Diameter D (Imperial)	2.0			
Diameter D (Metric)	50.8			
Nominal Diameter (Imperial)	2			
Nominal Diameter (Metric)	50.8			
Wall Thickness WT (Imperial)	0.038			
Wall Thickness WT (Metric)	0.97			

Material	Polyester (PET)
Material Shortcut	PET
Flammability	FAR 25 UL 224 VW-1
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	ASTM E 162 ASTM 1354 ASTM E 662
UL Recognized (US)	Yes
Package Quantity (Imperial)	50

About HellermannTyton

Package Quantity (Metric)

Customs Number

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global

15.24

5808100000

customers. HellermannTyton operates (www.hellermann.tyton.com).	in 39 countries	s, with North American headq	uarters in Milw	aukee, Wisconsin.
© 2023 HellermannTyton. All Rights	Reserved. Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions
		·		