



**Product:** <u>89503</u> ☑

RS232, #24-3pr, FEP, O/A Foil, FEP Jkt, CMP

# **Product Description**

Computer EIA RS-232 Cable, 24 AWG stranded (7x32) tinned copper conductors, FEP insulation, 3 twisted pair, overall Beldfoil® shield (100% coverage), 24 AWG stranded tinned copper drain wire, FEP jacket, plenum rated

# **Technical Specifications**

## **Product Overview**

Suitable Applications: extreme high/low temperature environments; rs-232 applications; computer communications; low voltage analog signals (4-20ma, 0-10v,	); low voltage digital control (24v,);
--	--

#### **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	3	24	7x32	TC - Tinned Copper

#### Insulation

Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
FEP - Fluorinated Ethylene Propylene	0.006 in (0.15 mm)	0.036 in (0.91 mm)	Black & Red, Black & White, Black & Green

## Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

### Outer Jacket

Material	Nom. Thickness	Nom. Diameter
FEP - Fluorinated Ethylene Propylene	0.015 in (0.38 mm)	0.177 in (4.50 mm)

## **Electrical Characteristics**

### Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
28.8 Ohm/1000ft	10.46 Ohm/1000ft (34.32 Ohm/km)	21 pF/ft (69 pF/m)	40 pF/ft (130 pF/m)	1.5 Amps per Conductor at 25°C

## Voltage

UL Voltage Rating 300 V

# **Mechanical Characteristics**

## Temperature

UL Temperature	Operating
150°C	-70°C To +150°C

## Bend Radius

Stationary Min.	Installation Min.
1.77 in (45.0 mm)	1.77 in (45.0 mm)

Max. Pull Tension:	39 lbs (18 kg)
Bulk Cable Weight:	21 lbs/1000ft

## **Standards and Compliance**

Environmental Suitability:	Outdoor, Sunlight Resistance, Oil Resistance
Flammability / Reaction to Fire:	NFPA 262 (UL910), FT6, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	9503

## History

Update and Revision:	Revision Number: 0.431 Revision Date: 01-20-2023

## **Part Numbers**

#### Variants

Item #	Color	UPC	Footnote
89503 002100	Red	612825220992	С
89503 0021000	Red	612825221005	С
89503 002500	Red	612825221012	С

#### © 2023 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.