




**Product:** <u>5100UP</u> ☑

Audio Cable, 2 Conductor 14 AWG, BC, Unshielded, CL3

# **Product Description**

Audio Cable, Rated-CL3, 2-14 AWG highly flexible stranded bare copper conductors with PVC insulation, PVC jacket with ripcord

# **Technical Specifications**



Operating
-20°C to +75°C

## **Bend Radius**

Stationary Min.	Installation Min.
2.7 in (69 mm)	2.7 in (69 mm)
Max. Pull Tension	ո։
Bulk Cable Weight:	

## **Standards and Compliance**

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor			
Flammability / Reaction to Fire:	UL 1685 UL loading , IEC 60332-1-2			
CPR Compliance:	CPR Euroclass: Eca			
NEC / UL Compliance:	Article 725, CL3			
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
UK Regulation Compliance:	UKCA Mark			
APAC Compliance:	China RoHS II (GB/T 26572-2011)			

# **History**

Update and Revision:	Revision Number: 0.489 Revision Date: 04-13-2023	
----------------------	--	--

## **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
5100UP 010500	Black	Reel	500 ft	612825156529	
5100UP 010U500	Black	UnReel	500 ft	612825433484	
5100UP 0101000	Black	Reel	1,000 ft	612825156550	С
5100UP 010U1000	Black	UnReel	1,000 ft	612825156536	
5100UP 010Z1000	Black	ReelTuff Box	1,000 ft	612825156611	
5100UP 008U500	Gray	UnReel	500 ft	612825156505	
5100UP 0081000	Gray	Reel	1,000 ft	612825156451	С
5100UP 008U1000	Gray	UnReel	1,000 ft	612825156468	
5100UP 005500	Green, Dark	Reel	500 ft	612825156413	
5100UP 005U500	Green, Dark	UnReel	500 ft	612825156475	
5100UP 0051000	Green, Dark	Reel	1,000 ft	612825156444	
5100UP 005U1000	Green, Dark	UnReel	1,000 ft	612825156420	
5100UP 009500	White	Reel	500 ft	612825156482	
5100UP 009U500	White	UnReel	500 ft	612825156543	
5100UP 0091000	White	Reel	1,000 ft	612825156512	
5100UP 009U1000	White	UnReel	1,000 ft	612825156499	

# © 2023 Belden, Inc

## All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.