



- SPECIFICATIONS**
1. Current Rating: 3A AC, DC
 2. Voltage Rating: 250V AC, DC
 3. Temperatur Range: -25°C~ +85°C
 4. Contact Resistance: 20mΩ Max
 5. Insulation Resistance: 1000mΩ Min
 6. Withstanding Voltang: 800V AC/minute
 7. Material: Wafer Nylon66 UL94-VO
Pin Brass Tin-plated

Circuit	Part No.	Dimensions mm	
		A	B
2	XD-PHD-2x2AW-X-XX	2.00	6.00
3	XD-PHD-2x3AW-X-XX	4.00	8.00
4	XD-PHD-2x4AW-X-XX	6.00	10.00
5	XD-PHD-2x5AW-X-XX	8.00	12.00
6	XD-PHD-2x6AW-X-XX	10.00	14.00
7	XD-PHD-2x7AW-X-XX	12.00	16.00
8	XD-PHD-2x8AW-X-XX	14.00	18.00
9	XD-PHD-2x9AW-X-XX	16.00	20.00
10	XD-PHD-2x10AW-X-XX	18.00	22.00
11	XD-PHD-2x11AW-X-XX	20.00	24.00
12	XD-PHD-2x12AW-X-XX	22.00	26.00
13	XD-PHD-2x13AW-X-XX	24.00	28.00
14	XD-PHD-2x14AW-X-XX	26.00	30.00
15	XD-PHD-2x15AW-X-XX	28.00	32.00
16	XD-PHD-2x16AW-X-XX	30.00	34.00
17	XD-PHD-2x17AW-X-XX	32.00	36.00
18	XD-PHD-2x18AW-X-XX	34.00	38.00
19	XD-PHD-2x19AW-X-XX	36.00	40.00
20	XD-PHD-2x20AW-X-XX	38.00	42.00

Ordering Information

XD - PHD - N*** - * - **

Pin	Type 针类型	Colour 颜色	Contact Plating 镀层
	AW: 镀针	CS: 镀锡	CS1/2: Gold
	AL: 镀铝	CS: 镀锡	CS2/2: Gold
		CS3/3: Gold	CS3/3: Gold
		CS4/4: Gold	CS4/4: Gold
		CS5/5: Gold	CS5/5: Gold
		V: 镀银	

GENERAL TOLERANCE		制图 DRAWING	02
DIM TOL		审核 CHECK	
X.X ±0.30		批准 APPROVAL	
X.XX ±0.20		比例 SCALE	
X.XXX ±0.10		投影 Projection	
Angle ±3.0°		材料 MATERIAL	

XD 深圳讯答科技有限公司
ShenzhenXunDaTechnology Co.,Ltd

产品名称 TITLE	PHD (2.00) 双排 弯针	版本 REV.	A
产品料号 PART NO.	XD-PHD-2xNAW-X-XX	单位 UNITS	mm
材料 MATERIAL		页次 SHEET	1/1

序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE
1	初版发行	