

Product: 6548PA ☑



Security & Sound, 12 Pair 22 AWG, BC, CMP

# **Product Description**

Security, Pro Audio & Intercom Cable, 12 Pair 22 AWG stranded (7x30) bare copper pairs with FEP insulation, Individually Beldfoil® shielded and PVDF jacket with ripcord, Plenum rated.

# **Technical Specifications**

### **Product Overview**

Suitable Applications:	Security, Audio, Intercom

## **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	12	22 AWG	7x30	BC - Bare Copper

#### Insulation

Eler	nent Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair	s) FEP - Fluorinated Ethylene Propylene	0.010 in (0.25 mm)	0.049 in (1.2 mm)	Black & Red, Black & White, Black & Green, Black & Blue, Black & Yellow, Black & Brown, Black & Orange, Red & White, Red & Green, Red & Blue, Red & Yellow, Red & Brown

### Inner Shield

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

# Outer Shield



### **Outer Jacket**

Material	Nom. Thickness	Nom. Diameter	Ripcord
PVDF - Polyvinylidene Fluoride	0.017 in (0.43 mm)	0.408 in	Yes
Overall Cable Diameter (Nomina	al): 0.4	408 in	

## **Electrical Characteristics**

### Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Nom. Velocity of Prop.	Max. Current
17.6 Ohm/1000ft	15.3 Ohm/1000ft (50.2 Ohm/km)	27.5 pF/ft (90.2 pF/m)	49.5 pF/ft (162 pF/m)	50 Ohm	69%	3.6 Amps per Conductor at 30°C

### Voltage



## **Mechanical Characteristics**

Γem	nor	atu	ır۵
	201	all	

UL Temperature	Operating
150°C	-15°C to +150°C

#### **Bend Radius**

Stationary Min.	Installation Min.
4.08 in (104 mm)	4.08 in

Max. Pull Tension:	223.9 lbs (101.6 kg)
Bulk Cable Weight:	116 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262 (UL 910), FT6
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

#### **Product Notes**

Notes:	Ripcord under jacket

# History

Update and Revision:	Revision Number: 0.307 Revision Date: 12-20-2022

#### **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
6548PA 0081000	Gray	Reel	1,000 ft	612825433866	С
6548PA 0081500	Gray	Reel	1,500 ft	612825178507	

#### © 2023 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.