



Product: [3072Z](#)

Blue Hose®, 1 Pr #18 Str TC, PP Ins, OS+TC Brd, LSZH-TS Jkt, 600V TC-ER-ST1

Product Description

Blue Hose® for Data Highway Plus, 1 Pair 18AWG (7x26) Tinned Copper, Polypropylene Insulation, Overall Beldfoil®+Tinned Copper Braid(55%) Shield, LSZH Thermoset Outer Jacket, 600V TC-ER-ST1

Technical Specifications

Product Overview

Suitable Applications:	shipboard, harsh environment, IIoT, factory or process automation, video, audio, data communication, etc.
------------------------	---

Construction Details

Conductor

Element	Number of Element	Size	Stranding	Material
Pair(s)	1	18 AWG	7x26	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Color Code	Notes
Pair(s)	PP - Polypropylene	0.025 in (0.64 mm)	Blue & White	Flame Retardant

Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	20 AWG (7x28) TC
Braid	Tinned Copper (TC)	55%	

Outer Jacket

Material	Nom. Thickness	Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant, Thermoset)	0.100 in (2.54 mm)	0.480 in (12.2 mm)

Overall Cable Diameter (Nominal):	0.480 in (12.2 mm)
-----------------------------------	--------------------

Electrical Characteristics

Electricals

Element	Nom. Characteristic Impedence	Nom. Velocity of Prop.
Pair(s)	78 Ohm	65%

High Frequency (Nominal/Typical)

Element
Pair(s)

Voltage

UL Voltage Rating	Voltage Rating
600 V (TC-ER-ST1), 300 V (CMG-ST1, PLTC-ST1)	150 V (ITC-ST1)

Mechanical Characteristics

Temperature

UL Temperature

75°C Dry

Standards and Compliance

Environmental Suitability:	Burial
CPR Compliance:	CPR Euroclass: Fca
NEC / UL Compliance:	Article 336, Article 725, Article 727, Article 800, CMG-ST1, TC-ER-ST1, PLTC-ST1, ITC-ST1
CEC / C(UL) Compliance:	CMG-ST1

History

Update and Revision:	Revision Number: 0.162 Revision Date: 05-05-2023
----------------------	--

Part Numbers

Variants

Item #	Color	UPC
3072Z 0105000	Black	612825140122

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.