

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Hybrid cable, Ethernet hybrid CAT5 (100 Mbps), 8-position halogen-free, shielded (Advanced Shielding Technology), Plug angled M12, coding: Y / IP65/IP67, on Socket angled M12, coding: Y / IP65/IP67, cable length: 2 m, Power with Ethernet (PWE)

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1057783       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF04          |
| Product key                          | BF1CML        |
| GTIN                                 | 4055626702223 |
| Weight per piece (including packing) | 273.3 g       |
| Weight per piece (excluding packing) | 22.22 g       |
| Customs tariff number                | 85444290      |
| Country of origin                    | PL            |

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

## Technical data

### Product properties

|                      |                         |
|----------------------|-------------------------|
| Product type         | Data cable preassembled |
| Sensor type          | Ethernet hybrid         |
| Number of positions  | 8                       |
| Application          | Standard                |
| No. of cable outlets | 1                       |
| Shielded             | yes                     |
| Coding               | Y                       |

### Interfaces

|                      |                                            |
|----------------------|--------------------------------------------|
| Bus system           | Ethernet                                   |
| Signal type/category | Ethernet hybrid CAT5 (IEC 11801), 100 Mbps |

### Signaling

|                        |    |
|------------------------|----|
| Status display         | No |
| Status display present | No |

### Electrical properties

|                       |                          |
|-----------------------|--------------------------|
| Nominal voltage $U_N$ | 48 V AC (Power and data) |
|                       | 50 V DC (Power and data) |
| Nominal current $I_N$ | 6 A (Power)              |
|                       | 0.5 A (Data)             |
| Transmission medium   | Copper                   |

### Material specifications

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

### Connector

#### Connection 1

|                             |                                                    |
|-----------------------------|----------------------------------------------------|
| Type                        | Plug angled M12 / IP65/IP67                        |
| Number of positions         | 8 (4+4)                                            |
| Coding type                 | Y (Hybrid)                                         |
| Shielded                    | yes                                                |
| Handle color                | black                                              |
| Material                    | CuZn (Contact)                                     |
|                             | Ni/Au (Contact surface)                            |
|                             | PA (Contact carrier, data)                         |
|                             | PA (Contact carrier, power)                        |
|                             | TPU, hardly inflammable, self-extinguishing (Grip) |
| Insertion/withdrawal cycles | Zinc die-cast, nickel-plated (Screw connection)    |
|                             | ≥ 100                                              |

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

|                                 |                  |
|---------------------------------|------------------|
| Contact resistance              | ≤ 5 mΩ           |
| Insulation resistance           | ≥ 100 MΩ         |
| Tightening torque               | 0.4 Nm           |
| Degree of protection            | IP65/IP67        |
| Ambient temperature (operation) | -25 °C ... 90 °C |
| Number of positions             | 8                |
| Insertion/withdrawal cycles     | 100              |

## Connection 2

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                            | Socket angled M12 / IP65/IP67                                                                                                                                                                                   |
| Number of positions             | 8 (4+4)                                                                                                                                                                                                         |
| Coding type                     | Y (Hybrid)                                                                                                                                                                                                      |
| Shielded                        | yes                                                                                                                                                                                                             |
| Handle color                    | black                                                                                                                                                                                                           |
| Material                        | CuZn (Contact)<br>Ni/Au (Contact surface)<br>PA (Contact carrier, data)<br>PA (Contact carrier, power)<br>TPU, hardly inflammable, self-extinguishing (Grip)<br>Zinc die-cast, nickel-plated (Screw connection) |
| Insertion/withdrawal cycles     | ≥ 100                                                                                                                                                                                                           |
| Tightening torque               | 0.4 Nm                                                                                                                                                                                                          |
| Ambient temperature (operation) | -25 °C ... 90 °C                                                                                                                                                                                                |
| Number of positions             | 8                                                                                                                                                                                                               |
| Degree of protection            | IP65/IP67                                                                                                                                                                                                       |

## Cable/line

|              |     |
|--------------|-----|
| Cable length | 2 m |
|--------------|-----|

## Ethernet hybrid [94H]

|                                 |                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing             |  |
| UL AWM Style                    | 20233 (80°C/300 V)                                                                   |
| Number of positions             | 8                                                                                    |
| Shielded                        | yes                                                                                  |
| Cable type                      | Ethernet hybrid [94H]                                                                |
| Conductor structure             | 1x4x AWG 26+1x4x AWG 18                                                              |
| Conductor structure signal line | 19x 0.10 mm                                                                          |
| AWG signal line                 | 26                                                                                   |

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

|                                               |                                                                     |
|-----------------------------------------------|---------------------------------------------------------------------|
| Conductor cross section                       | 4x 0.15 mm <sup>2</sup> (Data)                                      |
|                                               | 4x 0.85 mm <sup>2</sup> (Power)                                     |
| Wire diameter incl. insulation                | 1.05 mm (Data)                                                      |
|                                               | 1.4 mm (Power)                                                      |
| External cable diameter                       | 8.8 mm ±0.2 mm                                                      |
| Outer sheath, material                        | PUR                                                                 |
| External sheath, color                        | black RAL 9005                                                      |
| Conductor material                            | Bare Cu litz wires                                                  |
| Material wire insulation                      | PP (Data)                                                           |
|                                               | PP (Power)                                                          |
| Single wire, color                            | white/orange, orange, white/green, green, white, blue, brown, black |
| Overall twist                                 | 1 star quad and 4 wires with 2 fillers                              |
| Optical shield covering                       | 85 %                                                                |
| Insulation resistance                         | ≥ 5 GΩ*km                                                           |
| Loop resistance                               | ≤ 280.00 Ω/km (Data)                                                |
|                                               | ≤ 45.00 Ω/km (Power)                                                |
| Wave impedance                                | 100 Ω ±15 Ω (4 MHz ... 100 MHz)                                     |
| Working capacitance                           | nom. 50 nF (per kilometer)                                          |
| Differential impedance                        | 100 Ω ±5 % (at 100 MHz)                                             |
| Nominal voltage, cable                        | ≤ 125 V (Peak value, not for high-power applications)               |
| Test voltage Core/Core                        | 2000 V (50 Hz, 1 min.)                                              |
| Test voltage Core/Shield                      | 2000 V (50 Hz, 1 min.)                                              |
| Minimum bending radius, fixed installation    | 4 x D                                                               |
| Minimum bending radius, flexible installation | 8 x D                                                               |
| Max. bending cycles                           | 2000000                                                             |
| Tensile strength                              | 85 N (in accordance with DIN EN 50565-1 for flexible installation)  |
|                                               | 295 N (in accordance with DIN EN 50565-1 for fixed installation)    |
| Near end crosstalk attenuation (NEXT)         | 56.3 dB (at 4 MHz)                                                  |
|                                               | 50.3 dB (at 10 MHz)                                                 |
|                                               | 47.2 dB (at 16 MHz)                                                 |
|                                               | 45.8 dB (at 20 MHz)                                                 |
|                                               | 42.9 dB (at 31.25 MHz)                                              |
|                                               | 38.4 dB (at 62.5 MHz)                                               |
|                                               | 35.3 dB (at 100 MHz)                                                |
| Shield attenuation                            | 6.2 dB (at 4 MHz)                                                   |
|                                               | 9.8 dB (at 10 MHz)                                                  |
|                                               | 12.4 dB (at 16 MHz)                                                 |
|                                               | 13.9 dB (at 20 MHz)                                                 |
|                                               | 17.6 dB (at 31.25 MHz)                                              |
|                                               | 25.4 dB (at 62.5 MHz)                                               |
|                                               | 32.8 dB (at 100 MHz)                                                |
|                                               | ≥ 80 dB (30 MHz ... 100 MHz)                                        |
| Halogen-free                                  | according to IEC 60754-1                                            |

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

|                                 |                                                                     |
|---------------------------------|---------------------------------------------------------------------|
|                                 | in accordance with DIN VDE 0472 part 815                            |
| Flame resistance                | in accordance with UL 1581, Section 1060                            |
|                                 | in acc. with UL 1581, section 1061                                  |
|                                 | in accordance with UL 2556, Section 9.3                             |
|                                 |                                                                     |
| Resistance to oil               | in accordance with IEC 60811-404                                    |
|                                 | According to DIN EN 50363-10-2                                      |
| Other resistance                | Low adhesion                                                        |
|                                 | Hydrolysis resistance DIN EN 50396                                  |
| Special properties              | Free of substances which would hinder coating with paint or varnish |
|                                 | Silicone-free                                                       |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation)                        |
|                                 | -30 °C ... 70 °C (Cable, flexible installation)                     |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-113 |

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable


1057783

<https://www.phoenixcontact.com/us/products/1057783>




## Drawings


Circuit diagram



Dimensional drawing




M12 x 1 male plug, angled, shielded



M12 hybrid plug pin assignment, 8-pos., Y-coded, socket side view


Dimensional drawing



M12 x 1 socket, angled, shielded

1057783

<https://www.phoenixcontact.com/us/products/1057783>



M12 hybrid plug pin assignment, 8-pos., Y-coded, pin side view



# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1057783>



### UL Listed

Approval ID: E221474

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| Power | 48 V                  | 6 A                   | -                 | - 18                        |
| Data  | 50 V                  | 0.5 A                 | -                 | - 26                        |



### cUL Listed

Approval ID: E221474

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| Power | 48 V                  | 6 A                   | - 18              | -                           |
| Data  | 50 V                  | 0.5 A                 | - 26              | -                           |

### cULus Listed

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060307 |
| ECLASS-12.0 | 27060307 |
| ECLASS-13.0 | 27060307 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

## Accessories

### TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

---

### TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

# NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable



1057783

<https://www.phoenixcontact.com/us/products/1057783>

## TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

---

## SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

## NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable

1057783

<https://www.phoenixcontact.com/us/products/1057783>



## PROT-M12 FS-PA-CHAIN - Sealing cap

1430873

<https://www.phoenixcontact.com/us/products/1430873>

M12 sealing cap made of plastic with fixing band, for sensor cables, for free M12 plugs



---

## SAC-M12-EXCLIP-M - Locking clip

1558988

<https://www.phoenixcontact.com/us/products/1558988>

Locking clip for the pin side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



## NBC-M12MRY/2,0-94H/M12FRY - Hybrid cable

1057783

<https://www.phoenixcontact.com/us/products/1057783>



## PROT-M12 MS-PA-CHAIN - Screw plug

1430899

<https://www.phoenixcontact.com/us/products/1430899>

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



## SAC-M12-EXCLIP-F - Locking clip

1558991

<https://www.phoenixcontact.com/us/products/1558991>

Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)