



**Product:** <u>3113A</u> ☑

Type TX Thermocouple, 1 Pr #20 Sol, PVC Ins Blu, Red, OS, Blue PVC Jkt, 300V PLTC ITC CMG

Request Sample
Requ

# **Product Description**

Type TX Thermocouple, 1 Pair 20AWG (Solid) OFHC+Constantan, PVC Insulation Blu, Red Color Code, Overall Beldfoil® Shield, Blue PVC Outer Jacket, PLTC ITC CMG AWM 2464 SUN RES DIR BUR

# **Technical Specifications**

# **Product Overview**

Suitable Applications: Industrial Control, Raceways Cable trays and ducts, Digital Control, Instruments (4-20ma, 0-10v, ...),low voltage digital control (24v, ...),Thermocouple, distributed control system (DCS),programmable logic controller (PLC)

### **Construction Details**

### Conductor

Element	Number of Element	Size	Stranding	Material
Pair(s)	1	20 AWG	Solid	Copper & Constantan

### Insulation

Element	Material	Nom. Thickness	Color Code
Pair(s)	PVC - Polyvinyl Chloride	0.021 in (0.53 mm)	Blue & Red

# Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	22 AWG (7x30) TC

### Outer Jacket

Material	Nom. Thickness Nom.	bm. Diameter Ripcord
PVC - Polyvinyl Chloride	0.037 in (0.94 mm) 0.226 i	26 in (5.74 mm) Yes
Overall Cable Diameter (Nominal):	0.226 in (5.74 mm)	

# **Electrical Characteristics**

# Electricals



# Voltage

UL Voltage Rating
300 V (PLTC, CMG, UL AWM 2464), 150 V (ITC)

# **Mechanical Characteristics**

# Temperature

<b>UL Temperature</b>	Operating
105°C	-30°C to +105°C

### Bend Radius

Stationary Min. Installation Min.

2.3 in (58 mm) 2.3 in (58 m	m)
Max. Pull Tension:	40 lbs (18 kg)
Bulk Cable Weight:	25 lbs/1000ft

### Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance	
Flammability / Reaction to Fire: UL1685 (FT4 Loading), FT4, 1202		
NEC / UL Compliance:	Article 725, Article 727, Article 800, CMG, ITC, PLTC	
AWM Compliance:	AWM 2464	
CEC / C(UL) Compliance:	: CMG	
European Directive Compliance:		
APAC Compliance: China RoHS II (GB/T 26572-2011)		
Other Standard Compliance(s):	ISA MC 96.1-1982 Type TX	

#### **Product Notes**

Notes:	Constantan is a Hoskins Manufacturing Company trademark.

# History

Update and Revision:	Revision Number: 0.383 Revision Date: 04-14-2023

### **Part Numbers**

#### Variants

	Item #	Color	Putup Type	Length	UPC
31	113A 0135000	Black	Reel	5,000 ft	612825141921

# © 2023 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.