

APPLICABLE STANDARD		SPECIFICATIONS					
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +105°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60°C (NOTE3)			
	OPERATING HUMIDITY RANGE	20% TO 80% (NOTE2)	STORAGE HUMIDITY RANGE	40% TO 70% (NOTE3)			
	APPLICABLE CONNECTOR	DF62B-*S-2.2C(##) DF62C-*S-2.2C(##)	VOLTAGE	AC/DC 250V			
	APPLICABLE CABLE	AWG 22	CURRENT	AWG 22 : 3A			
	INSULATION DIAMETER	ϕ 1.2 ~ ϕ 1.45 mm					
CONSTRUCTION							
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X X		
MARKING	CONFIRMED VISUALLY.				X X		
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE	20mV MAX, 1mA (DC or 1000Hz).		30 mΩ MAX.		X —		
MECHANICAL CHARACTERISTICS							
CONTACT INSERTION AND EXTRACTION FORCES	T=0.44±0.002 mm BY STEEL GAUGE.		INSERTION FORCE 2.8 N MAX. EXTRACTION FORCE 0.15 N MIN.	X —			
MECHANICAL OPERATION	30 TIMES INSERTION AND EXTRACTION.		① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLES FOR 3 DIRECTION.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES EACH FOR 3 BOTH AXIAL DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2°C, 90 TO 95 %, 96 h. (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)		① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55°C → +85°C TIME 30min → 30min UNDER 5 CYCLES. (THE TRANSFERRING TIME OF THE TANK IS 2~3 min) (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)		① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT. NOTE2: NO CONDENSING NOTE3: APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFOR PCB ON BOARD, AFTER PCB ON BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STRAGE DURING TRANSPORTATION.							
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE		
0							
REMARKS				APPROVED	KI. AKIYAMA		
				CHECKED	KI. AKIYAMA		
				DESIGNED	TS. KUMAZAWA		
				DRAWN	TS. KUMAZAWA		
Unless otherwise specified, refer to IEC 60512.			DRAWING NO.		ELC4-352024-00		
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	DF62-22SC			
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL544-0572-0-00	△ 1/1		