



N-Channel MOSFET

General description

SOT-23 Plastic-Encapsulate Mosfet

SOT-23**FEATURES**

- Lead free product is acquired
- Surface mount package
- DC/DC Converter

**Equivalent Circuit****MECHANICAL DATA**

- SOT-23 Small Outline Plastic Package
- Epoxy UL: 94V-0
- Mounting Position: Any

Marking:S4**Maximum Ratings & Thermal Characteristics** $T_A = 25^\circ\text{C}$ unless otherwise noted

Parameters	Symbol	Value	Unit
Drain-Source Voltage	VDS	30	V
Gate-Source Voltage	VGS	± 20	V
Continuous Drain Current	ID	3.3	A
Pulsed Drain Current	IDM	15	
Continuous Source-Drain Diode Current	IS	0.9	
Power Dissipation	PD	350	mW
Junction Temperature	Tj	150	$^\circ\text{C}$
Storage Temperature	Tstg	-50-+150	$^\circ\text{C}$
Thermal Resistance From Junction to Ambient	R θ JA	357	$^\circ\text{C/W}$

DN2304

Electrical Characteristics

T_A = 25°C unless otherwise noted


Parameter	Symbols	Test Condition	Limits			Unit
			Min	Typ	Max	
Static						
Drain-Source Breakdown Voltage	V(BR)DSS	VGS=0V, ID=250uA	30			V
Gate-Threshold voltage*	V GS (th)	VDS=VGS, ID=250uA	1	1.55	2.2	V
Gate-body Leakage	IGSS	VDS=0V, VGS=±20V			±100	nA
Zero Gate Voltage Drain current	IDSS	VDS=30V, VGS=0V			1	uA
Drain-Source On-Resistance (a)	RDS(ON)	VGS=10V, ID=3.2A		37	60	mΩ
		VGS=4.5V, IC=2.8A		57	75	
Forward trans conductance (a)	gfs	VDS=4.5V, ID=2.5A	2.5			S
Diode forward voltage	VSD	IS=2.7A, VGS=0V		0.8	1.2	V
Continuous source-drain diode current	IS	Tc=25℃			1.4	A
Pulse diode forward current	ISM				15	A
Dynamic						
Input capacitance(b)	Ciss	VDS=15V, VGS=0V,f=1MHz		235		pF
Output capacitance(b)	Coss			45		
Reverse Transfer capacitance(b)	Crss			17		
Total gate charge	Qg	VDS=15V, VGS=10V,ID=3.4A		4.5	6.7	nC
		VDS=15V, VGS=4.5V,ID=3.4A		2.1	3.2	
Gate-source charge	Qgs			0.85		
Gate-drain charge	Qgd			0.65		
Gate resistance	Rg	F=1.0MHz	0.8	4.4	8.8	Ω
Switching (b)						
Turn-on Time	td(on)	VDD=15V, RL=5.6Ω, VGEN=4.5V, ID≈2.7A, RG=1Ω		12	20	ns
Rise time	tr			50	75	
Turn-off Time	td(off)			12	20	
Fall time	tf			22	35	
Turn-on Time	td(on)	VDD=15V, RL=5.6Ω, VGEN=10V, ID≈2.7A, RG=1Ω		5	10	
Rise time	tr			12	20	
Turn-off Time	td(off)			10	15	
Fall time	tf			5	10	

Notes:


- Pulse Test: Pulse Width ≤300us, Duty Cycles≤2%.
- These parameters have no way to verify.

Typical characteristics


Output Characteristics




Transfer Characteristics




$R_{DS(ON)}$ — I_D




$R_{DS(ON)}$ — V_{GS}




I_S — V_{SD}




Threshold Voltage



SOT-23 PACKAGE OUTLINE Plastic surface mounted package



Recommended land dimensions for SOT-23 diode. Electrode patterns for PCBs



Note:

1. Controlling dimension; in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Important Notice and Disclaimer

DOESHARE has used reasonable care in preparing the information included in this document, but DOESHARE does not warrant that such information is error free. DOESHARE assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

DOESHARE no warranty, representation or guarantee regarding the documents, circuits and products specification, DOESHARE reservation rights to make changes for any documents, products, circuits and specifications at any time without notice.

Purchasers are solely responsible for the choice, selection and use of the DOESHARE products and services described herein, and DOESHARE assumes no liability whatsoever relating to the choice, selection or use of the products and services described herein.

No license, express or implied, by implication or otherwise under any intellectual property rights of DOESHARE.

Resale of DOESHARE products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by DOESHARE for the DOESHARE product or service described herein and shall not create or extend in any manner whatsoever, any liability of DOESHARE.