

SFF1006U/SFF1006UF
SUPER FAST RECOVERY RECTIFIERS



VOLTAGE 600 Volts

CURRENT 10 Amperes

Marking and Polarity

FEATURES

- Glass passivated chip junction
 - Super fast reverse recovery time
 - Low Forward Voltage Drop for high efficiency
 - Low leakage current for high reliability
 - High frequency operation
 - Solder bath temperature 275°C maximum, 10s, per JESD22-B106
- Component in accordance to RoHS 2011/65/EU


MECHANICAL DATA

- **Case:** JEDEC TO-220AC、ITO-220AC
Molding compound meets UL94V-0 flammability rating
- **Terminals:** Lead solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked
- **Mounting position:** Any


TYPICAL APPLICATIONS

For use in switching power supplies ,high frequency inverters ,PFC booster circuit, and polarity protection applications

TO-220AC
SFF1006U



ITO-220AC
SFF1006UF



Remark:

- ①. NH=niuhang trademark;
- ②. FF=Product line code,According to actual changes
YWW=Data code,According to actual changes
EDDQK=Internal code,According to actual changes
- ③. SFF1006F/UF=Module.

Maximum Ratings (Ratings at 25°C ambient temperature unless otherwise specified)

Parameter	Symbol	SFF1006U/SFF1006UF	Unit
Maximum repetitive peak reverse voltage	V_{RRM}	600	V
Maximum average forward rectified current(see fig.1)	$I_{F(AV)}$	10	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method at rated TL)	I_{FSM}	100	A
Peak repetitive reverse current per diode at $t_p=2\mu s$ 1KHz	I_{RRM}	5	μA

Electrical Characteristics (Ratings at 25°C ambient temperature unless otherwise specified)

Parameter	Test Conditions	Symbol	SFF1006U/SFF1006UF			Unit	
			Min.	Typ.	Max.		
Instaneous forward voltage per diode (note1)	$T_A=25^\circ C$	$I_F=10 A$	V_F	--	1.40	1.70	V
	$T_A=125^\circ C$			--	1.25	1.50	
Reverse current per diode (note2)	$T_A=25^\circ C$	$V_R=V_{RRM}$ $V_R=80\%*V_{RRM}$	I_R	--	1	5	μA
	$T_A=125^\circ C$			--	0.5	2	mA
Maximum Reverse Recovery Time	$I_F=0.5A, I_R=1.0A, I_{RR}=0.25A$	T_{RR}	--	30	35	ns	
Typical junction capacitance	4V,1MHz	C_J	--	6	--	pF	

Thermal Characteristics (Ratings at 25°C ambient temperature unless otherwise specified)

Parameter	Symbol	SFF1006U/SFF1006UF	Unit
Operating junction	T_J	175	°C
Storage temperature range	T_{STD}	-55 to +175	
Typical thermal resistance (note3)	$R_{\theta JC}$	TO-220AB	°C/W
		TO-220F	
		2.5	4.5

- Notes:
1. Pulse test: 300 μs pulse width,1% duty cycle
 2. Pulse test: pulse width $\leq 40ms$
 3. Device mounted on Device mounted on 75mm x 45mm x 2.5mm Aluminum Plate Heatsink.

SFF1006U/SFF1006UF
SUPER FAST RECOVERY RECTIFIERS



RATING AND CHARACTERISTIC CURVES




Fig.1-FORWARD CURRENT DERATING CURVE




Fig.2- TYPICAL INSTANTANEOUS FORWARD




Fig.3- TYPICAL JUNCTION CAPACITANCE




Fig.4- TYPICAL REVERSE CHARACTERISTICS




Fig.5-MAX. NON-REPETITIVE SURGE CURRENT





Fig.6-REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT

SFF1006U/SFF1006UF
SUPER FAST RECOVERY RECTIFIERS



OUTLINE DRAWINGS


TO-220AC



OUTLINE DIMENSIONS(Units:mm)						
Dim.	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.80	-	10.20	9.80	-	10.40
B	15.50	-	16.05	14.95	-	15.35
C	8.40	-	9.40	8.40	-	9.40
D	4.20	-	4.70	4.20	-	4.70
E	1.15	-	1.45	1.15	-	1.45
F	12.50	-	-	12.50	-	-
G	2.30	-	2.70	2.30	-	2.70
H	0.45	-	0.55	0.30	-	0.45
J	2.50	-	4.00	3.00	-	4.50
M	2.44	-	2.64	2.44	-	2.64
R	0.70	-	1.00	0.70	-	1.00
O	3.45	-	3.85	3.75	-	4.15
P	3.00	-	3.40	2.80	-	3.20

OUTLINE DRAWINGS

ITO-220AC



OUTLINE DIMENSIONS(MILI METERS)						
Dim.	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.90	-	10.40	10.00	-	10.40
B	14.90	-	15.40	14.40	-	16.20
C	6.48	-	6.88	6.48	-	6.88
D	4.30	-	4.70	4.50	-	4.90
E	2.70	-	3.30	2.35	-	2.75
F	12.50	-	-	12.50	-	-
G	2.40	-	2.80	2.00	-	2.40
H	0.50	-	0.70	0.40	-	0.60
M	4.90	-	5.30	4.90	-	5.30
N	1.25	-	1.45	0.70	-	1.00
K	1.20	-	1.40	1.20	-	1.40
R	0.45	-	0.75	0.60	-	1.00
O	3.10	-	3.70	3.10	-	3.70
P	2.40	-	3.50	3.00	-	4.00

PACKING INFORMATION

Package Code	Package Method	Tube Size LxWxH(mm)	Quantity (pcs/Tube)	Inner Box Size LxWxH(mm)	Quantity (pcs/Inner Box)	Outer Carton Size LxWxH(mm)	Quantity (pcs/carton)
TO-220AC	Tube	530x35x8	50	560x155x55	1000	570x284x185	5000
ITO-220AC	Tube	530x35x8	50	560x155x55	1000	570x284x185	5000


SFF1006U/SFF1006UF
SUPER FAST RECOVERY RECTIFIERS



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (Tsmmax to Tp)	3°C/second max.	3°C/second max.
Preheat -Temperature Min(TS min) -Temperature Max(TS max) -Time(ts min to ts max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: -Temperature (TL) - Time (tL)	183°C 60-150 seconds	217°C 60-150 seconds
Peak Temperature(TP)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

SFF1006U/SFF1006UF
SUPER FAST RECOVERY RECTIFIERS



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from niuhang Electronics co., LTD
- Niuhan Electronics co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhan Electronics co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhan Electronics co., LTD. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Niuhan Electronics co., LTD. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Niuhan Electronics co., LTD. for any damages resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer. quality, change the internal structure and the production process Niuhan can not notify