




A				B				C				D				E				F				G											
1	性能参数																																		
	1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A																																		
	2. Rated current:3A/DC36V 额定电流:3A/DC36V																																		
	3. Power-frequency withstand voltage:2000V1min 工频耐压:2000V1min																																		
	4. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ																																		
	5. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ																																		
	6. Pressing stroke:2.50mm ± 0.10 按压行程:2.50mm ± 0.10																																		
	7. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10																																		
	8. Nut assembly torque:5-14N 螺帽装配力矩:5-14N																																		
	9. Protection level:IP67 防护等级:IP67																																		
2	10. Explosion prevention level: IK10 防暴等级: IK10																																		
	11. Working environment temperature: -20 ℃~+55 ℃ 工作环境温度: -20 ℃~+55 ℃																																		
	12. Compression torque: ≤ 4N 按压扭力: ≤4N																																		
	13. Electrical life: 500000 cycles 电气寿命: 500000 cycles																																		
	14. mechanical: 500000cycles 机械寿命: 500000cycles																																		
	15. Operation method:Self repeating form 操作方式: 自复式																																		
	16. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N																																		
	17. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下																																		
	18. LED lamp lifespan: 40000h LED寿命: 40000h																																		
	19. LED color: Blue LED颜色: 蓝色																																		
3	连接形式																																		
	1. Welding temperature of wire: 320 ± 20 ℃ 线材焊接温度: 320±20℃ Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下																																		
	2. Can be used with dedicated connectors: 可配专用接插件使用:																																		
	2.1 Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC)																																		
	2.2 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极																																		
	2.3 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极																																		
	2.4 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极																																		
	2.5 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极																																		
	2.6 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极																																		
	2.7 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极																																		
4																																			
5																																			
A4																 台普 ROC PU				COMMON TOLERANCE		UNIT		MM		PROJECTED				PRODUCT NAME:					
A3																						DRAWN BY		FUYUAN		CHECKED BY		COCO		MODEL NO: TP91939P2120BS					
A2																						DATE		2019		APPROVAL B		ALEN		Https: www.rocpu.tw					
A1																														ROC PU TECHNOLOGY CO.,LTD					
REV				DATE				REVISION DESCRIPTION				ISSUE								ANGULAR												Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			
A				B				C				D				E				F				G											

		A			B			C			D			E			F			G		
材质参数																						
10		luminous zone 发光区				PC 塑料				1												
9		LEDpin LED脚				Brass 黄铜				1				Silvering 镀银								
8		Base 底座				PA46				1												
7		Pin 引脚				Brass 黄铜				1				gold-plating 镀金								
6		Contact material 接触材质				silver alloy 银合金				1				Silvering 镀银								
5		LED Base LED基座				PC 塑料				1												
4		Arm nut 固定螺帽				Brass 黄铜				1				nickeling 镀镍								
3		Oring O型圈				Silica gel 硅胶				1												
2		Housing 外壳				SUS 不锈钢				1												
1		Key 按键				SUS 不锈钢				1												
NO 序号		Part name 部件名				Material 材料				QTY 数量				Remark 备注								

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:	
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91939P2120BS	
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw	
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD					
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR						
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission												