


Description:

This P-Channel MOSFET uses advanced trench technology and design to provide excellent $R_{DS(on)}$ with low gate charge.

It can be used in a wide variety of applications.

Features:

- 1) $V_{DS}=-30V, I_D=-50A, R_{DS(on)}<14m\Omega @V_{GS}=-10V$
- 2) Low gate charge.
- 3) Green device available.
- 4) Advanced high cell density trench technology for ultra low $R_{DS(on)}$.
- 5) Excellent package for good heat dissipation.



Absolute Maximum Ratings: ($T_C=25^\circ C$ unless otherwise noted)

Symbol	Parameter	Ratings	Units
V_{DS}	Drain-Source Voltage	-30	V
V_{GS}	Gate-Source Voltage	± 25	V
I_D	Continuous Drain Current- $T_C=25^\circ C$	-50	A
	Continuous Drain Current- $T_C=100^\circ C$	-38	
$I_{DM (pulse)}$	Drain Current – Pulsed ^(Note 1)	-220	A
P_D	Power Dissipation- $T_C=25^\circ C$	75	W
	Power Dissipation- $T_C=100^\circ C$	37.5	
T_J, T_{STG}	Operating and Storage Junction Temperature Range	-55 to +175	$^\circ C$

Thermal Characteristics:

Symbol	Parameter	Max	Units
$R_{\theta JC}$	Thermal Resistance, Junction to Case	2	$^\circ C/W$

Electrical Characteristics: ($T_C=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Off Characteristics						
BV _{DSS}	Drain-Sourtce Breakdown Voltage	V _{GS} =0V, I _D =250 μ A	-30	---	---	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{GS} =0V, V _{DS} =-30V	---	---	1	μ A
I _{GSS}	Gate-Source Leakage Current	V _{GS} =± 25V, V _{DS} =0A	---	---	± 100	nA
On Characteristics						
V _{GS(th)}	GATE-Source Threshold Voltage	V _{GS} =V _{DS} , I _D =250 μ A	-1	-1.6	-2.5	V
R _{DS(ON)}	Drain-Source On Resistance	V _{GS} =-10V, I _D =-20A	---	9.5	14	m Ω
		V _{GS} =-4.5V, I _D =-15A	---	13	21	
G _{FS}	Forward Transconductance	V _{DS} =-5V, I _D =-6A	10	22	---	S
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =-15V, V _{GS} =0V, f=1MHz	---	2350	---	pF
C _{oss}	Output Capacitance		---	380	---	
C _{rss}	Reverse Transfer Capacitance		---	285	---	
Switching Characteristics						
t _{d(on)}	Turn-On Delay Time	V _{DD} =-15V, I _D =-1A, R _L =15 Ω , R _G =2.5 Ω , V _{GS} =-10V	---	11	---	ns
t _r	Rise Time		---	24	---	ns
t _{d(off)}	Turn-Off Delay Time		---	38	---	ns
t _f	Fall Time		---	10	---	ns
Q _g	Total Gate Charge	V _{DS} =-15V, V _{GS} =-10V, I _D =-12A	---	40	---	nC
Q _{gs}	Gate-Source Charge		---	7.5	---	nC
Q _{gd}	Gate-Drain Charge		---	10	---	nC
Drain-Source Diode Characteristics						
V _{SD}	Source-Drain Diode Forward Voltage	V _{GS} =0V, I _S =-6A	---	---	-1.2	V

I_{SD}	Continuous Source Current	---	---	---	-55	A
----------	---------------------------	-----	-----	-----	-----	---

Notes: 1.Repetitive Rating: Pulse width limited by maximum junction temperature

Typical Characteristics: ($T_C=25^{\circ}\text{C}$ unless otherwise noted)

Figure1. Power Dissipation




Figure2. Drain Current




Figure3. Output Characteristics




Figure4. Transfer Characteristics




Figure5. Capacitance






 Figure6. $R_{DS(ON)}$ vs Junction Temperature

 Figure7. Max BV_{DSS} vs Junction Temperature

 Figure8. $V_{GS(th)}$ vs Junction Temperature


Figure9. Gate Charge Waveforms




Figure10. Maximum Safe Operating Area






Figure11. Normalized Maximum Transient Thermal Impedance



■ TO-252 Package information


SYMBOL	DIMENSIONS					
	INCHES			Millimeter		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A1	0.000	---	0.008	0.000	---	0.200
A2	0.087	0.091	0.094	2.200	2.300	2.400
A3	0.035	0.039	0.043	0.900	1.000	1.100
b	0.026	0.030	0.034	0.660	0.760	0.860
c	0.018	0.020	0.023	0.460	0.520	0.580
D	0.256	0.260	0.264	6.500	6.600	6.700
D1	0.203	0.209	0.215	5.150	5.300	5.450
D2	0.181	0.189	0.195	4.600	4.800	4.950
E	0.390	0.398	0.406	9.900	10.100	10.300
E1	0.236	0.240	0.244	6.000	6.100	6.200
E2	0.203	0.209	0.215	5.150	5.300	5.450
e	0.090BSC			2.286BSC		
L	0.049	0.059	0.069	1.250	1.500	1.750
L1	0.035	---	0.050	0.900	---	1.270
L2	0.055	---	0.075	1.400	---	1.900
L3	0.240	0.310	0.039	0.600	0.800	1.000
L4	0.114REF			2.900REF		
θ	0°	---	10°	0°	---	10°

NOTE:

- 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
- 2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
- 3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.