

**AMG PP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Efficient machine and facility operation calls for fail-safe and maintenance-friendly control voltage distribution that can be installed in a time and space-saving manner.

With the new maxGUARD system, the terminal blocks (previously installed separately) for distributing potential to the outputs of the electronic load monitors become an integral part of a 24 V DC control voltage distribution system.

The innovative combination of load monitoring and potential distribution saves time during installation, increases safety against failure and reduces the amount of space required on the terminal rail by 50%.

**General ordering data**

| Version    | Partition plate            |
|------------|----------------------------|
| Order No.  | <a href="#">2123000000</a> |
| Type       | AMG PP                     |
| GTIN (EAN) | 4050118425338              |
| Qty.       | 40 pc(s).                  |

**AMG PP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 96.5 mm  | Depth (inches)  | 3.799 inch |
| Height     | 125 mm   | Height (inches) | 4.921 inch |
| Width      | 6.1 mm   | Width (inches)  | 0.24 inch  |
| Net weight | 13.983 g |                 |            |

**Temperatures**

|                     |                |                       |                |
|---------------------|----------------|-----------------------|----------------|
| Storage temperature | -40 °C...85 °C | Operating temperature | -25 °C...55 °C |
|---------------------|----------------|-----------------------|----------------|

**General data**

|                   |     |                   |      |
|-------------------|-----|-------------------|------|
| Conformal coating | Yes | Protection degree | IP20 |
|-------------------|-----|-------------------|------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000886    | ETIM 7.0    | EC000886    |
| ETIM 8.0    | EC000886    | ETIM 9.0    | EC000886    |
| ECLASS 9.0  | 27-14-11-33 | ECLASS 9.1  | 27-14-11-33 |
| ECLASS 10.0 | 27-14-11-33 | ECLASS 11.0 | 27-14-11-33 |
| ECLASS 12.0 | 27-14-11-33 | ECLASS 13.0 | 27250301    |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                                             |                                                                                     |
|---------------------------------------------|-------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Declaration of Conformity</a>                                           |
| Engineering Data                            | <a href="#">CAD data – STEP</a>                                                     |
| Engineering Data                            | <a href="#">Zuken E3.S</a>                                                          |
| User Documentation                          | <a href="#">Operating instructions / leaflet</a><br><a href="#">Manual_maxGUARD</a> |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                            |