

## Low Side Chopper 600 V, 400 A, DIAP IGBT Power Module (Trench Field Stop IGBT)



Dual INT-A-PAK

PRIMARY CHARACTERISTICS	
<b>IGBT Q1</b>	
$V_{CES}$	600 V
$I_C$ DC at 80 °C	375 A
$V_{CE(on)}$ (typical) at 400 A, 25 °C	1.67 V
<b>CHOPPER DIODE D2</b>	
$V_{RRM}$	600 V
$I_F$ DC at 80 °C	278 A
$V_{FM}$ (typical) at 400 A, 25 °C	1.61 V
$t_{rr}$ at 400 A, 25 °C	141 ns
<b>ANTIPARALLEL DIODE D1</b>	
$V_{RRM}$	600 V
$I_F$ DC at 80 °C	142 A
$V_{FM}$ (typical) at 200 A, 25 °C	1.56 V
$t_{rr}$ at 200 A, 25 °C	120 ns
Package	Dual INT-A-PAK
Circuit	Low side chopper

**FEATURES**

- Trench Field Stop IGBT technology
- 6  $\mu$ s short circuit capability
- Low  $V_{CE(on)}$
- Square RBSOA
- FRED Pt® antiparallel diode with ultrasoft reverse recovery characteristics
- Industry standard package
- Al<sub>2</sub>O<sub>3</sub> DBC
- UL pending
- Designed for industrial level
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

**BENEFITS**

- Increased operating efficiency
- Direct mounting on heatsink
- Very low junction to case thermal resistance

ABSOLUTE MAXIMUM RATINGS				
PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
<b>IGBT Q1</b>				
Collector to emitter voltage	$V_{CES}$		600	V
Continuous collector current	$I_C$ <sup>(1)</sup>	$T_C = 25\text{ °C}$	492	A
		$T_C = 80\text{ °C}$	375	
Pulsed collector current	$I_{CM}$	$T_p = 6\text{ ms, square pulse}$	850	
Clamped inductive load current	$I_{LM}$		693	
Gate to emitter voltage	$V_{GE}$		$\pm 20$	V
Maximum power dissipation	$P_D$	$T_C = 25\text{ °C}$	1363	W
		$T_C = 80\text{ °C}$	864	
<b>DIODE D2</b>				
Chopper diode continuous forward current	$I_F$	$T_C = 25\text{ °C}$	374	A
		$T_C = 80\text{ °C}$	278	
Single pulse forward current	$I_{FSM}$	10 ms sine or 6 ms rectangular pulse, $T_J = 25\text{ °C}$	1415	
Maximum power dissipation	$P_D$	$T_C = 25\text{ °C}$	652	W
		$T_C = 80\text{ °C}$	413	
<b>DIODE D1</b>				
Antiparallel diode continuous forward current	$I_F$	$T_C = 25\text{ °C}$	192	A
		$T_C = 80\text{ °C}$	142	
Single pulse forward current	$I_{FSM}$	10 ms sine or 6 ms rectangular pulse, $T_J = 25\text{ °C}$	725	
Maximum power dissipation	$P_D$	$T_C = 25\text{ °C}$	312	W
		$T_C = 80\text{ °C}$	198	
RMS isolation voltage	$V_{ISOL}$	Any terminal to case ( $V_{RMS} t = 1\text{ s, } T_J = 25\text{ °C}$ )	3500	V
Storage temperature range	$T_{STG}$		-40 to 150	°C
Operating junction temperature range	$T_J$		-40 to +175	°C

**Note**

<sup>(1)</sup> Maximum continuous collector current must be limited to 500 A to do not exceed the maximum temperature of terminals



<b>ELECTRICAL SPECIFICATIONS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
<b>IGBT Q1</b>						
Collector to emitter breakdown voltage	$V_{BR(CES)}$	$V_{GE} = 0\text{ V}, I_C = 500\text{ }\mu\text{A}$	600	-	-	V
Collector to emitter voltage	$V_{CE(on)}$	$V_{GE} = 15\text{ V}, I_C = 300\text{ A}$	-	1.48	-	
		$V_{GE} = 15\text{ V}, I_C = 400\text{ A}$	-	1.67	2.0	
		$V_{GE} = 15\text{ V}, I_C = 300\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	1.64	-	
		$V_{GE} = 15\text{ V}, I_C = 400\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	1.93	-	
Gate threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}, I_C = 6.4\text{ mA}$	4.6	5.9	7	
		$V_{CE} = V_{GE}, I_C = 6.4\text{ mA}, T_J = 125\text{ }^\circ\text{C}$	-	4.6	-	
Temperature coefficient of threshold voltage	$\Delta V_{GE(th)}/\Delta T$	$V_{CE} = V_{GE}, I_C = 6.4\text{ mA}, (25\text{ }^\circ\text{C to } 125\text{ }^\circ\text{C})$	-	-13	-	mV/°C
Forward transconductance	$g_{fe}$	$V_{CE} = 20\text{ V}, I_C = 400\text{ A}$	-	70	-	mS
Transfer characteristics	$V_{GE}$	$V_{CE} = 20\text{ V}, I_C = 400\text{ A}$	-	9.1	-	V
Collector to emitter leakage current	$I_{CES}$	$V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}$	-	0.2	20	$\mu\text{A}$
		$V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}, T_J = 150\text{ }^\circ\text{C}$	-	1.6	-	mA
Gate to emitter leakage current	$I_{GES}$	$V_{GE} = \pm 20\text{ V}$	-	-	$\pm 1200$	nA
<b>DIODE D1</b>						
Antiparallel diode forward voltage drop	$V_{FM}$	$I_{FM} = 100\text{ A}$	-	1.32	-	V
		$I_{FM} = 200\text{ A}$	-	1.56	1.82	
		$I_{FM} = 100\text{ A}, T_J = 150\text{ }^\circ\text{C}$	-	1.1	-	
		$I_{FM} = 200\text{ A}, T_J = 150\text{ }^\circ\text{C}$	-	1.42	-	
<b>DIODE D2</b>						
Blocking voltage	$V_{RRM}$	$I_R = 500\text{ }\mu\text{A}$	600	-	-	V
Leakage current	$I_{RRM}$	$V_R = 600\text{ V}$	-	0.2	15	$\mu\text{A}$
		$V_R = 600\text{ V}, T_J = 150\text{ }^\circ\text{C}$	-	2.8	-	mA
Chopper diode forward voltage drop	$V_{FM}$	$I_{FM} = 300\text{ A}$	-	1.48	-	V
		$I_{FM} = 400\text{ A}$	-	1.61	1.92	
		$I_{FM} = 300\text{ A}, T_J = 150\text{ }^\circ\text{C}$	-	1.34	-	
		$I_{FM} = 400\text{ A}, T_J = 150\text{ }^\circ\text{C}$	-	1.51	-	

<b>SWITCHING CHARACTERISTICS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)							
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS	
<b>IGBT Q1</b>							
Total gate charge (turn-on)	$Q_g$	$I_C = 400\text{ A}, V_{CC} = 480\text{ V}, V_{GE} = 15\text{ V}$	-	1970	-	nC	
Gate to emitter charge (turn-on)	$Q_{ge}$		-	144	-		
Gate to collector charge (turn-on)	$Q_{gc}$		-	1240	-		
Turn-off switching energy	$E_{off}$	$R_{g(off)} = 1\text{ }\Omega$	$I_C = 300\text{ A}, V_{CC} = 300\text{ V}, V_{GE} = \pm 15\text{ V}, L = 500\text{ }\mu\text{H}, T_J = 25\text{ }^\circ\text{C}$	-	12.9	-	mJ
Turn-off delay time	$t_{d(off)}$			-	594	-	ns
Fall time	$t_f$			-	77	-	ns
Turn-on switching energy	$E_{on}$			-	12.8	-	mJ
Turn-on delay time	$t_{d(on)}$	$R_{g(on)} = 6.8\text{ }\Omega$	$I_C = 300\text{ A}, V_{CC} = 300\text{ V}, V_{GE} = \pm 15\text{ V}, L = 500\text{ }\mu\text{H}, T_J = 25\text{ }^\circ\text{C}$	-	337	-	ns
Rise time	$t_r$			-	197	-	ns
Turn-off switching energy	$E_{off}$	$R_{g(off)} = 1\text{ }\Omega$	$I_C = 300\text{ A}, V_{CC} = 300\text{ V}, V_{GE} = \pm 15\text{ V}, L = 500\text{ }\mu\text{H}, T_J = 125\text{ }^\circ\text{C}$	-	14.7	-	mJ
Turn-off delay time	$t_{d(off)}$			-	638	-	ns
Fall time	$T_f$			-	91	-	ns
Turn-on switching energy	$E_{on}$	$R_{g(on)} = 6.8\text{ }\Omega$	$I_C = 300\text{ A}, V_{CC} = 300\text{ V}, V_{GE} = \pm 15\text{ V}, L = 500\text{ }\mu\text{H}, T_J = 125\text{ }^\circ\text{C}$	-	13.4	-	mJ
Turn-on delay time	$t_{d(on)}$			-	339	-	ns
Rise time	$t_r$			-	204	-	ns



<b>SWITCHING CHARACTERISTICS</b> ( $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)								
PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNITS	
Turn-off switching energy	$E_{off}$	$R_{g(off)} = 1\ \Omega$	$I_C = 400\text{ A}, V_{CC} = 300\text{ V}, V_{GE} = \pm 15\text{ V}, L = 500\ \mu\text{H}, T_J = 25\text{ }^\circ\text{C}$	-	19.3	-	mJ	
Turn-off delay time	$t_{d(off)}$			-	593	-	ns	
Fall time	$t_f$			-	82	-		
Turn-on switching energy	$E_{on}$	$R_{g(on)} = 6.8\ \Omega$		$I_C = 400\text{ A}, V_{CC} = 300\text{ V}, V_{GE} = \pm 15\text{ V}, L = 500\ \mu\text{H}, T_J = 25\text{ }^\circ\text{C}$	-	15.6	-	mJ
Turn-on delay time	$t_{d(on)}$				-	354	-	ns
Rise time	$t_r$				-	238	-	
Turn-off switching energy	$E_{off}$	$R_{g(off)} = 1\ \Omega$	$I_C = 400\text{ A}, V_{CC} = 300\text{ V}, V_{GE} = \pm 15\text{ V}, L = 500\ \mu\text{H}, T_J = 125\text{ }^\circ\text{C}$		-	21.2	-	mJ
Turn-off delay time	$t_{d(off)}$				-	631	-	ns
Fall time	$T_f$				-	92	-	
Turn-on switching energy	$E_{on}$	$R_{g(on)} = 6.8\ \Omega$		$I_C = 400\text{ A}, V_{CC} = 300\text{ V}, V_{GE} = \pm 15\text{ V}, L = 500\ \mu\text{H}, T_J = 125\text{ }^\circ\text{C}$	-	17.2	-	mJ
Turn-on delay time	$t_{d(on)}$				-	365	-	ns
Rise time	$t_r$				-	246	-	
Reverse bias safe operating area	RBSOA	$T_J = 175\text{ }^\circ\text{C}, I_C = 693\text{ A}, R_g = 10\ \Omega, V_{GE} = 15\text{ V to } 0\text{ V}, V_{CC} = 400\text{ V}, V_p = 600\text{ V}$			Fullsquare			
Short circuit safe operating area <sup>(1)(2)</sup>	SCSOA	$T_J = 150\text{ }^\circ\text{C}, V_{CC} = 360\text{ V}, V_{GE} = 15\text{ V}$			-	-	6	$\mu\text{s}$
<b>DIODE D2</b>								
Diode reverse recovery time	$t_{rr}$	$I_F = 400\text{ A}, V_{CC} = 400\text{ V}, T_J = 25\text{ }^\circ\text{C}, dl/dt = 1000\text{ A}/\mu\text{s},$	-	141	-	ns		
Diode peak reverse current	$I_{rr}$		-	41	-	A		
Diode recovery charge	$Q_{rr}$		-	3.2	-	$\mu\text{C}$		
Diode reverse recovery time	$t_{rr}$	$I_F = 400\text{ A}, V_{CC} = 400\text{ V}, T_J = 125\text{ }^\circ\text{C}, dl/dt = 1000\text{ A}/\mu\text{s},$	-	230	-	ns		
Diode peak reverse current	$I_{rr}$		-	77	-	A		
Diode recovery charge	$Q_{rr}$		-	10.2	-	$\mu\text{C}$		
<b>DIODE D1</b>								
Diode reverse recovery time	$t_{rr}$	$I_F = 200\text{ A}, V_R = 400\text{ V}, T_J = 25\text{ }^\circ\text{C}, dl/dt = 1000\text{ A}/\mu\text{s},$	-	120	-	ns		
Diode peak reverse current	$I_{rr}$		-	28	-	A		
Diode recovery charge	$Q_{rr}$		-	2.2	-	$\mu\text{C}$		
Diode reverse recovery time	$t_{rr}$	$I_F = 200\text{ A}, V_R = 400\text{ V}, T_J = 125\text{ }^\circ\text{C}, dl/dt = 1000\text{ A}/\mu\text{s},$	-	165	-	ns		
Diode peak reverse current	$I_{rr}$		-	90	-	A		
Diode recovery charge	$Q_{rr}$		-	9.1	-	$\mu\text{C}$		

**Notes**

- (1) Not subject to production test - verified by design / characterization
- (2) Allowed number of short circuits: < 1000; time between short circuits: > 1 s

<b>THERMAL AND MECHANICAL SPECIFICATIONS</b>						
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	
Operating junction temperature range	$T_J$	-40	-	175	$^\circ\text{C}$	
Storage temperature range	$T_{Stg}$	-40	-	150		
Thermal resistance, junction to case per leg	Q1 IGBT	$R_{thJC}$	-	-	0.11	$^\circ\text{C}/\text{W}$
	D1 diode		-	-	0.48	
	D2 diode		-	-	0.23	
Thermal resistance, case to sink per module	$R_{thCS}$	-	0.05	-		
Mounting torque	Power terminal screw: M6	2.5	-	5.0	Nm	
	Mounting screw: M6	3.0	-	5.0		
Weight		-	300	-	g	




Fig. 1 - Typical IGBT Output Characteristics,  $V_{GE} = 15\text{ V}$




Fig. 4 - Typical IGBT Transfer Characteristics




Fig. 2 - Typical IGBT Output Characteristics,  $T_J = 125\text{ °C}$




Fig. 5 - Typical IGBT Gate Threshold Voltage




Fig. 3 - Maximum IGBT Continuous Collector Current vs. Case Temperature




Fig. 6 - Typical IGBT Zero Gate Voltage Collector Current




Fig. 7 - Typical IGBT Energy Loss vs.  $I_C$  with Freewheeling Diode  
 $T_J = 125\text{ }^\circ\text{C}$ ,  $V_{CC} = 300\text{ V}$ ,  $R_{g(on)} = 6.8\ \Omega$ ,  $R_{g(off)} = 1\ \Omega$   
 $V_{GE} = +15\text{ V}/-15\text{ V}$ ,  $L = 500\ \mu\text{H}$




Fig. 10 - Typical Trench IGBT Gate Charge vs. Gate to Emitter Voltage




Fig. 8 - Typical Trench IGBT Switching Time vs.  $I_C$  with Freewheeling Diode  
 $T_J = 125\text{ }^\circ\text{C}$ ,  $V_{CC} = 300\text{ V}$ ,  $R_{g(on)} = 6.8\ \Omega$ ,  $R_{g(off)} = 1\ \Omega$ ,  
 $V_{GE} = +15\text{ V}/-15\text{ V}$ ,  $L = 500\ \mu\text{H}$




Fig. 11 - Typical D2 Diode Forward Characteristics




Fig. 9 - Typical Trench IGBT Energy Loss vs.  $R_g$  with Freewheeling Diode  
 $T_J = 125\text{ }^\circ\text{C}$ ,  $V_{CC} = 300\text{ V}$ ,  $I_C = 400\text{ A}$ ,  $V_{GE} = +15\text{ V}/-15\text{ V}$ ,  $L = 500\ \mu\text{H}$




Fig. 12 - Maximum D2 Diode Continuous Forward Current vs. Case Temperature




Fig. 13 - Typical D1 Diode Forward Characteristics




Fig. 16 - Typical Diode Reverse Recovery Current vs.  $di_F/dt$   
 $I_F = 400 \text{ A}, V_{CC} = 400 \text{ V}$




Fig. 14 - Maximum D1 Diode Continuous Forward Current vs. Case Temperature




Fig. 17 - Typical Diode Reverse Recovery Charge vs.  $di_F/dt$   
 $I_F = 400 \text{ A}, V_{CC} = 400 \text{ V}$




Fig. 15 - Typical Diode Reverse Recovery Time vs.  $di_F/dt$   
 $I_F = 400 \text{ A}, V_{CC} = 400 \text{ V}$




Fig. 18 - IGBT Reverse BIAS SOA  
 $T_J = 175 \text{ °C}, I_C = 693 \text{ A}, R_g = 10 \text{ } \Omega, V_{GE} = +15 \text{ V} / 0 \text{ V},$   
 $V_{CC} = 400 \text{ V}, V_p = 600 \text{ V}$




Fig. 19 - IGBT Safe Operating Area




Fig. 20 - Maximum IGBT Thermal Impedance  $Z_{thJC}$  Characteristics





Fig. 21 - Maximum D1 Diode Thermal Impedance  $Z_{thJC}$  Characteristics


 Fig. 22 - Maximum D2 Diode Thermal Impedance  $Z_{thJC}$  Characteristics

**ORDERING INFORMATION TABLE**

Device code	<b>VS-</b>	<b>G</b>	<b>T</b>	<b>400</b>	<b>L</b>	<b>H</b>	<b>060</b>	<b>N</b>
	①	②	③	④	⑤	⑥	⑦	⑧


- 1** - Vishay Semiconductors product
- 2** - Insulated gate bipolar transistor (IGBT)
- 3** - T = Trench Field Stop IGBT technology
- 4** - Current rating (400 = 400 A)
- 5** - Circuit configuration (L = low side chopper)
- 6** - Package indicator (H = Dual INT-A-PAK)
- 7** - Voltage rating (060 = 600 V)
- 8** - N = none

LINKS TO RELATED DOCUMENTS	
Dimensions	<a href="http://www.vishay.com/doc?95525">www.vishay.com/doc?95525</a>
Application Note	<a href="http://www.vishay.com/doc?95553">www.vishay.com/doc?95553</a>






**CIRCUIT CONFIGURATION**




**DIMENSIONS** in millimeters





## Double INT-A-PAK

**DIMENSIONS** in millimeters (inches)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.