

TINA2-W

~45° wide beam. Assembly with holder, installation tape and location pins.

SPECIFICATION:

Dimensions	Ø 16.0 mm
Height	9.5 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
TINA2-W-XP	Single lens	PMMA	clear	
TINA2-HLD-BLK	Holder	PC	black	
TINA-TAPE3	Tape	Acrylic foam	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA12378_TINA2-W	Single lens	4140	230	230	8.3
» Box size:					







See also our general installation guide: www.ledil.com/installation_guide



OPTICAL RESULTS (MEASURED):





LED XD16
FWHM / FWTM 40.0° / 61.0°
Efficiency 83 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON CZ
FWHM / FWTM 39.0° / 61.0°
Efficiency 92 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON TX
FWHM / FWTM 49.0° / 68.0°
Efficiency 88 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NVSxx19B/NVSxx19C
FWHM / FWTM 52.0° / 70.0°
Efficiency 87 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OPTICAL RESULTS (MEASURED):





LED NWSx229A
 FWHM / FWTM 55.0° / 77.0°
 Efficiency 84 %
 Peak intensity 1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED OSLON Square EC
 FWHM / FWTM 52.0° / 72.0°
 Efficiency 85 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED OSLON Square EC
 FWHM / FWTM 50.0° / 73.0°
 Efficiency 84 %
 Peak intensity 1.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED OSLON SSL 150
 FWHM / FWTM 53.0° / 70.0°
 Efficiency 84 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):

OSRAM

Opto Semiconductors

LED SFH 4170S
FWHM / FWTM 38.0° / 61.0°
Efficiency %
LEDs/each optic 1
Light colour IR
Required components:

OSRAM

Opto Semiconductors

LED SFH 4180S
FWHM / FWTM 34.0° / 60.0°
Efficiency %
LEDs/each optic 1
Light colour IR
Required components:

OSRAM



Opto Semiconductors

LED SFH 4715S
FWHM / FWTM 36.0° / 80.0°
Efficiency %
LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR


LED Z5M3
FWHM / FWTM 50.0° / 72.0°
Efficiency 86 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):




LED XB-D
FWHM / FWTM 40.0° / 64.0°
Efficiency 89 %
Peak intensity 1.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED XE-G
FWHM / FWTM 54.0° / 66.0°
Efficiency 92 %
Peak intensity 1.4 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED XQ-E HI
FWHM / FWTM 42.0° / 64.0°
Efficiency 92 %
Peak intensity 1.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON C
FWHM / FWTM 44.0° / 65.0°
Efficiency 91 %
Peak intensity 1.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):




LED LUXEON IR Compact
FWHM / FWTM 51.0° / 64.0°
Efficiency 84 %
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON Rubix
FWHM / FWTM 47.0° / 68.0°
Efficiency 93 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON Rubix
FWHM / FWTM 47.0° / 68.0°
Efficiency 93 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour Blue
Required components:




LED LUXEON Rubix
FWHM / FWTM 45.0° / 68.0°
Efficiency 93 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour Red
Required components:




OPTICAL RESULTS (SIMULATED):



LED LUXEON Z ES
FWHM / FWTM 43.0° / 62.0°
Efficiency 93 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NCSxE17A
FWHM / FWTM 29.0° / 56.0°
Efficiency 90 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




Opto Semiconductors

LED SFH 4770S
FWHM / FWTM 32.0° / 61.0°
Efficiency 88 %
LEDs/each optic 1
Light colour White
Required components:



Opto Semiconductors

LED Synios P2720 1 mm
FWHM / FWTM 31.0° / 60.0°
Efficiency 92 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):

OSRAM

Opto Semiconductors


LED Synios P2720 1/2 mm
FWHM / FWTM 30.0° / 58.0°
Efficiency 92 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM


Opto Semiconductors

LED Synios P2720 1/4 mm
FWHM / FWTM 31.0° / 60.0°
Efficiency 92 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SAMSUNG

LED LH181B
FWHM / FWTM 43.0° / 61.0°
Efficiency 93 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)